North Lily Heap Leach Facility Closure Report

Permit No. UGW230001 North Lily Mining Heap Leach Facility Juab County, Utah March 2002

Prepared for:

State of Utah
Utah Division of Water Quality
P.O. Box 14487
288 North 1460 West
Salt Lake City, Utah 84114-4870

Prepared by:

JBR Environmental Consultants, Inc. 8160 South Highland Drive Sandy, Utah 84093 (801) 943-4144

TABLE OF CONTENTS

1.0	Introd	uction	1
2.0	Heap	Leach Closure and Reclamation	1
3.0	Hazar	dous Materials Collection and Disposal	2
4.0	Drain	Field	2
5.0	Class	IIIb Industrial Landfill	4
6.0	Leach	ate Water Quality and Quantity	4
7.0	Heap	Leach Drainage Monitoring	4
8.0	Refer	ences	5
		LIST OF TABLES	
Table	1	Granite Seed Company Seed Mix	
Table	2	Percolation Rates at North Lily	
		LIST OF FIGURES	
Figure	e 1	Drain Field Design and Associated Topographic Map	
Figure	€2	Typical Trench Layout and Lateral Connection	
Figure	e 3	Typical Lateral Trench Cross-section	
Figure	e 4	Distribution Box Design and Dimensions	
Figure	e 5	Drain Field As-Built	

LIST OF APPENDICES

Appendix A	Site Photographs
Appendix B	Nevada Meteoric Water Mobility Procedure
Appendix C	Hazardous Materials Handling and Disposal Documentation
Appendix D	Draft Amended Ground Water Discharge Permit, No. UGW230001
Appendix E	Utah Underground Injection Control Program Inventory Information
Appendix F	Class IIIb Industrial Landfill Permit by Rule And Recorders Office Document
Appendix G	Heap Drainage Water Quality Data
Appendix H	Heap Drainage Water Quantity Data

1.0 Introduction and Summary

The North Lily Heap Leach Facility opened for operation in 1986 and continued through 1996. Prior to site closure, there were two fuel tanks, one diesel and one gasoline (both emptied and sold off as surplus), one caustic tank (residue removed, rinsed and steam cleaned, crushed and placed into on-site landfill), a lab/office trailer (crushed and placed into landfill following removal of all lab chemicals and equipment), a mill building (demolished and placed into landfill following salvaging, recycling, or proper disposal of all contents), a propane tank (removed from site), one material shed (demolished), pregnant pond (filled in and graded), barren pond (class IIIb landfill), overflow pond (filled in and graded), buried drain lines (removed), and electrical facilities (removed) (Figure 1). Following completion of closure activities, the entire site was fenced off for the safety of the public. All of these components were required to be removed, demolished and/or reclaimed, or installed in order to fulfill the Site Closure Plan. Photographs that depict the site and the reclamation process can be found in Appendix A.

2.0 Heap Leach Closure and Reclamation

The first step for closure was to restore the pad-margin leachate collection system. To do this, the under drain feeder solution collection system was restored and the perimeter drain system was replaced. The process involved the re-opening of the trench on the west side of the heap down to the heap liner, placing pea gravel into the trench, laying down a layer of pervious geofabric, installing a new perforated 4" PVC drain pipe, placing a second layer of geofabric on the pipe, adding more gravel onto the fabric, placing a third and final layer of geofabric on top of the gravel, and then covering the trench with spent leach material. After the peripheral drain was restored, the pad-margin was regraded to allow surface water runoff to drain from the pad surface to the adjacent terrain and reduce infiltration of precipitation and, thereby, the volume of water flowing from the pad to the pregnant solution pond.

Prior to the pad regrading, the leach pad material was sampled and analyzed for leachable trace metals, major anions, and cyanide using the Nevada Meteoric Water Mobility Procedure (Appendix B). This indicated no solutes present in concentrations that would adversely affect vegetation, soil, or water quality due to runoff leaving the margins of the lined leach pad.

Leachate which continued to flow to the pregnant solution pond through the reconstructed peripheral drain line was pumped into an enhanced evaporation system to reduce the volume of the collected leachate. This continued until the infiltration gallery/drain field was completed. When the drain field was completed, the perimeter drain line was connected to a concrete distribution box adjacent to the pad margin (No. 1 distribution box) (Figure 1), from which point the leachate would enter the post closure fluid management system (PCFMS).

The PCFMS begins with a gravity-fed, buried 4-inch line that extends from the No. 1 distribution box to a second distribution box (No. 2 distribution box) located adjacent to the drain/field. From the No. 2 distribution box leachate is carried in a second gravity-fed line to the drain field (Appendix A #1-3). These distribution boxes, each with the capacity of 1250 gallons each and the ability to be cleaned out, are designed to eliminate fines from entering the drain field by allowing the suspended sediment in pad leachate time to settle. Since shortly after construction of the pad margin was completed the drain down water has been non-turbid, which suggests that the perimeter drain line has been successful in its construction and that the sediment in the distribution boxes is minimal.

The heap leach pad itself was regraded using a D-8 Cat Dozer and a DS-155 Komatsu Dozer so that slopes were no more than 3h:1v and then reshaped. This was done to accomplish two objectives. The first was to establish a surface water drainage pattern and eliminate pooling of precipitation-derived water on the heap itself. The second objective was to have the heap blend into the surrounding topography. Once the regrading was completed, the area was ripped using D-6 and D-8 Cats to enable the approved seed mix a better chance to germinate and to prevent erosion. Then, a JBR employee, using an ATV-mounted broadcast seeder (Appendix A #4), applied a Granite Company Seed Mix to the heap (Table 1). To help aid in plant growth, composted cow manure from Silver City Compost was applied at a rate of 10 tons/acre. Because of the presence of whitetop clover and spotted knapweed, which are noxious weeds, a pesticide was sprayed wherever the weeds were located on the North Lily property. This was done in an effort to reduce the seed source from these weeds. (Appendix A #5).

3.0 Hazardous Materials Collection and Disposal

Prior to commencement of demolition of site components and pond closure, the facility was surveyed by a JBR hazardous materials specialist for potentially hazardous materials. All materials were documented, identified, inventoried, collected and properly packaged by trained personnel, profiled and manifested, removed from the site by licensed transporters, and taken to disposal facilities. All categorized waste was transported to Safety Kleens' Aragonite Facility Aptus, Utah, and Grassy Mountain Facility Clive, Utah, and Superior Special Services, Inc. Phoenix, Az. Caustic soda solution was transported to Kennecotts' Barneys Canyon gold mine for use in their heap leach solutions. Hazardous Materials Handling and Disposal Documentation is provided in Appendix C.

4.0 Drain Field

The drain field was designed in accordance with rule R317-5, Large Underground Wastewater Disposal Systems. The first step was to come up with a conceptual drain field design by estimating leachate discharge rates, identifying the preferred drain field location

(at a site that was both on North Lily property and would allow gravity flow from the pad), and conducting preliminary percolation tests.

When the conceptual design was approved by DWQ, final design began. A JBR geologist conducted thirteen percolation tests at various locations on the property during multiple site visits from September 2000 to February 2001. These tests were performed to ascertain the best location and size of the proposed drain field. All of the percolation test pits (designated T.P.), shown on Figure 1, were constructed in compliance with the Administrative Rules for a Large Underground Wastewater Disposal System R-317-5-4, Percolation Tests. Using the percolation data, an area defined by six test pits was selected as the footprint of the drain field (Figure 1). The lowest percolation rate, within this footprint, of 1.852 x10-3 cm/sec (T.P. Z) was used to calculate the appropriate application area for the drain field (Table 2).

The drain field was designed to have the capability of dispersing up to 6.41 gallons per minute (gpm), as approved by Department of Environmental Quality, Division of Water Quality (Appendix D). A Utah Underground Injection Control Program Inventory Information packet was completed and submitted to the Mr. Jerry Jackson at the Division of Water Quality on May 8, 2001 (Appendix E). When the leach field design was approved (Figures 1,2,3, & 4), construction commenced and was carried out in accordance with the Administrative Rules for a Large Underground Wastewater Disposal System R-317-5. On March 16, 2001, Blue Rock Excavating, Inc. grubbed the selected drain field area of vegetation and leveled the site to a uniform elevation with a D-8 Cat (85 feet per the site datum). During May 25-29, 2001, Western Excavating installed the drain field using a cat 322 track hoe, 2800 track hoe, and 950 loader. Excavation of the main feeder trenches was carried out first and the solid schedule 40 PVC lines were laid down with PVC crosses and tees connected along the solid line where the perforated schedule 40 PVC laterals would be connected. Then the lateral line trenches were excavated, 4-6 inches of 3/8 inch (nominal) gravel was placed in each trench, and the perforated pipe was installed on the gravel layer. Another layer of 4 - 6 inches of gravel was placed on top of the perforated pipe and then a pervious geofabric was placed on top of the gravel. This geofabric prevents fines, derived from the overlying soil, from filling in the voids of the gravel, which could diminish the capacity of the overall system. Then, a layer of hand-placed native soil was placed over the geofabric to a depth of at least 6 inches. The last step in the trench construction process was to machine-fill the trench with native material and crown the top to allow for settling (Appendix A #4-9).

The No. 2 distribution box (made of reinforced concrete and with a 1250-gallon capacity) and gravity-fed drain lines were installed next. The No. 1 distribution box is accessible by an access manhole door on top of the box. The No. 2 distribution box was buried, with DWQ approval because of the depth of the system, the necessity to contour the surface to deter waters from pooling above the drain field, and the cost of additional risers to allow access. For ease of location of the distribution box, the box has been marked on the

surface with a tee post. On May 5, 2001, an as-built survey was conducted and is included in this report as Figure 5.

5.0 Class IIIb On-Site Landfill

In order to meet DOGM's requirements for site reclamation, non-hazardous materials, consisting primarily of demolition debris, needed to be disposed. The most economical solution was to create an on-site landfill. On May 7, 2001, North Lily was granted approval for use of the former barren solution pond through a Permit by Rule as a Class IIIb Landfill by the Division of Solid and Hazardous Waste (Appendix F). The barren pond was chosen as the landfill site because it was no longer in use for water retention, it had the adequate volumemetric capacity to contain the estimated quantity of debris to be generated, and was adjacent to the mill building from which most demolition debris would be generated. Building materials from the mill and lab/office trailer consisting of steel, wood, crushed concrete foundation, fiberglass insulation, electrical wire, plumbing, and aluminum siding, was all placed in the landfill (Appendix A #11-13). The caustic tank, which had been cleaned, was then crushed and placed in the landfill along with miscellaneous items, pipes, hoses, and fittings found around the site. Once all of this material was deposited into the landfill, an earthen cover was placed on top and the surface was graded so that water would not pool over the landfill (Appendix A #14-16).

The entire area has been fenced off using 5.5 - 6.0 foot t-posts and Oklahoma 2 point barbed wire.

To comply with the R315 regulations, the Class IIIb Landfill was registered with the Juab County Recorders Office, as No. 00224218.

6.0 Leachate Water Quality and Quantity

Water quality has improved since solution application to the pad ceased. North Lily's Ground Water Discharge Permit has been modified to allow subsurface disposal via the drain field. A copy of water quality analyses over the last two years is included in Appendix G. The water flow from the heap was measured daily before the construction of the drain field and measured weekly at the No. 1 distribution box once the drain field was constructed. The flow has been below a rate of three gallons/minute since early January 2001 (Appendix H).

7.0 Monitoring

Monitoring of the Heap Leach effluent discharge for both instantaneous and cumulative flow will be conducted on a weekly basis and will be reported to the Division of Oil Gas and

Mining and the Division of Water Quality on a quarterly basis. Samples of the discharge will be taken from the draindown fluid sampling port at the number 1 distribution box quarterly. The results will be submitted in quarterly monitoring reports on April 15, July 15, October 15, and January 15 of each year until the site has been determined to be closed by DWQ. The fourth Quarter 2001 monitoring report has been submitted to DOGM and DWQ (JBR, 2002).

8.0 References

JBR, 2002. North Lily mining Company Ltd., North Lily Heap Leach Discharge Report. Prepared by JBR Environmental Consultants, Inc.

Table 1

Granite Seed Company Seed Mix

North Lily Mining Company Ltd TABLE 1

Granite Compa	Granite Company Seed Mixture to Heap Leach					
Plant Descr	ription	Amount (lbs)				
Agropyron Cristatum	Crested Wheatgrass	20				
Agropyron Dasystachyum	Thickspike Wheatgrass	40				
Agropyron Intermedium	Intermediate Wheatgrass	20				
Agropyron Spicatum	Bluebunch Wheatgrass	40				
Artemisia Tri Vaseyana	Mountain Big Sagebrush	2				
Chrysothamnus Nauseosus	Rubber Rabbitbrush	10				
Dactylis Glomerata	Orchardgrass	10				
Elymus Cinereus	Great Basin Wildrye	40				
Kochia Prostrata	Forage Kochia	10				
Melilotus Officionalis	Yellow Sweet Clover	10				
Medicago Sativa	Alfalfa	20				
Penstemon Palmeri	Palmer Penstemon	10				
Purshia Tridentata	Antelope Bitterbrush	20				
Rosa Woodsii	Woods Rose	15				
Sanguisorba Minor	Small Burnet	30				

Table 2

Percolation Rates at North Lily


North Lily Mining Company Ltd **TABLE 2**

		Percolat	ion Rates	Percolation Rates @ No.Lily		
	Inches/30 Minutes Inches/Hour	Inches/Hour		Minutes/Inch erc Rate cm/sec	: gal/ft2/day	Elevation
Pit A	1.313	2.625	22.86	0.001852	1.04583	* A/N
Pit B	0.625	1.250	48.00	0.000882	0.72169	91 *
Pit C	3.250	6.500	9.23	0.004586	1.64570	* 86
Pit D	3.188	6.375	9.41	0.004498	1.62980	* 86
PitE	0.125	0.250	240.00	0.000176	0.32275	* 06
PitF	2.688	5.376	11.16	0.003793	1.49688	. 98
PitG	2.188	4,376	13.74	0.003087	135031	*28
PitH	2.688	5,376	11.16	0.003793	1,49566	82*
Pit I	1.250	2.500	24.00	0.001764	1.02062	82 *
Pit W	0.375	0.750	80.00	0.000529	0.55902	83
PitX	1.750	3,500	17.14	0.002469	1,20761	83
PitY	2 625	5.250	11.43	0.003704	1,47902	83
PItZ	1.313	2.625	22.86	0.001852	1.04583	83


(*) **Note:** The Elevations reported here are all relative and were calculated using data from several survey trips to the area. The control point used was assigned an arbitrary 100 foot elevation. The highlighted test pits that are those located within the leach field foot print.

Test Pits Located in footprint of Drain Field	Test Pits Located in footprint of Drain Field	(Percolation Rate Used for Drainfield Sizing)


Drain Field Design and Associated Topographic Map



Typical Trench Layout and Lateral Connection




Typical Lateral Trench Cross-Section




NORTH LILY

Distribution Box Design and Dimensions



Drain Field As-Built




Appendix A

Site Photographs



1. PLACEMENT OF THE NO. 1 DISTRIBUTION BOX AND CONNECTION OF THE PERIMETER DRAIN LINE TO THE GRAVITY FED DISTRIBUTION LINE.




2. PLACEMENT OF GRAVEL AND GEOFABRIC AROUND THE NO. 1 DISTRIBUTION BOX.

NORTH LILY

APPENDIX A
PHOTO PAGE 1

ihr					DATE	8/1/01
IDI		ultants i	nc		NOISIN	
environn Salt Lake City	Iltoh Cedar (City Utah Ren	no, Nevada	Elko, Nevada	ISI	



3. WATER FLOW FROM THE HEAP TO THE DRAIN FIELD AS SEEN THROUGH THE NO. 1 DISTRIBUTION BOXES' CLEAN-OUT LID.



4. JBR EMPLOYEE PLACING THE GRANITE SEED MIX IN THE HEAP

APPENDIX A PHOTO PAGE 2 | Dr | Consultants, inc. | Consultants, i



5. EMPLOYEES OF LAWN WORLD SPRAYING HERBICIDE ONTO THE WHITE CLOVER NOXIOUS WEED.



6. EXCAVATION OF DRAIN FIELD TRENCHES



7. TYPICAL 4-6" OF COARSE GRAVEL ABOVE AND BELOW DRAIN LINE


NORTH LILY

APPENDIX A PHOTO PAGE 4

ihr					DATE	7/16/01
environm Salt Lake City.	nental consu	ltants, in	C. Nevada	Elko, Nevada	NOISION	
			_	1"-60'	REV	



8. IMPERVIOUS GEO-FABRIC PLACED OVER THE COARSE GRAVEL



9. DISTRIBUTION BOX LOCATED AT BEGINNING OF DRAIN FIELD

NORTH LILY

APPENDIX A PHOTO PAGE 5

ihr					DAT	EWN 7/16/01
environm Salt Lake City.	nental consu Utah Cedar Cit	ltants, inc	C. , Nevada	Elko, Nevada	NOISI	336.0
DESIGN JS	DRAWN CP	CH'D		1"-60'	REV	一片龙丛 园丛



10. VIEW FROM NORTH LOOKING SOUTH ACROSS GRADED DRAIN FIELD AREA.




11. VIEW FROM WEST LOOKING EAST ACROSS GRADED DRAIN FIELD AREA.

NORTH LILY	
APPENDIX A PHOTO PAGE 6	
environmental consultants, inc.	DATE 7/16/01
Salt Lake City, Utah Cedar City, Utah Rend, Nevada Line, 11	RE VSION
DESIGN JS DRAWN CP CH'D SCALE 1"-60'	8



12. A VIEW TO THE SOUTHEAST OF THE MILL BUILDING AS IT IS BEING DEMOLISHED.



13. LOOKING INTO THE NEWLY CONSTRUCTED CLASS IIIB INDUSTRIAL LANDFILL, THE FORMER BARREN POND.

N	IORTH LILY	1
	APPENDIX A PHOTO PAGE 7	
jor environmental consul	tants inc	DATE DRAWN 8/1/01
Salt Lake City, Utah Cedar City,	, Utah Reno, Nevada Elko, Neva	
DESIGN JS DRAWN CP	CH'D SCALE 1"-60	, R



14. A VIEW OF THE PARTIALLY CAPPED CLASS IIIB INDUSTRIAL LANDFILL.




15. LOOKING TO THE NORTH AT THE FORMER HEAP (RIGHT SIDE) AND PREGNANT POND (LEFT SIDE), NOW RECLAIMED.

	I	NOR.	TH LILY		
			ENDIX A D PAGE 8		
jbr				DATE	WN 8/1/01
Salt Lake City, I	Jtah Cedar Ci	ty, Utah Ren	nC. io, Nevada Elko, Nevada	REVISION	
DESIGN JS	DRAWN CP	CH'D	SCALE 1"-60'	RE	



16. STANDING ON THE LOCATION OF THE FORMER MILL BUILDING, LOOKING TO THE SOUTHEAST AT THE RECLAIMED SITE AND THE NEWLY INSTALLED FENCE.



17. A VIEW TO THE NORTHEAST AT THE HEAP IN THE MIDDLE RIGHT AND THE AREA WHERE THE DRAIN FIELD IS LOCATED (MIDDLE TO LOWER LEFT).

NORTH LILY

APPENDIX A PHOTO PAGE 9

ihr					DATE	N 8/1/01
Salt Lake City,	utah Cedar Ci	ty, Utah Rei	nc. no, Nevada	Elko, Nevada	NOISION	
	DRAWN CP	CH'D		1"-60'	R.	

Appendix B

Nevada Meteoric Water Mobility Procedure

RECEIVED SEP 2 2 2000

L ANALYTICAL, INC.

e Government Gulch m P.O. Box 929

Rellogg, Idaho 83837-0929

Phone: (208)784-1258

Fax: (208)783-0891

REPORT OF ANALYTICAL RESULTS

CLIENT: JBR Environmental Consultants SVL JOB No.: 95406
SVL SAMPLE No.: 242616

CLIENT SAMPLE ID: SCH-S

Sample Collected: 8/22/00 13:00

Sample Receipt : 8/29/00 Date of Report : 9/19/00 % Moisture: 0.4%

Matrix: ESOIL Extract: MWMP 9/06/00

Determination	Result	Units	Method	Test Date Reference
% Passing -200	15.1	g	Sieve	9/06/00 9/06/00
Moisture to Sat.	636	mL	MWMP	9/06/00
MWMP TIME	24.0	(hr)	150.1	
рН	8.85 5.86		150.1	9/12/00 1 9/06/00 1
PH LIXIVIANT	9.12		ASA M9	
pH Paste	5.00	kg		9/06/00
Weight	510	mg/L Ext	160.1	9/11/00 1
TDS	<0.01	mg/L Ext	1677	9/14/00
Cyanide-WAD Sodium	85.8	mg/L Ext	200.7	9/14/00 1 9/11/00 1
Nitrite-N	1.68	mg/L Ext	300.0	
Nitrate-N	19.7	mg/L Ext	300.0	9/11/00 1
Sulfate, SO4	70.4	mg/L Ext	300.0	9/11/00 1
Silver	<0.005	mg/L Ext	200.7	9/14/00 1
Arsenic	0.135	mg/L Ext	206.2	9/13/00 1
Barium	0.146	mg/L Ext	200.7	9/14/00 1
Cadmium	<0.002	mg/L Ext	200.7	9/14/00 1
Chromium	<0.006	mg/L Ext	200.7	9/14/00 1
Mercury	0.0003	mg/L Ext	245.1	9/12/00 1
Lead	0.089	mg/L Ext	239.2	9/14/00 1
Selenium	0.004	mg/L Ext	270.2	9/14/00 1

REFERENCES: 1) "Methods for Chemical Analysis of Water and Wastes", EPA-600/4-79-20; 2) "Test Methods for Evaluating Solid Wastes, 3rd Edition", SW 846, 1994; 3) "Standard Methods for the Examination of Water and Wastewater", 18th ED. 1992; 4) ASTM Method; 5) 40 CFR, Part 261

•viewed	d By:	Bluke	Lohnson	Date_	9/19	100
			7		9/19/00 3	13:30

Fax: (208)783-0891

REPORT OF ANALYTICAL RESULTS

CLIENT: JBR Environmental Consultants SVL JOB No.: 95406 SVL SAMPLE No.: 242617

CLIENT SAMPLE ID: SCH-N

Sample Collected: 8/22/00 13:30

Sample Receipt : 8/29/00 Date of Report : 9/19/00 % Moisture: 0.5%

Matrix: ESOIL Extract: MWMP 9/06/00

Determination	Result	Units	Method Sieve	Test Date Reference	
% Passing -200	10.0	g		9/06/00	
Moisture to Sat.	579	mL		9/06/00	
MWMP TIME	24.0	(hr)	MWMP	9/06/00	
pН	8.56		150.1		1
pH LIXIVIANT	5.86		150.1	9/06/00	1
pH Paste	8.74		ASA M9	9/15/00	
Weight	5.00	kg		9/06/00	
TDS	1890	mg/L Ext	160.1	9/11/00	1
Cyanide-WAD	<0.01	mg/L Ext	1677	9/14/00	
Sodium	572	mg/L Ext	200.7	9/14/00	1
Nitrite-N	2.38	mq/L Ext	300.0		1
	9.81	mg/L Ext	300.0		1
Nitrate-N	1680	mg/L Ext	300.0		1
Sulfate, SO4	<0.005	mg/L Ext	200.7		1
Silver	0.062	mq/L Ext	206.2		1
Arsenic		mg/L Ext	200.7		1
Barium	0.015		200.7		1
Cadmium	<0.002	mg/L Ext	200.7		1
Chromium	<0.006	mg/L Ext			1
Mercury	0.0004		245.1		1
Lead	0.076	mg/L Ext	239.2		1
Selenium	0.013	mg/L Ext	270.2	9/14/00	•

REFERENCES: 1) "Methods for Chemical Analysis of Water and Wastes", EPA-600/4-79-20; 2) "Test Methods for Evaluating Solid Wastes, 3rd Edition", SW 846, 1994; 3) "Standard Methods for the Examination of Water and Wastewater", 18th ED. 1992; 4) ASTM Method; 5) 40 CFR, Part 261

eviewed By: Blake Johnson Date 9/19/00 19:30

Part I Prep Blank and Laboratory Control Sample

	Client :JBR Environmental Consultants					Analysi				
nalyte	Method	Matrix	Units	Prep Blank	TrueLCS-	Found	LCS %R	Date		
Silver	200.7	ESOIL	mg/L Ext	<0.005	1.00	0.996	99.6	9/14/00		
mrium	200.7	ESOIL	mg/L Ext	<0.002	1.00	0.995	99.5	9/14/00		
dmium	200.7	ESOIL	mg/L Ext	<0.002	1.00	1.02	102.0	9/14/00		
Chromium	200.7	ESOIL	mg/L Ext	<0.006	1.00	0.999	99.9	9/14/00		
Sodium	200.7	ESOIL	mg/L Ext	<0.1	20.0	19.4	97.0	9/14/00		
rsenic	206.2	ESOIL	mg/L Ext	<0.001	0.050	0.045	90.0	9/13/00		
ad	239.2	ESOIL	mg/L Ext	<0.001	0.050	0.049	98.0	9/14/00		
Selenium	270.2	ESOIL	mg/L Ext	<0.001	0.050	0.044	88.0	9/14/00		
Proury	245.1	ESOIL	mg/L Ext	<0.0002	0.0050	0.0053	106.0	9/12/00		
trite-N	300.0	ESOIL	mg/L Ext	<0.05	3.65	3.80	104.1	9/11/00		
Nitrate-N	300.0	ESOIL	mg/L Ext	<0.05	19.4	19.7	101.5	9/11/00		
Sulfate, SO4	300.0	ESOIL	mg/L Ext	<0.3	18.4	19.5	106.0	9/11/00		
vanide-WAD	1677	ESOIL	mg/L Ext	<0.01	2.0	2.0	100.0	9/14/00		
oli	150.1	ESOIL		5.62	9.08	9.06	99.8	9/12/00		
pH Paste	ASA M9			N/A	8.60	8.60	100.0	9/15/00		
Ds	160.1	ESOIL	mg/L Ext	1	337	288	85.5	9/11/00		

LEGEND:

CS = Laboratory Control Sample

LCS %R = LCS Percent Recovery

N/A = Not Applicable

Part II Duplicate and Spike Analysis

Ag 200.7 ESOIL 1 mg/L Ex 0.005	Matrix Spike Lt SPK ADD	%R	Test Date
NO3-N 300.0 ESOIL 1 mg/L Ex 19.7 19.9 1.0 30.8 SOA 300.0 ESOIL 1 mg/L Ex 70.4 71.3 1.3 123 CN VAD 1677 ESOIL 1 mg/L Ex <0.01 0.1 M 0.0 0.1 PH 150.1 ESOIL 1 8.85 8.86 0.1 N/A PDS 160.1 ESOIL 1 mg/L Ex 510 497 2.6 N/A	1 1.00 2 1.00 1 1.00 20.0 86 0.0500 51 0.0500	85.6 99.4 102.0 101.0 86.0 102.0 144.0 96.0 110.0 100.2 111.0 105.2 100.0 N/A N/A	9/14/00 9/14/00 9/14/00 9/13/00 9/13/00 9/14/00 9/12/00 9/11/00 9/11/00 9/11/00

TEND.

RPD: = (|SAM - DUP|/((SAM + DUP)/2) + 100)

UDL = Both SAM & DUP not detected.

RP = (|SPK - MSD|/((SPK + MSD)/2) * 100)

M in Duplicate/MSD column indicates MSD.

E ADD column, A = Post Digest Spike; %R = Percent Recovery N/A = Not Analyzed; R > 4S = Result more than 4X the Spike Added QC Sample 1: SVL SAM No.: 242616 Client Sample ID: SCH-S

Appendix C

Hazardous Materials Handling and Disposal Documentation

- Notification of Regulated Waste Activities
- Hazardous Waste Manifests
- Documentation from TSD (Safety Kleen)
- MSDS's
- Waste Analysis Reports

Form Approved, CMB No. 2050-6003 Exits 10/31.

Please print or type with ELITE type (12 characters per lnch) in the unshaded areas only GEA NO. DEG EPA-Presentative Carrier V. Line-by-Line Metroctions for Completing EPA Form 8700-12 before completing the street. The information requested kers in required by two (Sacrier 3010 of the fitted formation) **Notification of Regulated** Date Received (For Official Use Only) Waste Activity United States Environmental Protection Agency RECOVERY ACC. l. installation's EPA ID Number (Mark X' in the appropriate box) C. Installation's EPA ID Number A Initial Notification B. Subsequent Notification (Complete item C) ii. Name of installation (include company and specific sile name) R T H I L Y CITITI I S L V FAC ill. Location of installation (Physical address not P.O. Box or Route Humber) Street 3 M S S U 0 U Street (Continued) City or Town State Zip Code UR ĸ A Ū 8 County Code County Name J U AB IV. Installation Mailing Address (See instructions) Street or P.O. Box 8 0 0 E N M S U I T E 2 0 City or Town State ZID Coda DEN V R clo 8 0 0 V. Installation Contact (Person to be contacted regarding waste activities at site) Name (Last) (First) FIL E CH N E R T S E P H E N Job Title Phone Number (Area Code and Number) CEO 3 2 9 4 VI. Installation Contact Address (See Instructions) B. Street or P.O. Box Location x City or Town State Zip Code VIL Ownership (See instructions) A. Name of Installation's Legal Owner R 0 T H L 1 M Ю Street, P.O. Box, or Route Number 8 0 G E N บ City or Town State Zip Code E N VE R 0 8 0 2 2 D B. Land Type D. Change of Dwner indicator C. Owner Type Phone Number (Area Code and Number) (Date Changes) Manth Day Yonr Yes 0 3 P P No EPA Form 8700-12 (Rev. 10/09/96) -1 of 2 -

1	UNIFORM HAZARDOUS 1. Generator	r.) 14665841941 8	Mani		2 5	age 1		WB No. 20 Ation in	-	ded area
_	WASTE MANIFEST		Docu	ment No.	o	i l	s not r	equired	by Fed	eral law.
	Generator's Name and Mailing Address NORTH LILY MINING COMPANY MILES SOUTH OF EUREKA ON US F EUREKA, UT 84093 Generator's Phone (!								
_	Transporter J Somplany Name T+R. Superior Special Services, Inc.		DANJIMbe MICORE							- 41
7	Transporter 2 Company Name	8. US EPA	ID Numbe	or .	E/S			yin s		
9.	Designated Facility Name and Site Address SUPERIOR SPECIAL SERVICES, INC. 5736 West Jefferson	10. USEPA	ID Numbe	or .	G S					
	Phoenix, AZ 85043	<u>L.</u>	NZD98 3			tellny				
11.	. US DOT Description (Including Proper Shipping Name, F	· · · · · · · · · · · · · · · · · · ·	umber)	12. Conta No.	iners Type	13. Tota Quan	al tity	14. Unit Wt/Vol	Wa	ste No.
a.	Personal Protective Equipment, 9, 3077	FIGHT 1				~				
b.				$\cup Q_i$	MG	<i>့</i> 0	100			**
		·								
C.										
d.			•					1		
	FOR NAVE SCURE COLUMN 1					ndling Ca				
				£ '	enne en enem		arat ares	# 1 20	n man	
15.	. Special Handling Instructions and Additional Informatio	n			ncuy bocun	ency Co word		11653		4(5);
		of this consignment are fued, and are in all respects tions. In in place to reduce the method of treatment, a small quantity generato I can afford.	in proper con volume and torage, or d r, I have ma	rately descrit adition for tra toxicity of w	ped abor	ve by highway enerated to allable to a	the deg	ree I hav	e detern	nined to b resent an and selec
16	GENERATOR'S CERTIFICATION: I hereby declare that the contents proper shipping name and are classified, packed, marked, and labele according to applicable international and national government regula if I am a large quantity generator, I certify that I have a program economically practicable and that I have selected the practicable future threat to human health and the environment; OR, if I am the best waste management method that is available to me and that Printed/Typed Name	of this consignment are fued, and are in all respects tions. In in place to reduce the emethod of treatment, sa small quantity generato I can afford. Signature	in proper con volume and torage, or d r, I have ma	rately descrit adition for tra toxicity of w	ped abor	ve by highway enerated to allable to a	the deg	ree I hav	e determ	nined to b resent an and selec
16	GENERATOR'S CERTIFICATION: I hereby declare that the contents proper shipping name and are classified, packed, marked, and labele according to applicable international and national government regula if I am a large quantity generator, I certify that I have a program economically practicable and that I have selected the practicable future threat to human health and the environment; OR, if I am the best waste management method that is available to me and that Printed/Typed Name	of this consignment are fued, and are in all respects tions. In in place to reduce the emethod of treatment, sa small quantity generato I can afford. Signature	in proper con volume and torage, or d r, I have ma	rately descrit adition for tra toxicity of w	ped abor	ve by highway enerated to allable to a	the deg	ree I have minimize waste ge	e detern	nined to b resent an and select
16	GENERATOR'S CERTIFICATION: I hereby declare that the contents proper shipping name and are classified, packed, marked, and labele according to applicable international and national government regula if I am a large quantity generator, I certify that I have a program economically practicable and that I have selected the practicable future threat to human health and the environment; OR, if I am the best waste management method that is available to me and that Printed/Typed Name Transporter 1 Acknowledgement of Receipt of Material Printed/Typed Name	of this consignment are fued, and are in all respects tions. in in place to reduce the emethod of treatment, s a small quantity generato I can afford. Signature Signature	in proper con volume and torage, or d r, I have ma	rately descrit adition for tra toxicity of w	ped abor	ve by highway enerated to allable to a	the deg	ree I have minimized waste ge	e determes the present of the property of the	nined to be resent and select and
17.	GENERATOR'S CERTIFICATION: I hereby declare that the contents proper shipping name and are classified, packed, marked, and labele according to applicable international and national government regula if I am a large quantity generator, I certify that I have a program economically practicable and that I have selected the practicable future threat to human health and the environment; OR, if I am the best waste management method that is available to me and that Printed/Typed Name Transporter 1 Acknowledgement of Receipt of Material Printed/Typed Name Transporter 2 Acknowledgement of Receipt of Material	of this consignment are fued, and are in all respects tions. In in place to reduce the emethod of treatment, sa small quantity generato I can afford. Signature Signature	in proper con volume and torage, or d r, I have ma	rately descrit adition for tra toxicity of w	ped abor	ve by highway enerated to allable to a	the deg	ree I have minimized waste ge	e determes the perfection	nined to be resent and select and
17.	GENERATOR'S CERTIFICATION: I hereby declare that the contents proper shipping name and are classified, packed, marked, and labele according to applicable international and national government regula if I am a large quantity generator, I certify that I have a program economically practicable and that I have selected the practicable future threat to human health and the environment; OR, if I am the best waste management method that is available to me and that Printed/Typed Name Transporter 1 Acknowledgement of Receipt of Material Printed/Typed Name Transporter 2 Acknowledgement of Receipt of Material Printed/Typed Name	of this consignment are fued, and are in all respects tions. In in place to reduce the emethod of treatment, sa small quantity generato I can afford. Signature Signature	in proper con volume and torage, or d r, I have ma	rately descrit adition for tra toxicity of w	ped abor	ve by highway enerated to allable to a	the deg	ree I have minimized waste ge	e determes the present of the property of the	nined to be resent and select and
16 17. 18.	GENERATOR'S CERTIFICATION: I hereby declare that the contents proper shipping name and are classified, packed, marked, and labele according to applicable international and national government regula if I am a large quantity generator, I certify that I have a program economically practicable and that I have selected the practicable future threat to human health and the environment; OR, if I am the best waste management method that is available to me and that Printed/Typed Name Transporter 1 Acknowledgement of Receipt of Material Printed/Typed Name Transporter 2 Acknowledgement of Receipt of Material Printed/Typed Name	s of this consignment are fued, and are in all respects tions. In in place to reduce the emethod of treatment, s a small quantity generato I can afford. Signature S Signature S Signature	in proper cor volume and torage, or d r, I have ma	rately descrit ndition for tra toxicity of w isposal curre ide a good	ped above nsport by aste gently available efforts	ve by highway enerated to allable to minim	the deg	ree I have a minimize waste ge	e determes the present of the property of the	nined to be resent and selection and selection and selection and selection and selection are selections.

....

JUL	۔ ۔		., .,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				\	1155			
		Emergency Emergency (801) 943	Contac	t Telephon dinator:	e Num na i	ber					
UNIFORM HAZAI	RDOUS	4 Congretore US	FPA ID No		Mar	nifest nent.No	2. Page			e shaded areas is Federal law.	
WASTE MANIF	FEST .	U.T.P.0.0.	0.0.0	.1 .0 .2 .6	N.L.	M.O.1	1 of 1		<u> </u>	ענס טפר ס־אַי ניזה פּי	di sa
S. Generator's Name and Malling North Lily Minit	na Combany		· •							., 10. 10. 10. 10. 10. 10. 10.	
1800 Glenarm Pla	ace, Suite	210				·	B. Sten	e.Generator's		ir ir grandinis vi Li primo il st. 84	194 my
4. Generator's Phone (303) 294-0427		<i></i>	110 504 10 11	bae		C Stel	e Transporter			
5. Transporter 1 Company Name			S.C.R	US EPA ID N . 0 . 0 . 0 .		5.9.1	D. Tran	naporter's Pho	ne (80	1): 508~760)5: ₂
Safety-Kleen (TO 7. Transporter 2 Company Name			<u> </u>	US EPA ID N						in the Constant in the Constant in	त थि।
						<u>···</u>		sporter's Pho		**************************************	
9. Designated Facility Name and			10.	US EPA ID N	moer		NJ. 310	and a second		ary at the	Y
Safety-Kleen Ara 11600 North Apt	agonice rac						H. Fac	In s Phone	ונייהה ייבטו	en ans some en	1977
Aptus. UT 84029	9.	·		.9.8.1.5	.2.2.		بسنا		·8100"	७२४मध्याः ५ - १८५ मध्	
11. US DOT Description (Includi	ing Proper Snipping	Name, Hazard Class	, and ID N	lumber)	.	12. Cont	Type	13. Total Quantity	Úr		
HM		p.				4	800	-; ·	1. ;;	ב יינוקבסיניי ב	ç :04
a Non-hazardo	us. used o	il and wate	er -		,	o o 5	DМ	0180	0 P	C: VE MA	ે ત્વર (પ્રકાઇ,
			<u></u>					<u> </u>			<u></u>
b	•	4				0 0 1	ם ת	0_0 2_0	, n =	mana NA	.::A
Non-hazardo	ous, used o	il and wate	erra.	•	. , «		ء بر	0.0.2.0		בין איינים היקונים	
C. 1 Cal de		্ প্ৰ া চ্চ		•	7		• 3: :	. *:		Sansporking!	
		, 194. 17 - 142.31	ማካቸ የውማየት		_					U.S. ERNID II.	
			<u>"; ;;,743 </u>	· · · · · ·	•				- · `	סרפו לפתערנים או והערם היצה	25.4
d.				• • • • • • • • • • • • • • • • • • • •	e - 2 € 7 kg					THE PARTY AND	Sec.
	•					·	V Une	dian Codes f	~Wastes	Listed Aboye	يبسبد
3 Additional Descriptions for M.	aterials Usted Above	ින් දෙදුම් ලදා සිය මු දර ඩොසෙරෙග සියි	ajuliuri. Smarri			;				ا بكايمانيا والمراجعة المراجعة	
MICIA N. APROUU690.		MOST TO SEPTIME	SITTE	64 94 65 118: Chies	er or the	SOPPES	भेद्र किर् देखें स्थि	teurn entire): 15	The winder of early	~30xCV
APROPOS	Drum	SOLUTION SOL	2020	. 6,	,			·	المحتوي	- 1.1~ 2/1 <i>ポイン・シィ・ア</i> ブルを記し かりひらが に の の	4 min
15 Special Handling Instruction	ns and Additional Info	ounstion .			er egit se	112 7 19 1	s.d	# 51	38		
Generator Loca	ation:	enne. Einskrijker in Nobel e		··· 1/44	.e.:		غ ا جهانه. ع	. 45: 5		ויי ארבעון	ۍ . س
3 miles south		on US High	way 6,	Eureka,	Utal	h . 4. 172. 2	na Sila	المراجعة		nger	
1 1							cribed al	bove by proper	shipping	name and are class	flied.
packed, marked, and labeled,	3ud ste tu en respect	S #1 proper consum.	J. 1	. , • •				ana deeree t b	www.dotorr	mined to be economic	ically.
practicable and that I have so and the environment; OR, if I	rator. I certify that I have cleated the practicable	ave a program in place method of treatment	storage, o	disposal curren	thy availab	es to me wh	ich mipir	nized the prese select the bes	ulul bne m 1m elsew 1	wabement weitigg the	ealth hait is
and the environment; OR, if I available to me and that I car	i aw a swall dravilly i	debetator i pave inso	- 1,73 m				4.027	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		.g. Month Day	
Printed/Typed Name	1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	e program analogi	16-coiBac	Signaturo	K. E.		= Cyiirt = Me:ส		usia siau Maga High		01
Elaria R. Transporter 9 Acknowledge	amond of Bacainf of	Materials (*** ** mp *	Regional PATOS	27.5	anone d	o , enxed no	500 =	11		4.7 4 dist 7/	
Printed/Typed Name		A.C. 101511-1111 1150	₩4105	Signature 9	- 1.00 A	1	Sing		(2/17)	Month Day	Year.
Sarso aw base 1 400	COSF X FOR	Administrator, 1935	Rogional	<i>X</i>	<u> </u>	acq .mc		XF		Total Quanto	275
18. Transponer 2 Acknowleds	ement of Receipt of	Materials (O. Sweet	20 2124	Signature	/		ejine.	tage no baditá	wastn des	to MANIPO BEX eq	11.09/Z
Principle acceptance of principle of princip	jouggeone respect a	ypo the came of the				<u>.</u> .	(ز			(100/24/1) \$\$\tau 0	1400 14
19. Discrepancy Indication Sp.	308	Cate Rot (coulver) by	A.A.adidas				0.875 99	igho annu - M	oldeT	tous custioned as	
owners or operators of breating	ne generators and	Copar Atimas	COCCOS.	The service		(yes soly)	nencoli			Mone (Equids noty)	60 3
Chief To Sucresson of the Control	ms. Conditions and	Security (Second 1)	ACCOUNT.		4	L DOOD LAN		N So		V	
202 Facility Owner or Operator	Certification of rec	elpt of hazardous m	ationals co	vered by this m	enifest ex	ceptastoc	ed to \$10	distant		Section (section)	
T. Maria		140 14 Tak		12-24			coores	ACTURE ATEC	Tires econd	Money - Day	Yai
Plinted Typed Name	1:			Sopara					1000	1-1-1-2-1-1-C-1	0/
かんであるできたろう			::em29000		A 51 (12)		2 2 7				
	30	En Youmanal Pic	200	in the court	NES	ATOP	Ý				
		-ORIGINAL -	ールピリ	ンススペーシングー		44.0×4				TOTAL P.	つつ

LOS DE LOS LOS ESTADOS			Form	Approved. OMB	No. 2050	-0039. Expires 9-30-99
to brint or type. (Form designed for use on elite (12-pltch) typowriter.) 1. Generator's US EPA ID No.	Manifest Document N		z. Page	1 Informs	ition in th	asens bebade en
UNIFORM HAZAKUOUS	1/0/2/6/0/6/0/	14	of	1 I is not re	equired b	by Federal law.
3. Generator's Name and Melling Address		17	a, Stai	le Manifeet Docu	ment Nui	
NORTH LILY MINING COMPANY	3462R	-	8. Sto*	te Generator's ID	١	
3 MI SOUTH OF EUREKA HWY 6 EUREKA, UI	37020 SE	- 1'		wisser w th		
4 Generalor's Phone (80] 943-4144 ATTN: 50011 FAV	US EPA ID Number			la Transporter's I		
5. Transponer 1 Company Value (TCF) INC 15/C/RK	0000745	711	D. Tres	nsporter's Phone	BOI-	-508-7605
7. Transporter 2 Company Name 8.	US EPA ID Number	<u>L</u>		ale Transporter's	וט	
	US EPA ID Number			neporter's Phone ate Facility's ID		
A SIGNAL AND SIGNAL AN	US EFA ID NUMBER	- 1				
SAFETY-KLEEN (GRASSI MODIFACTOR). 2.007 I-80	}		H. Fa	cílity's Phone		222 2000
	2 - 1 - 1 - 1 - 1 - 1				, 	323-8900
CJ.IVE, UT 11. US DOT Description (Including Proper Shipping Name, Hazard Class and I		Containe	- 1	13. Total	14. Unit	Waste No.
		10,	Туре	Quantity	WiVol	
X RQ, WASTF SODIUM HYDROXIDE, SOLID, N.C).s., 8,				1	
C X RQ, WASTF SODIUM HIDROXIDE, SECTION INC.	lon	0 6 1	MC	13/60/0	'P	D010
			\exists		7	1
b.		٠, ١	١, ١	1111	1 1	1
					1	
с					1 1	
1 1					4	
d.						
l	↓,	_ ,		1111		\
		لمسلمة	K. H	andling Codes for	r Wastes	Listed Above
J. Additional Descriptions for Materials Listed Above	•		1	<u> </u>		
a. GM01-0308	•	Ì	1			
	ERC 12	74	1			İ
	EPG 15			10100	,	
15. Special Handling Instructions and Additional Information	うんし	U T	4	W118		İ
		e		ı		Ì
24 HOUR EMERGENCY NUMBER: 3E Co. 1-B	200-451-8.	<u> 54</u> L	<u> </u>	. hv		
16. GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignation of the consignation of the consignation of the consignation of the content of the co	ment are they and according.	for trans	port by	highway		
proper shipping name and are classified, povernment regulations, according to applicable international and national government regulations.	e the valume and toxicity of v	waste ge r	norated	to the degree I ha	ve delem	ined to be economically
if I am a large quantity generator, I certify that I have a program in place to reduce practicable and that I have safected the practicable method of treatment, storage or and the environment; OR, II I am a small quantity generator, I have made a good to	t disposal currently syzilable	to me wi	nich mil ation a	nimizes the procont in pelect the best t	nulul bag ham əlagw	agement method that is
practicable and that I have made a good to and the environment; OR, if I am a small quantity generator, I have made a good to evaluable to me and that I can afford.		مر	_A	<u>/</u>	1500	Month Day Year
Printed/Type4 Name	Signature (1/1	ء[[]،	T AS NOT!	A.T.	MOGOTIAL
STEVEL ACHEY AS LET. FOR IVILLIA	- Clary	سرر	14			U
17. Transporter 1 Acknowledgement of Receipt of Materials	Signature		+,	1		Month Day Year
Printed/Typed Name	Signature		_			10/6/9/19/
18. Transporter 2 Acknowledgement of Receipt of Materials						Month Day Year
18. Transporter 2 Acknowledgement of Noceipt of Material Printed/Typed Name	Signatura					
	1					
F 19. Discrepancy Indication Space					۸,	S
					_1/0	ARM DOJC
C I I 20. Facility Owner or Operator; Certification of receipt of hazardous materials	s covered by this manifes	excep!	l BS no	ted in Item 19.		
	Signature	1.	1.	NIn.		Month Day Year
Printed/Typed Name	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	U	11	WUL	<u></u>	XKUVCI
I (MYGL)	- Julian	-	عصيت E	PA Form 8700-200 (Plev. 9-86)	Previous editions are obsolete
585-7521	/					



				EmergencyEmergency	Contact Telephy Coordinato 1-9768 (Box	r:	DBI .						
				(801) 943	3 <u>~9768 (BOX</u> 5 EPA 10 No.	Mar Docum	West Ment No	2. Pege				aded aress	is
	*	U	NIFORM HAZARDOUS WASTE MANIFEST	0.0.9.T.U	.0.0.0.1.0.2	.6 : L.	4.0.2	1 of	2 not 0		d by Fede		
7	3. (Genera	stor's Name and Mailing Address th Idly Mining Company					~	10%		. '5.		
	•	1800) Glenarm Place, Suite	210		•		B. Stea	e Generator	's 10 .			
۱۱	4.	Deny	ver 0 80202 Mors Phone (303 294-042	7	116.692	1D :		C. Stat	e Transport				
H	5.	Transp	ety-Kleen (TG) Inc.		6. USEPA [S.C.R.0.0.0	0.7.4.	5.9.1	D. Trai	nsporter's P	none	(801)	508-7	605
			porier 2 Company Name			10 ~~~.021			e Transport				
					10. US EPA	ID N 561			te Facility's				
		Cafe	nated Facility Name and S := Address ety-Kleen Grassy Mount	ain Facili	ty				14. 1. 10h - n				
		3 M	iles East, 7 Miles Noi	th of Exit	41, I-80 U. T. D. 9. 9.	1 3 0 1.			illy's Phone 01) 32		16	-	
١	_	Cliv	Ve, UT 84029 OOT Description (Including Proper Shipping)	o Name. Hazard Cla		1. 3. 0. 1.	12. Cont	ainers	13. Tota		14. Unit	L	
ľ	"	. USD HM					No.	Туре	Quant	ty	Wi/Vol	Wasto	No
	4	17	Waste flammable liqui		3. IM1993	:			Est	•		• • •	91
	ቦ	ا ار	Waste flammable liqui PGII (D001)	, 11.0.3.1	J (41)		001	M	001	0 0	P	D00	1 '
 		\Box	RQ waste sodium cyani	de 61 m	v1689.				Est	_			Tire.
EN	V	/X	PGI (P106, D003)	.uc, 01.7 o.			0 0 1	D F	000	6 0	P	P106,	
NER	7	,-		4- 5 1 TM	11403		'	j	Est	•			.सहस्रहेस स्टब्स्ट्राइस
ATO	V	, X	RQ waste silver nitra PGII (D011)	ive, 5.1, or	11277,		001	ÞF	000	1 5	P	D001,	. 7#
7									Est		٠.		.ಶಾಜ್ : :=.೫೦
	个	(Waste, toxic solid, (lead acetate), 6.1,	UN2811, PG	u.s., II		001	ÞF	aaq	.1 5	P	U144,	D008
	-	444	long Decederates for Maje at: Listed Ab	we	•			K. Ha	ndling Code		osios Us		:
H	-	11a) " GM 01- 0005; Lab pac	c, Derum # O c. Derum # O	<u> </u>		. I	4	•				• • •
		110) GM. 01-0005; Labbac	K, LALUM # 3	ロブーひろ] "	•		• •		
		.11d	ocial Handling Instructions and Additional					<u></u>	SWO	#	38	639	
	ľ	-			tureka on US	Highway	y 6				_ •		
			Eureka,	Utah									
		ie. GE	NERATOR'S CERTIFICATIO'1: I hereby di ked, marked, and labeled, and are in all resp	eclare that the conton	Is of this conzignment	ive full, and and and and and and and and and and	courately do applicable h	:cribed (critematic	above by pro nat and natio	ngi gov	pping nan smmental	regulations	: assnwo.
ľ		pac	rked, marked, and labeled, ar ; are in an issu	heve a program in th	ace to reduce the volum	ie and :: isity	of waste 90	beteren	to the degree	, I have	determine	ed to be ecc	-omically
		pre	acticable and that I have selected the practical the conviconment; OR, if I are a small quant	ly penerator, I have m	ade a good taith offen t	o minic z÷ my	wasie gene	US NOGEN	d select the	best wa	210 1101101		
ı	1	84	silable to me and that I can 2 - 0		Cinneture	h P					ł	Monin De TP VT!	; Year 7 ⊄ 1
	1			el Namoide		12 /- 1					T		
H	TRANSPORTER		ansponer 1 Acknowledgems: of Receipt	7 /	Signature	4	-	1/.			1	Month Da	" Year 91 /F.)
	S L		Gary II	i <u>ks</u>		Are-	7-	July 1				<u> </u>	7.07
	Ŗ		ransporter 2 Acknowledgem= 1 of Receipt rinted/Typed Name	OI MINIBINETS	Signature	7						Month Da	3) You
	1			·									
		19. D	iscrepancy Indication Space										
	F												
	AC-L	<u> </u>	acility Owner or Operator: Continuation of	roceipt of hazardous	materials covered by	hismar :764	PAPP	MYZ	P1 (18./1	_			
		20. F	BOING OWNER OF OPERATOR OF THE PROPERTY OF					<u> </u>	101			MODE D	- X44
	*	P	Printed/Typed Name	MIROS	Signatur	a////		M				UDK	\mathcal{I}
						· · ·							*
				ORIGINAL	- RETURN T	O GENER	RATOR.						

-	- :	7.50,77 p.		בי באני הוארול ביות ביות ביות ביות ביות ביות היים					· VIEV. U	MD 110. A	JOU'UU'S EXPILOS U'S	Ĭ Ú- ØZ
	A		FORM HAZARDOUS	21. Generator's US EF - 1	D No.	Manifest Doc	ument No.	22. Page	1		ne shaded	
	T		ASTE MANIFEST	UTP00000126		NILMO1	NLM02	2		not req	uired by Federal	J
	Ш		ontinuation Sheet)		لب بس			1 Conta M	law.			ا ب
		23 68	nerator's Name					L State M.	an ≑si⊾oc	ument r	lumber.	
	H		North:	Lily Mining Cor.	any				enerators	D' i di	Company of the Company	3°
	П			•				637		ar ar		
	П	24 Tra	insporter Company Nam	ne	25. U	S EPA ID Numi	ber	N. State Tr				_
	П	Sa	fety-Kleen (TG) Li	nc.	SCR00007	74591		O. Transpo	rter's Phor	10 (80	1) 508-760	5
	П	26. Tra	insporter Company Nan	ne ·	27 US	S EPA ID Numi	per	P. State Tr	arspoders	ID		
	П							Q. Transpo			1 1	
	Н	28 US	DOT Description (Including	Proper Shipping Name 22	ard Class, and	ID Number)	29. Conti	. 1	30. Total	31. Unil WtVol		
	П	HI					No.		Duanilly	Wt/Vol	Waste No.	
	П	a.	Waste corrosive	liquid, inorgan	ic, n.o.s	5., 8,		i i	Est.		D002, D00	₿.
	П	LA	UN3266, PGII	•	•	· •	001	DF	200	P	D011	Ž.
			1			**				1-	ADVESTIGATION OF THE PARTY OF T	SP ju
	П	11		ric acid solution	n, 8, UN1	1789,		DM .	Est.	_		8
		 	PGII				001	- '	200	P	D0024	
	П	c. /				·····			est.		THE REAL PROPERTY.	逃
	Ш		Non-hazardous w	aste			001	DM	400	P		
		4								-	No. No. of Lot	
	E	9	Non bassadana ca				000		200			
	E		Non-hazardous w	aste			002	DM	300	P	NA.	畿
	R	0.3		• • • •							CANCEL SE	
	T	Y	waste corrosive	liquid, n.o.s.,	(hydroch	iloric	001		400			
	O	1 8	acid and water)	, 8, UN1760, PGI	Ļ		001	DM	400	P		数
		1.										泵
												数
		<u> </u>									Sec. Sec. Sec.	
		9.		•								
	П											
		n.		•	****							
											184324	懋
										<u> </u>	AP 200 34	羉
	۱	i.										選
		S. Adr	 litional Descriptions for Mater	rials Listed Ahove			1 7	T. Handlin	Codes for	Wagtes	Listed Above	8
		28	a) GM 01-0005	aboack Drum # 9	89-05		100	1	•	130	1574	gr.
		28	b) GM 01-0005; L	abpack Drum # 9	89-06		4132	3	•	," 		
		1	c) GM 00-0626; D	abpack Drum # 90 rum # DM-7 rum DM-8, DM-9		· · ·	1.45 pt 1					# .
			d) GM 01-004; Dr	100 # DM-8, DM-9	•		, 44	2		• • •	्या अस्ति। स्टूर्स	
_		32. Sp 28	ecial Handling Instructions a e) QM 00-0627; D									l
	П	20	e/ G 1 00-002/; D									
	П											
-	₩											
	7	33. T	ransporter Acknowled	gement of Receipt of Mater							Date	
	3	P	rinted/Typed Name		Signa	iure					Month Day Ye	ear
_	5	<u> </u>			<u> </u>							
	ě.	_		gement of Receipt of Mater	ials Signa	tura					Date Month Day Ye	Ber
	E	"	inted/Typed Name		Signa	w10						, w
_	4	35. D	iscrepancy Indication Space		1					÷-		一
	Ŷ		•							20	0100/718 G-K	7_
	Ĭ	1								الماسر	1-k	ŀ
_	۲	<u> </u>	EV-6 LABELMASTER, Div. of AME	PRODUCTION OF THE PRODUCTION O	10 H 6566 65	0-621-6808	•	EPA Form A	/0C-2≥≜ /P		rious editions are obse	ا <u>ب</u> حمد
			EV.E (ABE) MACTER Dis ALAME	amicaaliasisiaaank CD CM(CAC		2002 14 DAIL M						



12/18/00

J B R CONSULTANTS GROUP 8160 S HIGHLAND DR SUITE A4 SANDY, UT 84093

Dear Customer,

Safety-Kleen (Lone and Grassy Mountain), Inc. (Grassy Mountain Facility) is pleased to provide you with pricing for the management of the following waste stream:

Generator: NORTH LILY MINING COMPANY EPA ID #: UTP000001026 Acceptance #: GM00-0624 Waste Name: BORAX PENTAHYDRATE

Bill Description 30 G DM DISPOSAL STATE NON-RCRA FEE Price UM 55.000 DM 2.500 T

The waste acceptance number GM00-0624 should be included on all correspondence, manifests, and waste labels of any containers that are sent to the Grassy Mountain Facility.

The price quote is based on the waste stream profile information and waste sample composition submitted by your company for this waste. Should any shipments of waste be non-conforming to the profile description or sample analysis, this may result in the waste becoming unacceptable for management by our facility. The Grassy Mountain Facility will notify you of any non-conformance as well as potential alternate management methods and charges that may be applicable should this problem arise.

To schedule a delivery or pick-up of waste, please contact our Customer Service Group at (800) 243-0783. Should you have questions regarding our management of your waste, please contact your local Technical Sales Representative or the facility Customer Service Group.

Thank you for your consideration of the Grassy Mountain Facility. We appreciate the opportunity to be of service to your company.

Sincerely,

Eva McCroskey Profile Approvals



NOTIFICATION OF WASTE ACCEPTANCE Safety-Kleen, Grassy Mountain Facility

12/18/00

USTOMER INFORMATION

EPA ID#: UTP000001026

NORTH LILY MINING COMPANY

3 MILES SOUTH OF EUREKA HIGHWAY 6

EUREKA, UT 84628-

CONTACT: SCOTT PAGE

PHONE: (801) 943-4144

PROFILE SHEET #: 8000688

WASTE NAME: BORAX PENTAHYDRATE

INVOICE INFORMATION

REF #: 504832

J B R CONSULTANTS GROUP

8160 S HIGHLAND DR SUITE A4

SANDY, UT 84093

CONTACT:

PHONE: (801) 943-4144

WASTE ACCEPTANCE #: GM00-0624

Thank you for selecting Safety-Kleen, Grassy Mountain for your waste management requirements. Your waste stream has been reviewed and is acceptable for management at our facility based on the information provided on the profile sheet number listed above and conditions listed below. Our facility has the necessary permits to allow the storage, treatment, or disposal of this waste. The above referenced acceptance number should be listed on all shipping documents and correspondence. Please retain these documents for your records and future reference.

Please contact Customer Service at 1-800-243-0783 should you have any questions. To schedule a shipment, contact Grassy Mountain Customer Service at 1-800-243-0783.

ACCEPTANCE INFORMATION

The waste stream identified by the reference number above is acceptable for disposal.

This waste is acceptable for delivery beginning on 12/18/00 thru 12/18/01, at which time an update review may be required for continued acceptability.

Comments:

ON SITE TSD/ RCRA CELL/ NON-RCRA CERTIFICATION ON FILE/ FINGERPRINT ON ARRIVAL

Shipping Requirements:

Acceptance number (GM00-0624) must be marked on top of drum(s).

Type of Container: DRUM

12/18/00

PROFILE SHEET #: 8000688 WASTE STREAM #: GM00-0624

WASTE STREAM ANALYSIS INFORMATION

Waste Name..... BORAX PENTAHYDRATE

Physical State..... SOLID

Process Producing Waste..: UNUSED CHEMICAL

EPA Waste Codes:

NONE

NS - NO SAMPLE

This analysis is solely for use by Safety-Kleen Grassy Mountain employees for the purpose of determining waste acceptability. No other claims are made or implied.

	t T			17	A	TI	_	R
Αl	JT	пu	К	L	н	H	u	К

Approval:	Eva McCroskey En	Date: 12/18/20
Approval:	Brett Bushnell 55 b	Date: 02/06/0(

Waste Stream #: GM00-0624



RECEIVED FEB 1 3 2001

12/18/00

J B R CONSULTANTS GROUP 8160 S HIGHLAND DR SUITE A4 SANDY, UT 84093

Dear Customer,

Safety-Kleen (Lone and Grassy Mountain), Inc. (Grassy Mountain Facility) is pleased to provide you with pricing for the management of the following waste stream:

Generator: NORTH LILY MINING COMPANY EPA ID #: UTP000001026

Acceptance #: GM00-0626 Waste Name: SODA ASH

Bill Description 5 G DM DISPOSAL STATE NON-RCRA FEE Price UM 50.000 DM 2.500 T

The waste acceptance number GM00-0626 should be included on all correspondence, manifests, and waste labels of any containers that are sent to the Grassy Mountain Facility.

The price quote is based on the waste stream profile information and waste sample composition submitted by your company for this waste. Should any shipments of waste be non-conforming to the profile description or sample analysis, this may result in the waste becoming unacceptable for management by our facility. The Grassy Mountain Facility will notify you of any non-conformance as well as potential alternate management methods and charges that may be applicable should this problem arise.

To schedule a delivery or pick-up of waste, please contact our Customer Service Group at (800) 243-0783. Should you have questions regarding our management of your waste, please contact your local Technical Sales Representative or the facility Customer Service Group.

Thank you for your consideration of the Grassy Mountain Facility. We appreciate the opportunity to be of service to your company.

Sincerely,

Eva McCroskey // Profile Approvals



NOTIFICATION OF WASTE ACCEPTANCE Safety-Kleen, Grassy Mountain Facility

12/18/00

USTOMER INFORMATION

EPA ID#: UTP000001026

NORTH LILY MINING COMPANY

3 MILES SOUTH OF EUREKA HIGHWAY 6

EUREKA, UT 84628-

CONTACT: SCOTT PAGE

PHONE: (801) 943-4144

PROFILE SHEET #: 8000686

WASTE NAME: SODA ASH

INVOICE INFORMATION

REF #: 504832

J B R CONSULTANTS GROUP

8160 S HIGHLAND DR SUITE A4

SANDY, UT 84093

CONTACT:

PHONE:

(801) 943-4144

WASTE ACCEPTANCE #: GM00-0626

Thank you for selecting Safety-Kleen, Grassy Mountain for your waste management requirements. Your waste stream has been reviewed and is acceptable for management at our facility based on the information provided on the profile sheet number listed above and conditions listed below. Our facility has the necessary permits to allow the storage, treatment, or disposal of this waste. The above referenced acceptance number should be listed on all shipping documents and correspondence. Please retain these documents for your records and future reference.

Please contact Customer Service at 1-800-243-0783 should you have any questions. To schedule a shipment, contact Grassy Mountain Customer Service at 1-800-243-0783.

ACCEPTANCE INFORMATION

The waste stream identified by the reference number above is acceptable for disposal.

This waste is acceptable for delivery beginning on 12/18/00 thru 12/18/01, at which time an update review may be required for continued acceptability.

Comments:

ON SITE TSD/ RCRA CELL/ NON-RCRA CERTIFICATION ON FILE/ FINGERPRINT ON ARRIVAL

Shipping Requirements:

Acceptance number (GM00-0626) must be marked on top of drum(s).

Type of Container: DRUM

12/18/00

PROFILE SHEET #: 8000686

WASTE STREAM #: GM00-0626

WASTE STRE	AM ANALYSIS	INFORMATION
------------	-------------	-------------

Waste Name..... SODA ASH Physical State..... SOLID

Process Producing Waste ...: UNUSED CHEMICAL

EPA Waste Codes:

NONE

NS - NO SAMPLE

This analysis is solely for use by Safety-Kleen Grassy Mountain employees for the purpose of determining waste acceptability. No other claims are made or implied.

AUT	Ή	0	R	١Z	A	T	0	N
-----	---	---	---	----	---	---	---	---

Eva McCroskey Approval:

Date: 12/18/00

Approval:

Brett Bushnell 65%

Waste Stream #: GM00-0626

RECEIVED MAR 1 3 2001



01/02/01

J B R CONSULTANTS GROUP 8160 S HIGHLAND DR SUITE A4 SANDY, UT 84093

Dear Customer,

Safety-Kleen (Lone and Grassy Mountain), Inc. (Grassy Mountain Facility) is pleased to provide you with pricing for the management of the following waste stream:

EPA ID #: UTP000001026 Generator: NORTH LILY MINING COMPANY

Acceptance #: GM00-0625 Waste Name: PREMIX

Bill Description Price UM 60.000 DM 55 G DM DISPOSAL STATE NON-RCRA FEE 2.500 T

The waste acceptance number GM00-0625 should be included on all correspondence, manifests, and waste labels of any containers that are sent to the Grassy Mountain Facility.

The price quote is based on the waste stream profile information and waste sample composition submitted by your company for this waste. Should any shipments of waste be non-conforming to the profile description or sample analysis, this may result in the waste becoming unacceptable for management by our facility. The Grassy Mountain Facility will notify you of any non-conformance as well as potential alternate management methods and charges that may be applicable should this problem arise.

To schedule a delivery or pick-up of waste, please contact our Customer Service Group at (800) 243-0783. Should you have questions regarding our management of your waste, please contact your local Technical Sales Representative or the facility Customer Service Group.

Thank you for your consideration of the Grassy Mountain Facility. appreciate the opportunity to be of service to your company.

Sincerely,

Éva McCroskey Profile Approvals

. **6**3



NOTIFICATION OF WASTE ACCEPTANCE Safety-Kleen, Grassy Mountain Facility

01/10/01

USTOMER INFORMATION

EPA ID#: UTP000001026

NORTH LILY MINING COMPANY

3 MILES SOUTH OF EUREKA HIGHWAY 6

EUREKA, UT 84628-

CONTACT: SCOTT PAGE

PHONE: (

(801) 943-4144

PROFILE SHEET #: 8000687

WASTE NAME: PREMIX

INVOICE INFORMATION

REF #: 504832

J B R CONSULTANTS GROUP

8160 S HIGHLAND DR SUITE A4

SANDY, UT 84093

CONTACT:

PHONE:

(801) 943-4144

WASTE ACCEPTANCE #: GM00-0625

Thank you for selecting Safety-Kleen, Grassy Mountain for your waste management requirements. Your waste stream has been reviewed and is acceptable for management at our facility based on the information provided on the profile sheet number listed above and conditions listed below. Our facility has the necessary permits to allow the storage, treatment, or disposal of this waste. The above referenced acceptance number should be listed on all shipping documents and correspondence. Please retain these documents for your records and future reference.

Please contact Customer Service at 1-800-243-0783 should you have any questions. To schedule a shipment, contact Grassy Mountain Customer Service at 1-800-243-0783.

ACCEPTANCE INFORMATION

The waste stream identified by the reference number above is acceptable for disposal.

This waste is acceptable for delivery beginning on 01/09/01 thru 01/09/02, at which time an update review may be required for continued acceptability.

Comments:

ON SITE TSD/ RCRA CELL/ NON-RCRA CERTIFICATION ON FILE/ DISPOSE IN DRUMS/ FINGERPRINT ON ARRIVAL

Shipping Requirements:

Acceptance number (GM00-0625) must be marked on top of drum(s).

Type of Container: DRUM

01/10/01 WASTE STREAM #: GM00-0625

PROFILE SHEET #: 8000687

WASTE STREAM ANALYSIS INFORMATION

Waste Name..... PREMIX
Physical State.... SOLID

Process Producing Waste..: UNUSED SURPLUS CHEMICAL MIX

EPA Waste Codes:

NONE

NS - NO SAMPLE

This analysis is solely for use by Safety-Kleen Grassy Mountain employees for the purpose of determining waste acceptability. No other claims are made or implied.

AUTHORIZATION

Approval:	Eva McCroskey 2m	Date: ////01
Approval:	Brett Bushnell 35 h	Date: 03/05/01

Waste Stream #: GM00-0625



12/18/00

J B R CONSULTANTS GROUP 8160 S HIGHLAND DR SUITE A4 SANDY, UT 84093

Dear Customer,

Safety-Kleen (Lone and Grassy Mountain), Inc. (Grassy Mountain Facility) is pleased to provide you with pricing for the management of the following waste stream:

Generator: NORTH LILY MINING COMPANY EPA ID #: UTP000001026
Acceptance #: GM00-0627 Waste Name: HYDROCHLORIC ACID AND WATER

Bill Description Price UM
55 G DM TREATMENT 84.000 DM
55 G DM DISPOSAL 56.000 DM
STATE NON-RCRA FEE 2.500 T

The waste acceptance number GM00-0627 should be included on all correspondence, manifests, and waste labels of any containers that are sent to the Grassy Mountain Facility.

The price quote is based on the waste stream profile information and waste sample composition submitted by your company for this waste. Should any shipments of waste be non-conforming to the profile description or sample analysis, this may result in the waste becoming unacceptable for management by our facility. The Grassy Mountain Facility will notify you of any non-conformance as well as potential alternate management methods and charges that may be applicable should this problem arise.

To schedule a delivery or pick-up of waste, please contact our Customer Service Group at (800) 243-0783. Should you have questions regarding our management of your waste, please contact your local Technical Sales Representative or the facility Customer Service Group.

Thank you for your consideration of the Grassy Mountain Facility. We appreciate the opportunity to be of service to your company.

Sincerely,

Eva McCroskey C Profile Approvals



NOTIFICATION OF WASTE ACCEPTANCE Safety-Kleen, Grassy Mountain Facility

12/18/00

USTOMER INFORMATION

EPA ID#: UTP000001026

NORTH LILY MINING COMPANY

B MILES SOUTH OF EUREKA HIGHWAY 6

EUREKA, UT 84628-CONTACT: SCOTT PAGE

PHONE: (801) 943-4144

PROFILE SHEET #: 8000685

WASTE NAME: HYDROCHLORIC ACID AND WATER

INVOICE INFORMATION

REF #: 504832

J B R CONSULTANTS GROUP

8160 S HIGHLAND DR SUITE A4

SANDY, UT 84093

CONTACT: PHONE:

(801) 943-4144

WASTE ACCEPTANCE #: GM00-0627

Thank you for selecting Safety-Kleen, Grassy Mountain for your waste management requirements. Your waste stream has been reviewed and is acceptable for management at our facility based on the information provided on the profile sheet number listed above and conditions listed below. Our facility has the necessary permits to allow the storage, treatment, or disposal of this waste. The above referenced acceptance number should be listed on all shipping documents and correspondence. Please retain these documents for your records and future reference.

Please contact Customer Service at 1-800-243-0783 should you have any questions. To schedule a shipment, contact Grassy Mountain Customer Service at 1-800-243-0783.

ACCEPTANCE INFORMATION

The waste stream identified by the reference number above is acceptable for disposal with the following treatment:

Stabilization

This waste is acceptable for delivery beginning on 12/18/00 thru 12/18/01, at which time an update review may be required for continued acceptability.

Comments:

ON SITE TSD/ RCRA CELL/ NON-RCRA CERTIFICATION ON FILE/ FINGERPRINT ON ARRIVAL

Shipping Requirements:

Acceptance number (GM00-0627) must be marked on top of drum(s).

Type of Container: DRUM

12/18/00

PROFILE SHEET #: 8000685

WASTE STREAM #: GM00-0627

WASTE STREAM ANALYSIS INFORMATION

Waste Name..... HYDROCHLORIC ACID AND WATER

Physical State..... LIQUID

Process Producing Waste..: TANK WASHING

EPA Waste Codes:

NONE

NS - NO SAMPLE

This analysis is solely for use by Safety-Kleen Grassy Mountain employees for the purpose of determining waste acceptability. No other claims are made or implied.

AUTHORIZATION

Approval:	Eva McCroskey En	Date:	12/18/00
-----------	------------------	-------	----------

Approval: Brett Bushnell 50 Date: 3/2/01

Waste Stream #: GM00-0627



02/16/01

J B R CONSULTANTS GROUP 8160 S HIGHLAND DR SUITE A4 SANDY, UT 84093

Dear Customer,

Safety-Kleen (Lone and Grassy Mountain), Inc. (Grassy Mountain Facility) is pleased to provide you with pricing for the management of the following waste stream:

Generator: NORTH LILY MINING COMPANY EPA ID #: UTP000001026

Acceptance #: GM01-0005 Waste Name: LABPACK

Bill Description Price UM
5 G LABPACK TREATMENT & DISP 120.000 DM
55 G LABPACK TREATMENT & DISP 400.000 DM
LP INCINERATION-180 LB MIN 1.960 P
LP REACTIVE INCIN- 25 LB MIN 1.960 P

The waste acceptance number GM01-0005 should be included on all correspondence, manifests, and waste labels of any containers that are sent to the Grassy Mountain Facility.

The price quote is based on the waste stream profile information and waste sample composition submitted by your company for this waste. Should any shipments of waste be non-conforming to the profile description or sample analysis, this may result in the waste becoming unacceptable for management by our facility. The Grassy Mountain Facility will notify you of any non-conformance as well as potential alternate management methods and charges that may be applicable should this problem arise.

To schedule a delivery or pick-up of waste, please contact our Customer Service Group at (800) 243-0783. Should you have questions regarding our management of your waste, please contact your local Technical Sales Representative or the facility Customer Service Group.

Thank you for your consideration of the Grassy Mountain Facility. We appreciate the opportunity to be of service to your company.

Sincerely,

Eva McCroskey

Profile Approvals

GM01-0005 Page - 1 -



NOTIFICATION OF WASTE ACCEPTANCE Safety-Kleen, Grassy Mountain Facility

02/16/01

USTOMER INFORMATION

EPA ID#: UTP000001026

NORTH LILY MINING COMPANY

3 MILES SOUTH OF EUREKA HIGHWAY 6

EUREKA, UT 84628-CONTACT: SCOTT PAGE

PHONE: (801) 943-4144

PROFILE SHEET #: M010005

WASTE NAME: LABPACK

INVOICE INFORMATION

REF #: 504832

J B R CONSULTANTS GROUP

8160 S HIGHLAND DR SUITE A4

SANDY, UT 84093

CONTACT:

PHONE: (801) 943-4144

WASTE ACCEPTANCE #: GM01-0005

Thank you for selecting Safety-Kleen, Grassy Mountain for your waste management requirements. Your waste stream has been reviewed and is acceptable for management at our facility based on the information provided on the profile sheet number listed above and conditions listed below. Our facility has the necessary permits to allow the storage, treatment, or disposal of this waste. The above referenced acceptance number should be listed on all shipping documents and correspondence. Please retain these documents for your records and future reference.

Please contact Customer Service at 1-800-243-0783 should you have any questions. To schedule a shipment, contact Grassy Mountain Customer Service at 1-800-243-0783.

ACCEPTANCE INFORMATION

The waste stream identified by the reference number above is acceptable for disposal with the following treatment:

Other

This waste is acceptable for delivery beginning on 02/16/01 thru 02/16/02, at which time an update review may be required for continued acceptability.

Comments:

MUST COMPLY WITH GRASSY MOUNTAIN LABPACK GUIDELINES/ REQUIRES INVENTORY APPROVAL PRIOR TO SHIPMENT

Shipping Requirements:

Acceptance number(GM01-0005) must be marked on top of drum(s). A Notification is required with each shipment in accordance with 40 CFR Section 268.7

Type of Container: DRUM

02/16/01

PROFILE SHEET #: M010005

WASTE STREAM #: GM01-0005

M/A	QTE	CTDEANA	ARIAI VOIC	INFORMATION
WA	DIE	DIREAM	ANAL 1 515	INFURINATION

Waste Name..... LABPACK

Physical State....:

Process Producing Waste..: SURPLUS CHEMICALS

EPA Waste Codes:

D001 D002 D003 D008 D011 P106 U144

NS - NO SAMPLE

This analysis is solely for use by Safety-Kleen Grassy Mountain employees for the purpose of determining waste acceptability. No other claims are made or implied.

AUTHORIZATION

Approval: _____ Eva McCroskey 4___

Date: <u>2/14/0)</u>

Approval:

Brett Bushneli 858

Date: <u>03/05/01</u>

Waste Stream #: GM01-0005

Profile 8000 690 oil/water

323-8/00 C/s. Curtis williams

SK REFERENCE NO:

MATERIAL PROFILE

Sefety-Kleen	If applicable, Intercompany Billing Facility #	Customer Number:		SK Line Of Business #:	Facility Profile #:
(SI) Use Only	R INFORMATION		ck if Billing	Information is same as G	enerstor Information
Generator Name	North Lily Mini			wy JBR Fnvironm	ental Consultants
-	No P.O. Box) 3 Miles		Billing Addre	s 8160 South H	ighland Drive
•	on US Highway 6				,
City/State/Zip	Eureka, Utah		City/State/Zip	Sandy, UT 84	093
Technical Contact	G . 11 D			Susan Kolan	
(801)	943-4144 Fax (801) 942–1852	Phone (80	1) 943-4144	Fax (801) 942-1852
		4000 01		, Suite 210, De	enver, CO 80202
	n (If different from Facility Addr			State Generating ID #	
SIC Code:		T Assistance Requested		heck if S& Transportation	Services are requested
	boati	_			
US DOT Proper S	N/A	NI/A	Packing Grat	ip (PG) N/A RQ N	/A
Hazard Class / Div	vision # ID # (UN / Non-Bulk Shipping Con	NA)		Bulk Shippin	
Size	Steel Poly Fiber	Quantity & Frequency		ainer Type	Quantity, Size & Frequency
55 Gal	☑ □ □ Appr	ox 8 one time or	JJA, G, Box	or Super Sack	
Gal			Hard Top	or Terped Bin	
Gal			_	(Turped) Trailer	
Gel				Vacuum Trailer	
-	MATERIAL & REGULATO	RY INFORMATION			
Name of Material	Uséd oil		<u> </u>		
Process Generatin		e maintenance			
	Mild Strong, Describe	petroleum			
Yes No			Yes No	Maria I DB Glandards	Partially Meets (Landfill Only)
	egulated or Licensed Radioactive	•			more paradons waster mixed as one)
	egulated Medical / Infectious Wa	· ·		_	sorbent biodegradable? Yes N
	egulated Benzene NESHAP Was			Exempt Waste; If Yes, lis	
	SCA Regulated PCB Waste (Lis			State Hazardous Waste;	State Code
	egulated Subpart CC Waste (VC	_	· _ <u>-</u>	EPA Hazardous Waste	
	egulated Ozone Depleting Substa				egories, e.g., D003 Water Reactive):
	ERCLA Regulated (Superfund) azardous Debris (Subject to alterna			•	·
i .	azardous Debris (Subject to attema Vaste Contains UHCs/Constituent				
	Vaste Contains UHCL/Constituent Yes, list in ☐ Sec. D <i>or</i> ☐ Co				
			Code: A _	Form Code: B	System Code: M
EPA Haz Waste		LIJ LI Source	C006: A	Total Code, D	
D. MATERIA	AL COMPOSITION 1/Physical Constituents: List at	I detectable components by che	mical name, ir	cluding physical material, e	.g., sorberat, debris.
ľ	ial Components & Composition	nom □wt:%		erial Components & Compo	
		⊠ vol % 60–80	7		
Used mo	otor oil	30-40	 		
water			· ·		
			· ·		
					+
	3				
	Castian Deputie	nes on the next page for	Elemental (anstituents 🗩	Range Total ≥ 100 °

SAFETY-KLEEN MATERIAL PROFILE (continued).											
Note: Completion of Sections D.2 & F is optional for: Analytical Profile (representative sample submitted; test results used to complete D.2 & F)											
Completion of Sections D.2, E, & F is optional for: Standard Industry Profile (Safety-Kleen historical data utilized to complete D.2, E, & F)											
D. MATERIAL COMP				(Matala surface	listed balan						
2. Elemental Constitu		reste contains No De					i				
Check either, Total An				enter data below. Constituent		Constituent	ppm				
Constituent ppm	Constituent ppm	Constituent	bben	CORDUNCTION	ppca						
Aluminum	Cadmium <0.5	Fluorine		Nickel		Sodium _					
Antimony	Chlorine	Lead	>0.02	Phosphorous		Sulfor _					
Araenic <0.2	Chromium <0.02	Lithium		Potassium		Thallium _					
Barium 0.2	Cobalt	Manganese		Selenium	<0.1	Titanium _					
Beryllium	Copper	Mercury	<0.0002	Silicon		Vanadium _					
_	Iodine	Molybdenum	•	Silver	<0.01	Zinc _					
Bromine		Check if this was		ctive Characte	ristics	***					
E. REACTIVE CHARA	ACIEKISIICS L] Creck if this was Yes No	er eminim 110 Her	Yes No							
Explosive		☐ 🖾 Oxidiz	er ·		Reactive Cyan	ide	ppm				
Shock Sensitive		□ 🔯 Water	Reactive		Reactive Sulfic	ie	ppm				
	•		eactive		Polymerizable						
□ ⊠ Pyrophoric	Ollan Baratta	AFRE	ygaay bi ∀ W								
Other Incompan											
F. MATERIAL PHYS	•	11CS @ 70°F.		1							
# of Phases 2 Co	black	Flash Point	•F (if < 73		iquids >20% H ₂ O						
	ecific Gravity N/A	☐ 73 - <100°F	□100 - 141°F		≤2 pH □>						
Sludge % ≤5 Vi	scosity cpsN/A	⊠142°F <200	°F		> 10 - < 12.5 pH	. □≥12.5	pH				
Solid % De	ensity N/A	Boiling Point (if <	130°F)	BIUs/	lb. or Range						
Powder %	libs/gal. libs/cu.ft.	Ash % (Bridgeport	Only)			. •					
Gas % Co	omments										
G. GENERATOR PRO	FILE CERTIFICATION	N .									
any attachments or sug- disclosed. I agree that generator may initiate and that this profile on	am an authorized agent of to pplements hereto is complet at if the sample test results further testing and evaluati rdification may be amended	e and accurate, and to indicate a discrepant on in accordance with accordingly.	nat all known or so	nation supplied ditions of the con	on this form. What	either Safety-Kie	generator				
Generator's Att	mwinder offinites					<u></u>					
Comments				· .							
				• •		<u> </u>					
				·							
		·				- - -					
SK Use Only	. U SK	os 🗆 skvs 🗖	Non-haz Evaluation	Stands	erd Industry Profil						
SK Sales Rep. Name			_ Employee #			ry/Branch#					
Process Approval #	Produc	Code or Part #	TRI	Flowpath#_	Pricin	g					
Waste Approval & Certifi	ication										
We certify acceptability	ty of this waste stream and	that all appropriate po	ermits have been obt	tained, as indicat	ed by Safety-Klee	n's facility approv /	val below:				
94644 VI	ried Rocility Single	N/	ume & Title (Printed	or Typed)		Date					
COURA S'ESSLA-VISITES	prized Facility Signature	Les		/ /		A1 W					

SK REFERENCE NO:

Get twento Silver City No servis.

SKREFERENCE NO: GW 60-06024

F50yds injut turn

155+2.50 = 57.50

wick Mou.	·	MATERIA	IL I KO	SK Line Of	Facility					
Safety-Kleen	If applicable, intercompany Billing Facility #	Customer Number:		Business #:	Profile #:					
(SI) Use Only	OR INFORMATION	C	Check if Billin	g Information is sume as	Generator Information					
Generator Name	North Lily Mini		· Billing Con	PPANY JBR ENVIRON	mental Consultants					
		South of	Billing Ack	ress 8160 South	Highland Drive					
Facility Address (,					
	on US Highway 6 Eureka, Utah		City/State/	Zip Sandy, UT 8	34093					
City/State/Zip			Billing Co	susan Kolan						
Technical Contac	Scott Page 943-4144 Fax (801) 942–1852	Phone (8	01) 943-4144	Fax (801) 942-1852					
Phone (801)		4000 01 -	narm Plac	e, Suite 210, 1						
Generator Location	Generator Location (1) different from Landy 110 HP UTP000001026 State Generating ID #									
SIC Code: U CESQU USQU CS CERTAIN										
B. SHIPPING	INFORMATION DO	TAssistance Requeste azardous solic		CHECK Y DA 1 PROSPORTAL						
US DOT Proper	Shipping Name	NI/A		roup (PG) N/A RQ _	N/A					
Hazard Class / D	ivision# N/A ID#(UN	/1(//)	Packing G	roup (PG) ************************************	ing Containers					
· · ·	Non-Bulk Shipping Co Steel Poly Fiber	ntainers Ouantity & Frequency	c	ontainer Type	Quantity, Size & Frequency					
Size 55 Col		one time only	y □Yď, Β	ox or Super Sack						
Oai				op or Turped Bin						
Gal				amp (Turped) Trailer	•					
Gal				Vacuum Trailer						
Gal		ODV INFORMATION								
	MATERIAL & REGULAT	DKX TUROKWYTIÓU								
Name of Materia	ــــــــــــــــــــــــــــــــــــــ	sed surplus c	hemical n	nix						
•		ised surprus c			·					
Odor: None	e Mild Strong, Describe			No	City Made II and III Only					
	Regulated or Licensed Radioactiv	e Waste			s or Partially Meets (Landfill Only)					
	Regulated Medical / Infectious W	aste		Commingled Waste	2 or more hazardous wasies mixed as one) , is sorbest biodegradable? Yes No					
	Regulated Benzene NESHAP Wa				, list reference, 40 CFR					
8	TSCA Regulated PCB Waste (L		<i>U</i>) —							
B	Regulated Subpart CC Waste (V	•	: . 0							
	Regulated Ozone Depleting Subs		. 0	EPA Hazardous Was	ne bestegories, e.g., DOG3 Water Resettive):					
	CERCLA Regulated (Superfund			te Codes (including my LLAC size	aread after a constitution of					
	Hazardous Debris (Subject to alter		is)	None - non-haza	ardous					
	Waste Contains UHCs/Constitue	nts Of Concern		MOHE - HOH-HAZO						
	If Yes, list in ☐ Sec. D or ☐ C				System Code: M					
EPA Haz Was	te Only Origin Code: 11	2 3 4 5 8	Source Code: A	Form Code: B	Dynam Cole. M					
D. MATER	HAL COMPOSITION		. L., alaminal wa-	e including physical materi	al, e.g., sorbent, debris.					
	CIAL COMPOSITION cal/Physical Constituents: List		wt %	Material Components & Cor						
	erial Components & Composition	, bber	lvol %							
	pentahydrate			dium tetra bor	ate - CAS 1330-43-4)					
	nitrate		15							
Soda a			15							
silica	sand		40							
 				· ·						
[L	Castley Dear	tinnes on the next par	re for Element	al Constituents	Range Total ≥ 100 %					

Dakety-	KLEEN I	VIALERIAL	INCIAL	A - dudical Banfila	(consequentialists ex	mole submitted:	lest results used to	complete D.2	kF)
Note: Comp	letion of Secti	ions D.2 & F is o	ptional for:	Analytical Profile Standard Indus	(representative se irv Profile (Safety	Kleen historica	data utilized to o	omplete D.2, E,	&F)
Compl	ction of Section	003 D.Z, E, & F 1 1007TION <i>(C-</i>	z opuonat roc:	CI OMMENTO HISTOR	_, (•		•	
2. Eleme	ntai Caustiiu	OSITION (Contents Marches	ck if this wast	contains No Dete	ctable Elements i	Metals, unless	listed below		1
Check either	☐Total Ar	alysis or 🔲	CLP Method	or Generator	Knowledge, then	eater data below.			
Constituent	ppar	Constituent	· ppm	Constituent	ppm	Constituent	ppon	Constituent	ppm
Aluminum	none	Cadmium	none	Fluorine	none	Nickel	none	Sodium	none
Antimony	none	Chlorine	none	Lead	none	Phosphorous	none	Sulfur	_none
Amenic	none	Chromium	none	Lithium	none	Potassium	none	Thallium	none
Barium	none	Cobalt	none	Manganese	none	Selenium	none	Titanium	none
Beryllium	none	Copper	none	Mercury	none	Silicon	none	Vanadium	none
Bromine	none	Lodine	none	Molybdenum	none	Silver	none	Zinc	none
E. REACT	IVE CHAR	ACTERISTIC		heck if this waste	e exkibits No Re	active Charact	eristics		
Yes No Yes No DR Reactive Cvanide ppm									
	xplosive		[_				ppm
	hock Sensitiv	e	[- ",			1		rr
☐ № Pyrophoric ☐ ☑ Air Reactive ☐ ☑ Polymerizable									
_		tibles; Describe							
F. MATEI	RIAL PHYS	ICAL CHARA	CTERISTIC	∑@70°F.		1			
# of Phases	1 c	colorW	nite F	lash Point	•F(if<7	3°F) pH □1	iquids >20% H _z C		Non-Aqueous
Liquid %.	0 s	pecific Gravity	N/A	☐ 73 -<100°F	□100 - 141°F	. []≤2pH □>	2-4pH 🛘	> 4 - 10 pH
Sludge %		iscosity cps	N/A	□142°F <200°	F 🔼 ≥200°F	. c	> 10 - < 12.5 pH		.5 pH
	100	Density	N/A	Soiling Point (if < 1	30°F)	I/A BTU's	/ lb. or Range	N/A	
Solid %		lbs/gal. []lbs	/ A	\sh % (Bridgeport (I/A		•	
Powder %				PH to (Tringshore)					
Gas %		Comments							
I hereby any atta disclose general and that	certify that I comments or such I agree the may initiate this profile of	applements heret	ed agent of the o is complete a test results in and evaluation be amended ac	1.4/19	IN ATT STATE OF A	mation supplied additions of the co	on this form the	at either Safety afety-Kleen and	Kieen or the
Comments		n-hazardo		rial			·		
	 					•		<u> </u>	
	<u></u>					·			
			- 						
er n A		·	∏ sKo	S C SKVS C	Non-haz Evaluati	on Stan	dard Industry Prof		#
SK Use On SK Sales R	-				_ Employee #			ory/Branch#	
Process Ap	•		Product C	code or Part#	TR	I Flowpath#	Price Price	ing	
		ification		_					nomel below
We cer	tify acceptabl	ility of this waste	stream and the	at all appropriate pe	amits have been o	btained, as indic	ated by Safety-Kk	en s iachny ap	lanasi nelam.
						ad as Tource!	 , -	′ 	'
Safet	-Kleen's Aut	horized Facility	Signature	Na	me & Title (Print	ea or 1 Abea)	المستخرج والمستجد والمستران		

SK REFERENCE NO:

Rubber liner

SK REFERENCE NO: GM- 01-0004 ?

+ 51+78+2.50 s 137.50

SERVICE.		MATERI	AL PKUI	SK Line Of	Facility	
Safety-Kleen	If applicable, Intercompany Billing Pacility #	Customer Number:		Business #:	Profile #:	
(SI) Use Only	OR INFORMATION		Check if Billin	g Information is same as	Generator Information	
Generator Name	North Lily Mini	ng Company	· Billing Con	puny JBR Environ		
The Allies Address (No P.O. Box) 3 Miles		Billing Add	ress 8160 South	Highland Driv	<u>re</u>
Eureka (on US Highway 6					
-	Eureka, Utah		City/State/2	ip Sandy, UT	84093	
City/State/Zip Technical Contac	0 11 0		Billing Con	ted Susan Kolan	·	
(004)	042 4144 =		Phone (801) 943-4144	_ Fax (801) 942	<u>2–1852 </u>
Phone (OUI)	943–4144 Fax on (If different from Focility Add	1800 Gle	narm Place	e, Suite 210, D	enver, co 802	202
	a (if aliferent from Facility Add	US EPAID # UTPO	00001026	State Generating ID	#	
SIC Code:		T Assistance Requests		Check if SK Transportate	ion Services are request	ed
	Non_h:	ezardous soli	d waste (r	ubber covered	with oil)	
US DOT Proper	Stribbing Name			roup (PG) RQ _		
Hazard Class / D	ivision # ID # (UN Non-Bulk Shipping Co			Bulk Shipp	ing Containers	
Size	Steel Poly Fiber	Quantity & Frequency		ontainer Type	Quantity, Size & Frequ	iency
55 _{Gal}	Ø 0 0 2-	one time onl	Ā □λ¶, Βο	x or Super Sack		
Gal			[] Hard To	op or []Turped Bin		
Gal				mp (Tarped) Trailer		
Gai				Vacuum Trailer		
C CENTER AT	MATERIAL & PECILAT	ORY INFORMATIO	٧			
No. of Motor's	Rubber conta	inment liner	contaminat	ed with.oil		
	ng The Material facil	ity cleanup				
T	Mild Strong, Describe			· · · · · · · · · · · · · · · · · · ·		
Yes No		- TVIda		lo D Mects LDR Standards	or Partially Meets (Lax	ifill Only)
_	Regulated or Licensed Radioactiv		,		or more hazardous wastes mix	
	Regulated Medical / Infectious W			Sorbent Added; If Yes,	is sorbent biodegradable?]Y≈□‰
	Regulated Benzene NESHAP Wa TSCA Regulated PCB Waste (L		ו ם נמ	Exempt Waste; If Yes,	list reference, 40 CFR	
H . •	18CA Regulated FCB Waste (2) Regulated Subpart CC Waste (V			A State Hazardous Wast	ie; State Code	
-	Regulated Ozone Depleting Subs	•		☐ EPA Hazardous Wast		
	CERCLA Regulated (Superfund		EPA Wast	c Codes (including any LDR sub	categories, e.g., D003 Water R	eactive):
	Hazardous Debris (Subject to alter		qs)	None		
•	Waste Contains UHCs/Constitue					
	If Yes, list in Sec. D or C					
EPA Haz Wast			Source Code: A	Form Code: B	System Code:	м
					ملتف من المنا	
1. Chemi	IAL COMPOSITION cal/Physical Constituents: List	all detectable component	s by chemical name	, including physical materia	l, e.g., sorbent, debris.	□wt %
	erial Components & Composition	, nemo]wt % N	faterial Components & Com	position ppm	□vol %
rubbe	r		97			
oil			1			
water			2			+
						
						1
		inues on the next pa	re for Flemente	d Constituents	Range Tota	≥ 100 %
I	Section. D con	mues on the next pu	- In Samual	_		Page 1 of 2

1	<i>[∑</i>	MATERIAL	PROFILE	(continued):			RENCE			
	التحجيب			a	representative sa	mple su	bmitted; te	st results used t	o complete D.2 & 1	Ď į
te: Compl	etion of Se	ctions D.2 & F ts op	contional for:	Analytical Profile (Standard Industr	ry Profile (Safety	-Kleen	historical	data utilized to	complete D.2, E, &	·F)
Comple										1
	4 0 0 4	Annual 7 Che	& if thus was	te contains No Detec	table Elements	/ Metals	, uniess u	пеа оесоч.		1
book either,	Total .	Analysis or 🔲 T	CLP Method	or Generator	Knowledge, then	Cons	stituent	ppm	Constituent	ppm
onstituent	ppm	Constituent	ppm	Constituent	ppm	1			Sodium	
iuminum ,		Cadmium		Fluorine	 	Nicke			Sulfur	
atimony		Chlorine		Lead		1	horous		Thallium _	
rsenic		Chromium		Lithium		1	sium		Titanium	
arium		Cobalt		Manganese		Selen			7	
eryllium		Copper		Mercury		Silic	oin		Vanadium	
romine		Iodine		Molybdenum		Silve			Zinc	
	IVE CHA	RACTERISTIC:	s D	Check if this waste	exhibits No Re	active (Characte	ristics		
es No	_ , _			Yes No			Yes №	Reactive Cys	mide	ppm
) () E	xplosive			Oxidizer				Reactive Sul		ppm
o o	hock Sensi	tive	· ·	□ □ Water R				Polymerizab		•
	yrophoric			☐ ☐ Air Read	nive					
		patibles; Describe								
MATER	RIAL PH	YSICAL CHARA	CTERISTI	CS @ 70° F.		1			- 11 EAT	A myonite
of Phases	2	Color blac	k	Flash Point	•F(if<7	3°F)	1		O or pH ZN	
iquid %	3	Specific Gravity	NA	☐ 73 -<100°F	□100 - 141°F	, .		≤ 2 pH □	>2-4pH 🔲>	
Sludge %		Viscosity cps _	NA	□142°F <200°	7			> 10 - < 12.5 p	H □≥12.5	pН
Solid %	97	Density	NA .	Boiling Point (if < 1	30°F)	AV	BTU's/	lb. or Range		
Powder %	-	lbs/gal. lbs	/ cu. ft.	Ash % (Bridgeport (Only)	ĄV]			,
-		Comments			·					
Gas %			TEXALTIO	N.						
I hereby any atta disclose general	y certify the achments of sed. I agree to may initely this profile.	at I am an authorize	ed agent of the complete compl	e generator, and want and accurate, and the indicate a discrepant on in accordance with accordingly.		mation anditions An	supplied s of the con	on this form, water the one of the contract between S		e generator
Comments										
									<u> </u>	
						ند جيي	-			
									· · ·	<u></u>
SK Use O	nlv		☐ SK	os 🗆 skvs 🗖		ion			ofile: SIP Index# ritory/Branch#	
	Rep. Name				_ Employee#				icing	
Process Ap				Code or Part #		RI Flow				
Waste App We ce	proval & (artify accep	Certification tability of this wast	e stream and	that all appropriate p	ermits have been	obtaine	d, as indica	ated by Safety-K	(Jeen's facility app	roval below:
!									/	
0-64	w. Vlacer's	Authorized Facility	Signature_	N.	une & Title (Prin	ned or 1	ypeu)			

Acid/water SKREFERENCE NO: GM 00-0627 \$4+56+2.50 = 142.5

		MATE	RIAL I	PRO	FILE	1841	15647	.50	142.5
Safety-Lleen	If applicable, Intercompany	Customer Number:			SK Line Of Business #:		Pacility Profile #:		
(SI) Use Only	Billing Facility # OR INFORMATION	Numba:	Chec	k if Billin	g Information i	is same as (ienerator Inf	ormation	
Generator Name	North Lily Mini	nor Company	-		mpuny JBR E				ants
Facility Address (South of		illing Add			lighland		
•	on US Highway 6								
City/State/Zip	Eureka, Utah			ity/State/			4093		
Technical Contact	Scott Page	· · · · · · · · · · · · · · · · · · ·	F	Billing Co	tect Susan	Kolan	1004	\ 042	1052
Phone (801)	943-4144 Fax, (801) 942-1			01) 943-4		Fax (801		
Generator Location	on (If different from Facility Addr	/		_	e, Suite	210, D	enver, C	0 802	202
SIC Code:	CESQG SQG		TP00000			erating ID #			
B. SHIPPING	INFORMATION DO	T Assistance Req	uested	_	Check if SK Tr				
US DOT Proper	Shipping Name Waste	corrosive						& wat	er)
Hazard Class / Di			601	Packing G	roup (PG) II	RQ ulk Shinnin	o , UUU 1g Containers		<u>:</u>
Size	Non-Bulk Shipping Cor Steel Poly Fiber	itamers Quantity & Freque	ncy	· c	ontainer Type	omble.	Quantity, Siz		ency
55 _{Gal}		ne time on		□λq, Βα	ox or Super S	sck			
Gal				∐Hard T	op or Tarped l	Bin			
Gal					emp (Tarped) Trai				
Gal	0 0 0			Tank o	Vacuum Tr	ailer			
	MATERIAL & REGULATO	RY INFORMA							
Name of Materia	**			·		· ·			
Process Generation	ng The Material Tank	washing	<u> </u>	<u>.</u>					
	Mild K Strong, Describe	acid		Yes 1	lo .				
Yes № П	Regulated or Licensed Radioactive	: Waste	•		Meets LDR		r 🔲 Partially M		
	legulated Medical / Infectious Wa						r more hazardous		
	Regulated Benzene NESHAP Was	•					sorbent biodeg		Yes 🗆 No
1	ISCA Regulated PCB Waste (Lis	t any PCB level in	Sec.D)		-		ist reference, 40		
•	Regulated Subpart CC Waste (VC		• : .			rdous Waste;		ie	
	Regulated Ozone Depleting Substa				EPA Hazar Codes (including a	rdous Waste nv LDR subca		03 Water Re	active):
•	CERCLA Regulated (Superfund)			Dago2					-
	Hazardous Debris (Subject to alterna		rancasos) _				· · · · · · · · · · · · · · · · · · ·		
	Waste Contains UHCs/Constituen fYes, list in □ Sec. D or □ Co		n						
1			Source C	ode: A	Form	Code: B	Syst	em Code: N	٤
EPA Hoz Waste D. MATERI	AT COMPOSITION			· · · ·					
1. Chemic	al/Physical Constituents: List a	ll detectable compo	ments by chem	rical name	, including physic	cal material,	e.g., sorbent, d		wt %
Mate	rial Components & Composition	bbar	∐wt % ⊠vol %		faterial Compone	nts & Comp	osition	ppm	□vol %
Hydrock	nloric acid		5–10						
Water			90-95						
				 					
				 				-	
				1					
1				1					

Section. D continues on the next page for Elemental Constituents

Range Total ≥ 100 %

Safety-Kleen	MATERIAL	Profile	(continued):	SK	REFER	ENC	NO:		
Vales Completion of Se	ctions D.2 & F is op	ntional for:		(representative sa ry Profile (Safety	mple subu	nitted; to storical	est results used to data utilized to c	occuplete D.2 & I complete D.2, E, &	r) F)
D. MATERIAL COM 2. Elemental Consti		* if this wast	e contains No Detec	zable Elements .	/Metals, u	nless li	isted below		
Check either, Total					enter data	below.		T 22	
Constituent ppm	Constituent	· ppm	Constituent	ppm	Constit	vent	ppm	Constituent	ppm
Aluminum	Cadmium		Fluorine		Nickel	•	 	Sodium	
Antimony	Chlorine		Load		Phospho			Sulfur _	
Armonic	Chromium .		Lithium		Potassiu			Thallium _	
Barium	Cobalt .		Manganese		Seleniu	m		Titanium	
Beryllium	Copper		Mercury		Silicon			Vanadium _	
Bromine	Iodine		Molybdenum		Silver			_ Zinc _	
E. REACTIVE CHA	RACTERISTICS		heck if this waste s No	exhibits No Re	active Ch	aractei es No	ristics		
Explosive		C				S	Reactive Cyan	jide	bbur
Shock Sensiti	ive		Water Re	eactive) 🖄	Reactive Sulfi	de	ppm .
☐ Ø Pyrophoric			Air Reac	tive		M	Polymerizable	;	•
	patibles; Describe								
F. MATERIAL PHY	SICAL CHARA	CTERISTIC	S @ 70°F.		1	- ,		•	
# of Phases 1	color gre	y F	lash Point	°F (if < 73	3°F) p	H 🗆 Li	quids >20% H ₂ O	or pH□No	-Aqueous
400			☐ 73 -<100°F	 []100 - 141°F		区	≤2pH ⊠ >	2-4pH □>	4 - 10 pH
Enquire 70		NI/A	□142°F <200°F			`		≥ 12.5 p	
	Viscosity ops	NI/A		N1 / N		٠.	b, or Range		
	Density		oiling Point (if < 13	2	\neg				
Powder %	☐lbs./ gal. ☐lbs./	oric IV	sh % (Bridgeport O	nly)	<u></u>				
Gas %	Comments								
G. GENERATOR PI I hereby certify that any attachments or a disclosed. I agree to generate may initia and that this profile Generator's. Comments	I am an authorized supplements hereto that if the sample the further testing an	agent of the g is complete ar test results include evaluation is amended accomply.	dicate a discrepancy in accordance with the ordingly.	t all known of st	mation suraditions of Ana	plied o	n this form, that tract between Sai	either Safety-Kla	en or the generator
·			· · · · · · · · · · · · · · · · · · ·						
		·							
SK Use Only	· · · · · · · · · · · · · · · · · · ·	☐ skos	☐ SKVS ☐ N	on-haz Evaluatio	n 🗆	Standa	rd Industry Profi		-
SK Sales Rep. Name				Employee #				ry/Branch #	· · · · · ·
Process Approval #		_ Product Co	ode or Part #	TRI	Flowpath	# _	Prici	······································	
Weste Approval & Cert We certify acceptab	tification	and that	-11 ammonariste nerr	-ite have heen oh	wained, as	indicate	ed by Safety-Klee	- n's facility approv	al below:
We certify acceptant	ality of this waste w	Tan and dies	· att afrikahrenne form	10 to 100 to 100	/house,		· · · · · ·	1	1
				e & Title (Printe	1 T	<u> </u>		Date	_ `



MATERIAL PROFILE

afety-Kleen SK) Use Only	If applicable, Intercompany Billing Facility #	Customer Number:		SK Line Of Business #:	Facility Profile #:
	OR INFORMATION	П	Check if Billing		e as Generator Information
enerator Name	North Lily Mining Compan	y	_ Billing Com		mental Consultants
cility Address	(No P.O. Box) 3 miles sout	h of Eureka	Billing Addr	ess 8160 South H	lighland Drive Suite A-4
on U.S. High					
ity/State/Zip	Eureka, Utah 84628		City/State/Z	ip Sandy, Utah 84	093
			Billing Cont	act Susan Kolan	
	3-4144 Fax	801-942-1852		1-943-4144	Fax 801-942-1852
enerator Locat	ion (If different from Facility A	ddress) 1800 Glenarm Pl	ace, Suite 210, D	enver, Colorado 8020	02
IC Code:		US EPA ID# UTP000		State Generating	
	INFORMATION \(\pi\) D		Name and Address of the Owner, where the Owner, which is the Owner, whi	Check if SK Transpor	rtation Services are requested
	Shipping Name Waste, So				
	Division # 8 ID # (UI		Packing Gro	oup (PG) <u>II</u> RQ	1,000
lazaru Class / L	Non-Bulk Shipping C	ontainers		Bulk Sh	ipping Containers Quantity, Size & Frequency
Size	Steel Poly Fiber	Quantity & Frequency		ntainer Type	Qualitity, Size & Frequency
Gal		ne time only		or □Super Sack	
Gal				p or Tarped Bin	N 87 26 6 18 1
Gal				np (Tarped) Trailer	
Gal			Tank or	☐ Vacuum Trailer	
	L MATERIAL & REGULA				
	al Sodium Hydroxide, Solid				
	ting The Material Tank clea				
Odor: Nor Yes No	ne Mild Strong; Describ	e	Yes No)	
	Regulated or Licensed Radioac	tive Waste			ards or Partially Meets (Landfill Or
	Regulated Medical / Infectious	Waste			te (2 or more hazardous wastes mixed as
	Regulated Benzene NESHAP				Yes, is sorbent biodegradable Yes
	TSCA Regulated PCB Waste	(List any PCB level in Sec.L			Yes, list reference, 40 CFR
	Regulated Subpart CC Waste (
	Regulated Ozone Depleting Su		⊠ □		R subcategories, e.g., D003 Water Reactiv
	CERCLA Regulated (Superfu			Codes (including any 222	
	Hazardous Debris (Subject to alt		D 010	1 1 1	
	Waste Contains UHCs/Constitution of the If Yes, list in ☐ Sec. D or ☐				
		[일본이 남은 아일이 됐다. 그는 경기에 됐다.	irce Code: A	Form Code: I	B System Code: M
EPA Haz Was	THE COMPOSITION				
D. MATER	ical/Physical Constituents: L	ist all detectable component	by chemical na	me, including physical	material, e.g., sorbent, debris.
	erial Components & Compositi	on ppm LIW	Ma Ma	terial Components & C	Composition ppm
		Øve 60-70			
	ydroxide, Solid Chunks/Debris	30-40			
Soils/Roci	1.b	1.00			
Colonium		2.6			
Selenium Arsenic		THE RESERVE THE PROPERTY OF THE PARTY OF THE			
Arsenic					THE PROPERTY OF STREET AND

SAFETY-KLEEN MATERIAL PROFILE (continued):

SK REFERENCE NO:

-	Sections D.2 & F is option	_						
Completion of	Sections D.2, E, & F is o	ptional for	: Standard Ind	ustry Profile (Sa	afety-Kleen hi	storical data utiliz	ed to complete D.2	2, E, & F)
	MPOSITION (Continu			- etable Element	to / Beatala and	ees listed below		
2. Elemental Con			e contains No Det					
Constituent ppm	al Analysis or 🛛 TCL	ppm	Constituent	ppm	Constituent		Constituent	ppm
		ppm	·	ppiii		Ppin		Ppin
Aluminum	Cadmium		Fluorine		Nickel		Sodium _	
Antimony	Chlorine		Lead		Phosphorous		Sulfur _	
Arsenic 2.6	Chromium		Lithium		Potassium		Thallium _	
Barium	Cobalt		Manganese		Selenium	1.00	_ Titanium _	
Beryllium	Copper		Mercury		Silicon		Vanadium _	
Bromine	Iodine		Molybdenum		Silver		Zinc	
E. REACTIVE CH	ARACTERISTICS	□ Ch	eck if this waste	exhibits No Re	active Charac	cteristics		
Yes No		Yes	-		Yes No			
☐ ☑ Explosive						Reactive Cya	nide	— ppm
☐ ☑ Shock Sens	sitive		☑ Water Re	active		Reactive Sulf	fide	ppm
☐ ☑ Pyrophoric			☑ Air React	ive		Polymerizabl	e	
Other Incom	mpatibles; Describe							
F. MATERIAL PH	YSICAL CHARACTE	ERISTICS	5 @ 70°F.					
# of Phases	Color Varies	Flas	sh Point	°F (if < 73	∘F) pH 🗀	Liquids >20% H₂0	O or pH⊠No	n-Aqueous
Liquid %	Specific Gravity N/.	<u>A</u> [] 73 - <100°F	□100 - 141°F	[] ≤ 2 pH	> 2 - 4 pH	4 - 10 pH
Sludge %	Viscosity cps N/A		142°F <200°F	⊠ ≥200°F] > 10 - < 12.5 pF	H ⊠≥ 12.5	ρΗ
Solid %	Density N/A	Boi	ling Point (if < 13	0°F)	BTU's	/ lb. or Range		
Powder %	□lbs./ gal. □lbs./ cu.	ft. Ash	n % (Bridgeport O	nly)				
Gas %	Comments							
	PROFILE CERTIFIC							
on any attachmen have been disclos Kleen or the gene and the generator	at I am an authorized age ats or supplements hereto sed. I agree that if the sa rator may initiate further and that this profile certi AGAGT FOR	is comple ample test testing an	ete and accurate, a results indicate a devaluation in accay be amended acc	and that all know discrepancy with cordance with the	wn or suspecte h any informat e terms and co	d hazards of the it ion supplied on t	material(s) describ his form, that eithe	ed herein er Safety-
Comments Plea	ase complete ASAP & co	ntact Chuc	k Lawrence when	completed.		<u> </u>		
	s greater than 50% caust							
\$160 per drum, treatm	nent & disposal		···					
\$70 per drum transpo	ortation							
<u> </u>								
SK Use Only	Г	¬skos	□ SKVS □ No	on-haz Evaluatio	n	ard Industry Profi		
SK Sales Rep. Name			!	Employee #		Territor	ry/Branch #	
Process Approval #		oduct Cod	e or Part #	TRI F	Flowpath #	Pricin	g	
Waste Approval & C		_				P	. Winamin En 1984.	1
We certify accept	tability of this waste strea	um and that	t all appropriate pe	rmits have been	obtained, as ii	idicated by Safety	-Kieen's facility a	pprovat
G-GA VIII	uthorized Facility Signat		N	& Title (Printed	or Typed)		/	/
Natetv∗K leen's A	umorized Excility Signat	ure	Name	ac i iuc (Priiiicu	OL LYDCU)		Daw	

PAT MUMBERA 200 NC. Pairo

RION: COP SODA ASH

EFFECTIVE DATE: 02/21/91

ORDER NO: 116465 PROD NO : 342640

NORTH LILY MINING CO

EUREKA JUT 84628

WATERS & ROGERS , SUBSIDIARY OF UNIVAR (408)435-8700 DORTON BUILDING , SEATTLE , WA 98104

-----EMERGENCY ASSISTANCE -----

EMERGENCY ASSISTANCE INVOLVING CHEMICALS CALL - CHEMIREC (800)424-9300

_____ FOR PRODUCT AND SALES INFORMATION -----

CONTACT YOUR LOCAL VAN WATERS & ROGERS BRANCH OFFICE AT VW&R SALT LAKE CTY OFFICE 801-328-1112 SALT LAKE CT, UT

-----PRODUCT IDENTIFICATION-----

SECT NAME: SODA ASH

CAS NO.: 497-19-8

MON NAMES/SYNONYMS: SODIUM CARBONATE, MSDS #: P1120

YAROUS; SODA ASH BENSE

ASH LIGHT

MULA: NA2 CO3

DATE ISSUED: 02/91

EULAR WEIGHT: 106 SUPERCEDES: 10/90

(ADD RATING (MANUFACTURER)

HMIS RATING

LTH: 2

IVITY: 0

TAL: NONE

HAZARD RATING SCALE:
0=MINIMAL 3=SERIOUS
1=SLIGHT 4=SEVERE

HEALTH: 2

REACTIVITY: 0

2=MODERATE

-----HAZARDOUS INGREDIENTS-----

EXPOSURE LIMITS, PPM

OBHA ACGIH OTHER
OMPONENT CAS NO. % PEL TLV LIMIT HAZARD
JOIUN CARBONATE (497-19-8) >99 NONE NONE NONE IRRITANT

PHYSICAL PROPERTIES

INN: COP SODA ASH

EFFECTIVE DATE: 02/21/91

ORDER NO: 116465 PROD NO : 342640

NORTH LILY MINING CO

EUREKA ,UT 84628

WATERS & ROGERS , SUBSIDIARY OF UNIVAR (408)435-8700 , MORTON BUILDING , SCATTLE , WA 98104

-----EHERGENCY ASSISTANCE -----

DE EMERGENCY ASSISTANCE INVOLVING CHEMICALS CALL - CHEMIREC (800)424-9300

CONTACT YOUR LOCAL VAN WATERS & ROGERS BRANCH OFFICE AT VWAR SALT LAKE CTY OFFICE 801-328-1112 SALT LAKE CT, UT

-----PRODUCT IDENTIFICATION-----

DIET NAME: SODA ASH

CAS NO.: 497-19-8

MON NAMES/SYNCNYMS: SODIUM CARBONATE, MSDS 4: P1120

YEROUS; SODA ASH BENSE A ASH LIGHT

MULA: NA2 CD3

DATE ISSUED: 02/91

ELLAR WEIGHT: 106

SUPERCEDES: 10/90

AND RATING (MANUFACTURER)

HMIS RATING

LTH: 2

IVITY: 0 CTAL: NONE

HAZARD RATING SCALE: HEALTH: 2
0=MINIMAL 3=SERIOUS FIRE: 0
1=SLIGHT 4=SEVERE REACTIVITY: 0

2=MODERATE

-----HAZARDOUS INGREDIENTS-----

A CONTRACTOR OF THE PARTY OF TH

EXPOSURE LIMITS, PPM
OSHA ACGIH OTHER
OSHA ACGIH OTHER
HAZARD
DIUM CARBONATE (497-19-8) >99 NONE NONE TRRITANT

ORT : S RO:

TING POINT, L CITIC GRAVITY EARANCE AND CL ORLESS, WHITE

ONTILE (BY VOL.

IMALED: REMOVE V

CESE OF EYE CONTACT EX FOR 15 MINUTES, L IMMEDIATE MEDICAL A

SE OF SKIN CONTACT: LR. REMOVE CONTAMINAT. PIECE ATTENTION IF IRRIV

SWALLOWED: DO NOT INDUC MILK. GET IMMEDIATE MED. IT TO AN UNCONSCIOUS OR C

ES TO PHYSICIAN: NONE

----HEALTH

HERY ROUTES OF EXPOSURE: IN.

INS AND SYMPTOMS OF EXPOSURE INHALATION: BREATHING DUST NO COUGHING AND CHEST DISCOMFOLE NASAL SEPTUM.

aND ause Damage

EYE CONTACT: DUSTS WILL IRRITA DAMAGE THE EYES. AND PROLONGED CONTACT

RKIN CONTACT: PROLONGED OR REPEATED CONTACT WITH THE DUST MAY REPEATED CONTACT WITH THE DUST MAY CAUSE FOR IRRITATION OR BURNS.

BUALLOUED: SWALLOWING LARGE QUANTITIES MAY CAUSE NAUSEA, VOMITING,

VAN WATERS & ROGERS INC. ATEPIAL DAMETY DATA SHEET

PAGE: 000

TON: 009 SODA ASH

EFFECTIVE DATE: 02/21/91

ORDER NO: 116465 PROD NO : 342640

INIC EFFECTS OF EXPOSURE: MAY CAUSE SENSITIZATION.

CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NOME REPORTED.

TCXICITY DATA----

RATS LD50 = 4 G/KG

RABBITS 500 MG/24 HR, MCDERATE IRRITATION

IN: NO DATA FGUND.

ICITY: THIS MATERIAL IS NOT CONSIDERED TO BE A CARCINOGEN TONAL TOXICOLOGY PROGRAM, THE INTERNATIONAL AGENCY FOR CANCER, OR THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

NONE

-----PERSONAL PROTECTION----

LOCAL MECHANICAL EXHAUST VENTILATION CAPABLE OF MAIN-"ISSIONS AT THE POINT OF USE BELOW THE PEL.

'ECTION: IF USE CONDITIONS GENERATE DUSTS, WEAR A NIGSH-...RATOR APPROPRIATE FOR THOSE EMISSION LEVELS. APPROPRIATE .JRS MAY BE A FULL FACEPIECE OR A HALF MASK AIR-PURIFYING CART-RESPIRATOR WITH PARTICULATE FILTERS, A SELF-CONTAINED BREATHING APATUS IN THE PRESSURE DEMAND MODE, OR A SUPPLIED-AIR RESPIRATOR.

PROTECTION: CHEMICAL GOGGLES AND FULL FACE SHIELD. IT IS GENERALLY OGNIZED THAT CONTACT LENSES SHOULD NOT BE WORN WHEN WORKING WITH CALS BECAUSE CONTACT LENSES MAY CONTRIBUTE TO THE SEVERITY OF AN NJURY.

CTIVE CLOTHING: LONG-SLEEVED SHIRT, TROUSERS, SAFETY SHOES, RUBBER VES, AND RUBBER APRON.

ER PROTECTIVE MEASURES: AN EYEWASH AND SAFETY SHOWER SHOULD BE AND READY FOR USE.

-----FIRE AND EXPLOSION INFORMATION-----

POINT, DEG F: N/A

METHOD USED: N/A

LOWER: N/A

LOWER: N/A

LOWER: N/A

GNITION TEMPERATURE DEGREE NOT APPLICABLE

INCUISHE DIAL VUSE DATERUSPRAY, DRY CHEMICAL 7 COZ MOR, ALODHOLA

SION: COV SOUP ASH

EFFECTIVE DATE: 02/21/91

ORDER NO: 116465 PROD NO: 342640

FIRE FIGHTING PROCEDURES: FIRE FIGHTERS SHOULD WEAR SELF-FATNED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. USE WATER AY_10 COOL NEARBY CONTAINERS AND STRUCTURES EXPOSED TO FIRE.

ELLE FIRE AND EXPLOSION HAZARDS: EXTINGUISH ALL NEARBY SOURCES OF

BILITY: STABLE POLYMERIZATION: WILL NOT OCCUR SITIONS TO AVOID: OPEN FLAMES, WELDING ARCS, OR OTHER HIGH TEM-ATORE SOURCES WHICH MAY INDUCE THERMAL DECOMPOSITION.

EFFALS TO AVOID: ACIDS, ALUMINUM POWDER, FLUORINE, FHOSPHOROUS
ICKIDE, SULFURIC ACID AMMONICAL SILVER NITRATE AND MOLTEN LITHIUM.
CTS WITH HYDRATED LIME IN THE PRESENCE OF MOISTURE TO FORM CAUSTIC SODA,
DEROSIVE.

ROOUS DECOMPOSITION PRODUCTS: MAY LIBERATE CARBON MONOXIDE,

_____SPILL, LEAK, AND DISPOSAL PROCEDURES----

TO TAKE FOR SPILLS OR LEAKS: WEAR PROTECTIVE EQUIPMENT INCLUDING BER BOOTS, RUBBER GLOVES, RUBBER APRON, AND A SELF-CONTAINED ATHING APPARATUS IN THE PRESSURE DEMAND MODE OR A SUPPLIED-AIR PRATOR. IF THE SPILL OR LEAK IS SMALL, A FULL FACEPIECE AIR-IVING CARTRIDGE RESPIRATOR EQUIPPED WITH PARTICULATE FILTERS MAY BE ISFACTORY, IN ANY EVENT, ALWAYS WEAR EYE PROTECTION. FOR SMALL LS, SWEEP UP AND DISPOSE OF IN DOT-APPROVED WASTE CONTAINERS. FOR SPILLS, SHOVEL INTO DOT-APPROVED WASTE CONTAINERS. KEEP OUT OF ERS, STORM DRAINS, SURFACE WATERS, AND SOIL.

PLY WITH ALL APPLICABLE GOVERNMENTAL REGULATIONS ON SPILL REPORTING, MANDLING AND DISPOSAL OF WASTE.

POSAL METHODS: DISPOSE OF CONTAMINATED PRODUCT AND MATERIALS USED CLEANING UP SPILLS OR LEAKS IN A MANNER APPROVED FOR THIS MATERIAL. IS LT APPROPRIATE FEDERAL, STATE AND LOCAL REGULATORY AGENCIES TO EXTAIN PROPER DISPOSAL PROCEDURES.

E: EMPTY CONTAINERS CAN HAVE RESIDUES, GASES AND MISTS AND ARE CT TO PROPER WASTE DISPOSAL, AS ABOVE.

_____SPECIAL PRECAUTIONS----

GE AND HANDLING PRECAUTIONS: STORE IN A COOL, DRY, WELL-VENTILATED CESTORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DE STORE AWAY FROM ALL DTHER CHEMICALS AND POTENTIAL SOURCES DE STORE AWAY FROM ALL DE STORE

8T ALMBER: 709

). P1120 .

COP SCDA ASH

EFFECTIVE DATE: 02/21/91

ORDER NO: 115465 PROB NO : 342640

AMINATION. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. DO NOT P ESSURE TO EMPTY CONTAINER. WASH THOROUGHLY AFTER HANDLING. CO GET IN EYES, ON SKIN, OR ON CLOTHING.

AND MAINTENANCE PRECAUTIONS: NONE.

ER_PRECAUTIONS: CONTAINERS, EVEN THOSE THAT HAVE BEEN EMPTIED, WILL PRODUCT RESIDUE AND VAPORS. ALWAYS OBEY HAZARD WARNINGS AND CHATY CONTAINERS AS IF THEY WERE FULL.

-----ECOLOGICAL INFORMATION SECTION----

DATA FOUND

-----OTHER REGULATORY INFORMATION-----

TION 313: NONE

BITION 45: SEE BELOW

THON 313 & PROP. 65: SEE BELOW

TION 313 (WITH CHEMICALS LISTED): NONE

PESITION 65 (WITH CHEMICALS LISTED):

CAS NO. MICAL(s)

TRACES 7440-38-2

TRACES 7440-47-3

TRACES 7439-92-1

CHUSETTS: UNDER THE MASSACHUSETTS RIGHT-TO-KNOW LAW, HAZARDOUS ANCE AND EXTRAORDINARILY HAZARDOUS SUBSTANCES COMPONENTS PRESENT IN S PRODUCT WHICH REQUIRES REPORTING ARE:

ORDINARILY HAZARDOUS SUBSTANCES CAS NO.

NUMBER: 703 VAN WATERS & RODERS INC. NO. 21130 MATERIAL SAFETY DATA SHEET UAN WATERS & REGERS INC.

TON: COP SODA ASH

EFFECTIVE DATE: 02/21/71

ORDER NO: 116465 PROD NO : 342640

RNIA SCAQMD: NONE

THE INGREDIENTS OF THIS PRODUCT ARE ON THE TSCA INVENTORY.

RODUCT CONTAINS THE FOLLOWING CHEMICAL(S) CONSIDERED BY THE STATE IFORNIA'S SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 POSITION 65) AS CAUSING CANCER OR REPROBUCTIVE TOXICITY AND FOR WARNINGS ARE NOW REQUIRED:

CHEMICAL

________REVISION----

PO: ADDED SYNONYM.

ADDED: MOLECULAR WEIGHT, HMIS RATING, NOTES TO PHYSICIAN, JIONITION TEMPERATURE, MATERIALS TO AVOID, PH, % VOLATILE, ECOLOGICAL DENATION, OTHER RESULATORY INFORMATION 1,2,3,4,5-% WT., 7,8,9,10

91: ADDED: SYNONYM

) NT NUMBER: 703 1 MD: 191120

WAN MAYING & ROOTABLIED. PROPRIATE WATERY DATA CHEER

THE ACC SODA ASH

EFFECTIVE DATE: 02/01/91

ORDER NO: 113465 PROD NO: 342640

ACT: MSDS COORDINATOR VW&R SALT LAKE CTY OFFICE OURING SUSINESS HOURS, FACIFIC TIME (408)435-3700

24/91 10:50 PRODUCT: 342640 CUST NO: 121045 ORDER NO: 11/465

-----NOTICE -----

VAN WATERS & ROGERS INC. ("VUGR") EXPRESSLY DISCLAIMS ALL EXPRESS OR

LIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE,

RESPECT TO THE FRODUCT OR INFORMATION PROVIDED HEREIN. **

ALL INFORMATION APPEARING HEREIN IS EASED UPON DATA OBTAINED FROM THE UNICTURER AND/OR RECOGNIZED TECHNICAL SOURCES. WHILE THE INFORMATION IS 16/20 TO BE ACCURATE, VWAR MAKES NO REPRESENTATIONS AS TO ITS ACCURACY OR FICIENCY. CONDITIONS OF USE ARE BEYOND VWARS CONTROL AND THEREFORE USERS ASSENDED TO VERIFY THIS DATA UNDER THEIR GWN OPERATING CONDITIONS TO ENINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PARTICULAR PURPOSES AND THEY UME ALL RISKS OF THEIR USE, HANDLING, AND DISPOSAL OF THE PRODUCT, OR FROM FUBLICATION OR USE OF, OR RELIANCE UPON, INFORMATION CONTAINED HEREIN. SINFORMATION RELATES ONLY TO THE PRODUCT BESIGNATED HEREIN, AND DOES NOT ATE TO ITS USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY OTHER CESS.

* * * END OF MSDS * *

ORT NUMBER: 703 8 MO: P1169

VAN WATERS & ROGERS INC. MATERIAL SAFETY DATA SHEET

PAGE: 001

ORDER NO: 112403 100 880 8RODSNO-1 350170

NORTH LILY MINING CO

EUREKA ,UT 84628

WATERS & ROGERS , SUBSIDIARY OF UNIVAR (408)435-8700 RORTON BUILDING , SEATTLE , WA 98104

-----EMERGENCY ASSISTANCE -----

EMERGENCY ASSISTANCE INVOLVING CHEMICALS CALL - CHEMTREC (800)424-9300

---- FOR PRODUCT AND SALES INFORMATION -----

CONTACT YOUR LOCAL VAN WATERS & ROGERS BRANCH OFFICE AT VWAR SALT LAKE CTY OFFICE 801-328-1112 SALT LAKE CT, UT

MUN NAMES/SYNONYMS: NITRIC ACID, JUM SALT; NITRATE DE COMA JIUM SALT; NITRATE OF SODA; NITRATINE; LAN NITRATE; SODIUM NITRATE 35%

CAS NO.: 7631-99-4 VW&R CODE: P1167

MULA: NA N DS D RATING (NFPA 49) EALTH: 0 FIRE: 0 REACTIVITY: 0 PECIAL: OXY

DATE ISSUED: 01/90 SUPERCEDES: 08/89 HAZARD RATING SCALE: O=MINIMAL 3=SERIOUS 1=SLIGHT 4=SEVERE 2=MODERATE

------HAZARDOUS INGREDIENTS-----

EXPOSURE LIMITS, MG/M3

OSHA ACGIH OTHER

COMPONENT X PEL TLV LIMIT HAZARO SODIUM NITRATE >99 15 10 2 (BASF) DXTDIZER (NUISANCE (NUISANCE (NUISANCE))

Continue de la contraction de

ORT NUMBER: 703

VAN WATERS & ROGERS INC. MATERIAL SAFETY DATA SHEET

PAGE: 002

THE REPORT OF THE PARTY OF THE

QQ48 SODIUM NITRATE REVISION OF: 01/16/90

ORDER NO: 112403 PROD ND : 350170

EARANCE AND ODOR: WHITE EVAPORATION RATE (BUTYL ACETATE=1): 0

DER; ODORLESS

_____FIRST AID MEASURES----

INHALED: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NOT MING. GET IMMEDIATE MEDICAL ATTENTION.

CASE OF EYE CONTACT: IMMEDIATELY FLUSH EYES WITH LOTS OF RUNNING EFFOR 15 MINUTES, LIFTING THE UPPER AND LOWER EYELIDS OCCASIONALLY. MEDIATE MEDICAL ATTENTION.

CASE OF SKIN CONTACT: IMMEDIATELY FLUSH SKIN WITH LOTS OF RUNNING FOR 15 MINUTES. REMOVE CONTAMINATED CLOTHING AND CHOES; WASH E REUSE. OET IMMEDIATE MEDICAL ATTENTION.

STALLOWED: IF CONSCIOUS, IMMEDIATELY INDUCE VEMITING BY GIVING 2 ES OF WATER AND STICKING A FINGER DOWN THE THROAT. GET IMMEDIATE ZAL ATTENTION. DO NOT GIVE ANYTHING TO AN UNCONSCIOUS OR CONVULSING

----HEALTH HAZARD INFORMATION----

RY ROUTES OF EXPOSURE: SKIN OR EYE CONTACT

SHS AND SYMPTOMS OF EXPOSURE

INHALATION: BREATHING DUST MAY IRRITATE THE NOSE, THROAT, MUCOUS 12 ANES AND RESPIRATORY TRACT, CAUSE COUGHING AND CHEST DISCOMFORT, PRINESS OF BREATH, HEADACHE, AND DIZZINESS.

YE CONTACT: DUSTS MAY IRRITATE THE EYES WITH SYMPTOMS INCLUDING DNESS, ITCHING, AND PAIN.

KIN CONTACT: CONTACT WITH THE DUST MAY IRRITATE THE SKIN, CAUSING SS. ITCHING AND PAIN.

WALLOWED: SWALLOWING MAY CAUSE GASTRO ENTERITIS AND ABDOMINAL FURGING AND DIVRESIS CAN BE EXPECTED REPEATED INGESTION OF RGE AMOUNTS CAN LEAD TO CYANOSIS, CONVULSIONS, PARALYSIS OR COMA RE CASES OF THE PROPERTY OF THE PROPERTY OF THE STATE OF

NUMBER: 709 WAN WATERS & ROGERS INC. P1169 MATERIAL SAFETY DATA SHEET

GO44 SODIUM NITRATE AND RESE

REVISION OF: 01/16/90

ORDER NO: 112403 PROD NO + 350170

----CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: INDIVIDUALS WITH ISTORY OF KIDNEY OR LUNG DISEASE MAY BE MORE SUSCEPTIBLE TO THE ECIS OF THIS SUBSTANCE.

____TOXICITY DATA----

HUMAN LDLO = 500 MG/KG; RAT LDLO = 200 MG/KG; HUMAN DEADLY DOSE OUT 15 GRAMS; RAT LD50 = 4.8 G/KG

NM: NO DATA FOUND

ACATION: NO DATA FOUND

C NOGENICITY: THIS MATERIAL IS NOT CONSIDERED TO BE A CARCINGGEN THE NATIONAL TOXICOLOGY PROGRAM, THE INTERNATIONAL AGENCY FOR EARCH ON CANCER, OR THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

DATA: PROLONGED EXPOSURE TO SODIUM NITRATE CAUSES BLOOD DISORDERS _MFANTS. OLIN CORPORATION, A MANUFACTURER, REPORTS THIS PRODUCT NOT TO BE MUTAGENIC.

-------PERSONAL PROTECTION-----

LATION: LOCAL MECHANICAL EXHAUST VENTILATION CAPABLE OF MAIN-INTING DUST EMISSIONS AT THE POINT OF USE BELOW THE FEL.

SERATORY PROTECTION: IF USE CONDITIONS GENERATE DUSTS, WEAR A NIOSH-PEVED RESPIRATOR APPROPRIATE FOR THOSE EMISSION LEVELS. APPROPRIATE SPIRATORS MAY BE A FULL FACEPIECE OR A HALF MASK AIR PURIFYING CART-DEF RESPIRATOR WITH PARTICULATE FILTERS, A SELF-CONTAINED BREATHING PRATUS IN THE PRESSURE DEMAND MODE, OR A SUPPLIED AIR RESPIRATOR.

The state of the s E_PROTECTION: CHEMICAL GOGGLES UNLESS A FULL FACEPIECE RESPIRATOR IS WORN TO TO GENERALLY RECOGNIZED THAT CONTACT LENSES SHOULD NOT BE WHEN WORKING WITH CHEMICALS BEGAUSE CONTACT LENSES MAY CONTRIBUTE THE SEVERITY OF AN EYE INJURY

ECTIVE CLOTHING: LONG-SLEEVED SHIRT, TROUSERS, SAFETY SHOES, RUBBER VEST SAND RUBBER APRON.

TO RESTRUCT THE ASSESSMENT AND STREET AND STREET ASSESSMENT OF THE PROPERTY OF

BE THE PROPERTY OF THE PROPERTY OF

TRANSPORTER STATE OF THE STATE

JRT NUMBER: 703 VAN WATERS & ROGERS INC. DE PILOP

PAGE: 004

DRDER: NO: 112403 PROD. NO : 350170

MUISHING MEDIA: FLOOD WITH WATER, OR USE APPROPRIATE MEDIUM FOR UISHING SURROUNDING FIRE.

CIAL FIRE FIGHTING PROCEDURES: FIRE FIGHTERS SHOULD WEAR SELF-TA NED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. USE WATER AY TO COOL NEARBY CONTAINERS AND STRUCTURES EXPOSED TO FIRE.

SULL FIRE AND EXPLOSION HAZARDS: THIS SUBSTANCE IS A STRONG OXIDIZER #S HEAT OF REACTION WITH REDUCING AGENTS OR COMBUSTIBLES MAY CAUSE ITION. THIS MATERIAL IS EXPLOSIVE WITH SHOCK, HEAT, OR FRICTION. NITRATE DECOMPOSES EXPLOSIVELY WHEN HEATED OVER 1,000 DEG F. S RODUCT MAY FUSE OR MELT IN LARGE FIRES AND USING WATER TO EX-GUISH MAY RESULT IN SCATTERING OF MOLTEN MATERIAL. WATER SHOULD NOT APPLIED TO MOLTEN SALT BATHS.

-----HAZARDOUS REACTIVITY--

ITY: STABLE TIONS TO AVOID: NONE POLYMERIZATION: WILL NOT OCCUR

EMTALS TO AVOID: REACTS WITH ACIDS TO EMIT NITROSEN DIOXIDE CASES. OT WITH OXIDIZABLE MATERIALS SUCH AS THE FOLLOWING MAY SE AN EXPLOSION: BARIUM RHODANIDE, BORON PHOSPHIDE, CYANIDES, ILM THIOSULFATE, SODIUM HYPOPHOSPHITE, SULFUR PLUS CHARCOAL, POWDERED MENUM, ALUMINUM OXIDE. FIBROUS ORGANIC MATERIALS SUCH AS WOOD, JUTE THER CELLULOSIC MATERIALS CAN BECOME HIGHLY COMBUSTIBLE BY NITRATE REGNATION. ALSO AVOID TRICHLOROETHYLENE, ZINC, AND SODIUM ACETATE.

DOUS DECOMPOSITION PRODUCTS: WILL LIBERATE OXIDES OF NITROGEN.

ION TO TAKE FOR SPILLS OR LEAKS: WEAR PROTECTIVE EQUIPMENT INCLUDING BER BOOTS, RUBBER GLOVES, RUBBER APRON, AND A SELF-CONTAINED HING APPARATUS IN THE PRESSURE DEMAND MODE OR A SUPPLIED AIR RATOR. IF THE SPILL OR LEAK IS SMALL, A FULL FACEPIECE AIR-IFYING CARTRIDGE RESPIRATOR EQUIPPED WITH PARTICULATE FILTERS MAY BE FACTORY. IN ANY EVENT, ALWAYS WEAR EYE PROTECTION, FOR SMALL S. TSWEEP UP AND DISPOSE OF INKOOS TRANSPORTATION OF THE PROPERTY OF THE PROPE SOME SET SHOVELS (Vete 110) FORFAMEL UNSUE GOVERNMENT STEEL SOLVERS (IN THE SECOND SEC

Topicus (1885) in Fine (1885) in the spanning and the spanning state (1885) is the spanning of

NUMBER: 703 1:0813169

gard of the Commission

VAN WATERS & ROGERS INC. VAN WATERS & ROGERS INC. MATERIAL SAFETY DATA SHEET

PAGE: 005

REVISION OF: 01/16/90

A Committee of the committee of the committee of

REVISION OF: 01/16/90
ORDER NO: 112403
PROD NO: 350170

EMPTY CONTAINERS CAN HAVE RESIDUES, GASES AND MISTS AND ARE JE T TO PROPER WASTE DISPOSAL, AS ABOVE.

-----SPECIAL PRECAUTIONS E AND HANDLING PRECAUTIONS: STORE IN A COOL, DRY, WELL-VENTILATED CE. STORE AWAY FROM ALL OTHER CHEMICALS AND POTENTIAL SOURCES OF INATION. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. PROTECT HYSICAL DAMAGE. DO NOT USE PRESSURE TO EMPTY CONTAINER. WASH ROUGHLY AFTER HANDLING. DO NOT GET IN EYES, ON SKIN, OR ON CLOTHING.

AND MAINTENANCE PRECAUTIONS: NONE.

ER PRECAUTIONS: CONTAINERS, EVEN THOSE THAT HAVE BEEN EMPTIED, WILL FRODUCT RESIDUE AND VAPORS. ALWAYS OBEY HAZARD WARNINGS AND DEE EMPTY CONTAINERS AS IF THEY WERE FULL.

-----REVISION----

70: ADDED SYNONYM.

TACT: MSDS COORDINATOR TO VUER SALT LAKE CTY OFFICE DURING BUSINESS HOURS, PACIFIC TIME 44 64 64087435-8700 15/91 11:15 PRODUCT: 350170 CUST NO: 121045 ORDER NO: 112403

N WATERS & ROGERS INC. ("VW&R") EXPRESSLY DISCLAIMS ALL EXPRESS OR

ED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE,

ESPECT TO THE PRODUCT OR INFORMATION PROVIDED HEREIN. **

ALL INFORMATION APPEARING HEREIN IS BASED UPON DATA OBTAINED FROM THE NUFACTURER AND/OR RECOGNIZED TECHNICAL SOURCES. WHILE THE INFORMATION IS LEVED TO BE ACCURATE, VW&R MAKES NO REPRESENTATIONS AS TO ITS ACCURACY OR FICIENCY. CONDITIONS OF USE ARE BEYOND VW&RS CONTROL AND THEREFORE USERS E RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR DWN OPERATING CONDITIONS TO RMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PARTICULAR PURPOSES AND THEY S ME ALL RISKS OF THEIR USE, HANDLING, AND DISPOSAL OF THE PRODUCT, OR FROM E PUBLICATION OR USE OF, OR RELIANCE UPON, INFORMATION CONTAINED HEREIN. INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT TE TO ITS USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY OTHER

END OF MSDS

NUMBER: 703

VAN WATERS & ROGERS INC. MATERIAL SAFETY DATA SHEET

PAGE: 001

SION: 007 BURAX PENTAHYDRATE

REVISION OF: 12/28/89

ORDER NO: 109878 PROD NO : 225671

NORTH LILY MINING CO

EUREKA ,UT 84628

EMERGENCY ASSISTANCE INVOLVING CHEMICALS CALL - CHEMTREC (800)424-9300

----- FUR PRODUCT AND SALES INFORMATION -----

CONTACT YOUR LOCAL VAN WATERS & ROGERS BRANCH OFFICE AT VW&R SALT LAKE CTY OFFICE 801-328-1112 SALT LAKE CT, UT

DECT NAME: BORAX PENTAHYDRATE DCT NAME: BURAX PENTAHYURATE CHS NO.: 1350 S DN NAMES/SYNONYMS: SOBIUM TETRABORATE VW&R CODE: P1113 NTAHYBRATE

CAS NO.: 1330-43-4

RULA: NA2 84 07 5H20 ZARU RATING (MANUFACTURER) JIEALTH: 1

DATE ISSUED: 11/89 SUPERCEDES: 08/89 SUPERCEULS.
HAZARD RATING SCALE: O=MINIMAL 3=SERIOUS 1=SLIGHT 4=SEVERE

2=MODERATE

FIRE: 0 REACTIVITY: 0 SPECIAL: NONE

AHYURATE

-----HAZARDOUS INGREDIENTS-----HAZARDOUS

EXPOSURE LIMITS, PPM OSHA ACGIH OTHER

COMPONENT CAS NO. % PEL TLV LIMIT HAZARD IRRITANT TOTUM TETRABORATE 1330-43-4 >99 NONE 5 NONE IRRITANT

---PHYSICAL PROPERTIES----

PHYSICAL PROPERTIES

VAPOR PRESSURE NO HEAVY NO LONG PROPERTIES

VAPOR PRESSURE NO HEAVY NO LONG PROPERTY NO HEAVY NO LONG PROPERTY NO LONG PR

NUMBER: 703 8 NO: P1113

VAN WATERS & RUGERS INC. MATERIAL SAFETY DATA SHEET

PAGE: 002

SION: 007 BURAX PENTAHYURATE

REVISION OF: 12/28/89

URDER NO: 109878 PROD NO : 225671

-----FIRST AID MEASURES-----

HALED: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NOT ATHING. GET IMMEDIATE MEDICAL ATTENTION.

SE OF EYE CONTACT: IMMEDIATELY FLUSH EYES WITH LOTS OF RUNNING TER FOR 15 MINUTES, LIFTING THE UPPER AND LOWER EYELIDS OCCASIONALLY. IMMEDIATE MEDICAL ATTENTION.

CASE OF SKIN CONTACT: IMMEDIATELY WASH SKIN WITH LOTS OF SOAP AND TER. REMOVE CONTAMINATED CLOTHING AND SHOES; WASH BEFORE REUSE. GET DITAL ATTENTION IF IRRITATION PERCENTS WETER WASHING.

SWALLOWED: IF CONSCIOUS, IMMEDIATELY INDUCE VOMITING BY GIVING 2 ASSES OF WATER AND STICKING A FINGER DOWN THE THROAT. GET IMMEDIATE JI AL ATTENTION. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS CONVULSING PERSON.

-----HEALTH HAZARD INFORMATION-----

ARY ROUTES OF EXPOSURE: SKIN OR EYE CONTACT, INHALATION.

AND SYMPTOMS OF EXPOSURE INHALATION: BREATHING DUST MAY IRRITATE THE NOSE AND THROAT AND . COUCHING AND CHEST DISCOMFORT.

TYE CONTACT: DUSTS MAY IRRITATE THE EYES.

SKIN CONTACT: NO IRRITATION IS LIKELY AFTER BRIEF CONTACT BUT MAY RITATING AFTER PROLONGED CONTACT.

BWALLOWED: NONE CURRENTLY KNOWN.

RONIC EFFECTS OF EXPOSURE: NO SPECIFIC INFORMATION AVAILABLE.

DECAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE REPORTED.

____TOXICITY DATA----

RATS LD50= 3.4 G/KG

ALI RABBITS LD50= 12 G/KG

The straight has some an enthromany affiners and the straight of the configurations.

Paring area cases that as was a first of the contract and the contract contract and the contract contract and the contract contra ente divination en mode de la company de company de la company de la company de la company de la company de la La company de la company de la company de la company de la company de la company de la company de la company d

ORT NUMBER: 703 VAN WATERS & ROGERS INC. 38 NO: P1113 MATERIAL SAFETY DATA SHEET

PAGE: 003

RSION: 007 BORAX PENTAHYDRATE

REVISION OF: 12/28/89

ORDER NO: 109878 PROD NO : 225671

DATA: NONE

-----PERSONAL PROTECTION----

NT LATION: GENERAL ROOM VENTILATION.

SHERATORY PROTECTION: WEAR A NIOSH-APPROVED RESPIRATOR APPROPRIATE R HE DUST CONCENTRATION AT THE POINT OF USE. APPROPRIATE RESPIRATORS Y BE A FULL FACEPIECE OR A HALF MASK ATR-PURIFYING CARTRIDGE RES-RATUR WITH PARTICULATE FILTERS, A SELF-CONTAINED BREATHING APPARATUS IE PRESSURE DEMAND MODE, OR A SUPPLIED AIR RESPIRATOR.

E PROTECTION: CHEMICAL GOGGLES UNLESS A FULL FACEPIECE RESPIRATOR IS SE WORN. IT IS GENERALLY RECOGNIZED THAT CONTACT LENSES SHOULD NOT BE RE WHEN WORKING WITH CHEMICALS BECAUSE CONTACT LENSES MAY CONTRIBUTE THE SEVERITY OF AN EYE INJURY.

O ECTIVE CLOTHING: LONG-SLEEVED SHIRE, TROUSERS, AND SAFETY SHOES.

ER PROTECTIVE MEASURES: AN EYEWASH AND SAFETY SHOWER SHOULD BE ABY AND READY FOR USE.

------FIRE AND EXPLOSION INFORMATION-----

H POINT, DEG F: N/A

METHOD USED: N/A

LOWER: N/A UPPER: N/A METHOD USED: N/A TINGUISHING MEDIA: USE WATER SPRAY, DRY CHEMICAL, CO2, OR ALCOHOL

ECTAL FIRE FIGHTING PROCEDURES: FIRE FIGHTERS SHOULD WEAR SELF-AINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. USE WATER Y TO COOL NEARBY CONTAINERS AND STRUCTURES EXPOSED TO FIRE.

MUAL FIRE AND EXPLOSION HAZARDS: NONE.

HAZARDOUS REACTIVITY-----

POLYMERIZATION: WILL NOT OCCUR DITIONS TO AVOID: EXCESSIVE HEAT AND CONTAMINATION OF ANY KIND. Reple Many Exemental Zerconium

erent distant and in the fall assumed the second

the first the supplication of the supplication

NUMBER: 703 DS NO: P1113

VAN WATERS & ROGERS INC. MATERIAL SAFETY DATA SHEET

PAGE: 004

KSTON: 007 BORAX PENTAHYDRATE

REVISION OF: 12/28/89

ORDER NO: 109878 PROD NO : 225671

BOER BOOTS, RUBBER GLOVES, RUBBER APRON, AND A FULL FACEPIECE OR A LAMMASK AIR-PURIFYING CARTRIDGE RESPIRATOR WITH PARTICULATE FILTERS. AF CHEMICAL GOOGLES IF A HALF MASK IS WORN. FOR SMALL SPILLS, SWEEP AND DISPOSE OF IN DOT-APPROVED WASTE CONTAINERS. FOR LARGE SPILLS, QUEL INTO DOT-APPROVED WASTE CONTAINERS. KEEP OUT OF SEWERS, STORM ATES, SURFACE WATERS, AND SOIL. HEY WITH ALL APPLICABLE GOVERNMENTAL REGULATIONS ON SPILL REPORTING,

D HANDLING AND DISPOSAL OF WASTE. SAL METHODS: DISPOSE OF CONTAMINATED PRODUCT AND MATERIALS USED

CLEANING UP SPILLS OR LEAKS IN A MANNER APPROVED FOR THIS MATERIAL. NEWLT APPROPRIATE FEDERAL, STATE AND LOCAL REGULATORY AGENCIES TO CURTAIN PROPER BALL GOAL PROCEDURES.

TET LEMPTY CONTAINERS CAN HAVE RESIDUES, GASES AND MISTS AND ARE BLECT TO PROPER WASTE DISPOSAL, AS ABOVE.

OMGE AND HANDLING PRECAUTIONS: STORE IN A DRY, WELL-VENTILATED * AWAY FROM INCOMPATIBLE MATERIALS. KEEP CONTAINER TIGHTLY CLOSED NOT IN USE. DO NOT USE PRESSURE TO EMPTY CONTAINER. WASH OPPUGHLY AFTER HANDLING. DO NOT GET IN EYES, ON SKIN, OR ON CLOTHING.

PAIR AND MAINTENANCE PRECAUTIONS: NONE.

HER PRECAUTIONS: CONTAINERS, EVEN THOSE THAT HAVE BEEN EMPTIED, WILL THEN PRODUCT RESIDUE AND VAPORS. ALWAYS OBEY HAZARD WARNINGS AND NDLE EMPTY CONTAINERS AS IF THEY WERE FULL.

-----OTHER REGULATORY INFORMATION-----.

IM PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) CONSIDERED BY THE STATE ALIFORNIA'S SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 RUPOSITION 65) AS CAUSING CANCER OR REPRODUCTIVE TOXICITY AND FOR ICH WARNINGS ARE NOW REQUIRED:

CHEMICAL

. CAS NO.

-----REVISION-----

TELL EDRMATTING CHANGES FOR COMPUTER CONVERSION ONLY

NUMBER: 703 DS NO: P1113

G GATERS & ROGERS INC. MATERIAL SAFETY DATA SHEET

PAGE: 005

ON: 007 BURAX PENTAHYDRATE

REUTSION OF: 12/28/89

ORDER NO: 109878 PROD NO : 225671

...____FOR ADDITIONAL INFORMATION -----

RTACT: MSDS COORDINATOR VW&R SALT LAKE CTY OFFICE DURING BUSINESS HOURS, PACIFIC TIME (408)435-8700

/13/91 11:24 PRODUCT: 225671 CUST NO: 121045 ORDER NO: 107978

.....NOTTCE

VAN WATERS & ROGERS INC. ("VW&R") EXPRESSLY DISCLAIMS ALL EXPRESS OR

PEIEU WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE,

RESPECT TO THE PRODUCT OR INFORMATION PROVIDED HEREIN. **

ALL INFORMATION APPEARING HEREIN IS BASED UPON DATA OBTAINED FROM THE NUFACTURER AND/OR RECOGNIZED TECHNICAL SOURCES. WHILE THE INFORMATION IS EVED TO BE ACCURATE, VW&R MAKES NO REPRESENTATIONS AS TO ITS ACCURACY OR ICIENCY. CONDITIONS OF USE ARE BEYOND VW&RS CONTROL AND THEREFORE USERS RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS TO TRMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PARTICULAR PURPOSES AND THEY ME ALL RISKS OF THEIR USE, HANDLING, AND DISPOSAL OF THE PRODUCT, OR FROM TE PUBLICATION OR USE OF, OR RELIANCE UPON, INFORMATION CONTAINED HEREIN. TE TO ITS USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY OTHER

END OF MSDS

RECALEMBITATION

Date: 11/28/00

To: JBR Consultants

attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84093

Group #: 41748 Lab #: 00-U011407 Project: NORTH LILY

Sample Desc: Refinery Sweepings

Sample Matrix: SLUDGE-S

Date/Time Sampled: 11/10/00 , 13:00 Date/Time Received: 11/10/00 , 16:25

CERTIFICATE OF ANALYSIS

MUMINIM

REPORTING

PARAMETER	RESULT	LIMIT (MRL)	DATE ANALYZED		METHOD	Al	NALYST
INORGANIC PARAMETERS							
Mercury, as Hg TCLP, mg/L	440	0.02	11/22/00		SW 846	7470A	
TCLP Ext. Solution pH, units	4.9	0.05	11/21/00	9:00			MJB
pH, solution selection, units	6.5	0.05	11/21/00		SW 846		MJB
pH, after extraction TCLP, units	6.0	0.05	11/21/00		SW 846		MJB
Arsenic (TCLP), as As, mg/L	< 0.2	0.2	11/27/00	12:36	SW-846		LH
Barium (TCLP), as Ba, mg/L	0.4	0.1	11/27/00	12:36	SW-846	6010	LH
Cadmium (TCLP), as Cd, mg/L	14	0.01	11/27/00	12:36	SW-846	6010	LH
Chromium (TCLP), as Cr, mg/L	< 0.02	0.02	11/27/00	12:36	SW-846	6010	LH
	32	0.1	11/27/00	12:36	SW-846	6010	LH
Lead (TCLP), as Pb, mg/L	0.1	0.1	11/27/00		SW-846	6010	LH
Selenium (TCLP), as Se, mg/L Silver (TCLP), as Ag, mg/L	0.14	0.01	11/27/00		SW-846	6010	LH

NOTE: Sample not received on ice.

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page 1

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007946 Project: SILVER PEAK

Sample Desc: Heap Leach Outfall Sample Matrix: WASTE WATER Date/Time Sampled: 8/22/00, 14:00 Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

MUMINIM

REP	OR	TII	NG.	

PARAMETER	RESULT	LIMIT (MRL)	DATE ANALYZED		METHOD	ANALYST
INORGANIC PARAMETERS						
Calcium (T), as Ca, mg/L	350	0.2	8/29/00		EPA 200.7	JJT
Chromium (D), as Cr, mg/L	< 0.005	0.005	8/29/00		EPA 200.7	JJT
Copper (D), as Cu, mg/L	19	0.01	8/29/00	15:19	EPA 200.7	JJT
Magnesium (T), as Mg, mg/L	29	0.2	8/29/00	15:19	EPA 200.7	JJT
Potassium (T), as K, mg/L	310	0.2	8/29/00	15:19	EPA 200.7	JJT
Sodium (T), as Na, mg/L	5,600	20	9/ 5/00		EPA 200.7	JJT
Zinc (D), as Zn, mg/L	0.42	0.01	8/29/00	15:19	EPA 200.7	$\mathbf{J}\mathbf{J}\mathbf{T}$
Arsenic (D), as As, mg/L	0.2464	0.0005	9/ 6/00	14:16	EPA 200.8	JJT
Cadmium (D), as Cd, mg/L	0.0076	0.0005	9/ 6/00	14:16	EPA 200.8	JJT
Lead (D), as Pb, mg/L	0.1581	0.0005	9/ 6/00	14:16	EPA 200.8	JJT
Selenium (D), as Se, mg/L	0.2707	0.0005	9/ 6/00	14:16	EPA 200.8	JJT
Silver (D), as Ag, mg/L	0.3147	0.0005	9/ 6/00	14:16	200.2/200.	
Temperature, Receiving, C	18.0		8/23/00	10:15		CSM

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page 2

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007946 Project: SILVER PEAK

Sample Desc: Heap Leach Outfall Sample Matrix: WASTE WATER

Date/Time Sampled: 8/22/00, 14:00 Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

MINIMUM

REPORTING

LIMIT DATE

PARAMETER RESULT (MRL) ANALYZED METHOD ANALYST

INORGANIC PARAMETERS

NOTE: Sample received on ice.

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page 3

To: JBR Consultants

attn. Scott Page 8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007947 Project: SILVER PEAK Sample Desc: SP-1

Sample Matrix: WASTE WATER Date/Time Sampled: 8/22/00,

Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

MUMINIM

REPORTING LIMIT DATE

PARAMETER	RESULT	(MRL)	ANALYZED	METHOD	ANALYST
INORGANIC PARAMETERS					
Total Organic Halogens, mg/L Temperature, Receiving, C	< 0.05 16.0	0.05	8/28/00 8/23/00 10:15	SW846 9020	AWAL, Inc.

NOTE: Sample received on ice.

TOX analysis performed by American West Lab,

463 West 3600 South, SLC, UT 84115.

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page 4

{generic.rpt}

6100 SOUTH STRATLER SALT LAKE CITY UTAH 84107 6905 801 262 7299 PHONE 801 262 7378 FAX

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007948 Project: SILVER PEAK Sample Desc: SP-2

Sample Matrix: WASTE WATER Date/Time Sampled: 8/22/00,

Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

MINIMUM

REPORTING

PARAMETER	RESULT	LIMIT (MRL)	ANALYZED	METHOD	ANALYST
INORGANIC PARAMETERS					
Total Organic Halogens, mg/L Temperature, Receiving, C	< 0.05 17.0	0.05	8/28/00 8/23/00 10:15	SW846 9020	AWAL, Inc. CSM

NOTE: Sample received on ice.

TOX analysis performed by American West Lab,

463 West 3600 South, SLC, UT 84115.

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007949 Project: SILVER PEAK Sample Desc: SP-3

Sample Matrix: OIL/OILY WASTE Date/Time Sampled: 8/22/00,

Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

MINIMUM

REPORTING

PARAMETER	RESULT	LIMIT (MRL)	DATE ANALYZED	METHOD	ANALYST
INORGANIC PARAMETERS					
Flashpoint 1010, Degs. F	> 200	70	8/28/00 11:3	9 SW846 1010	AER
Arsenic (T), as As, mg/Kg	< 10	10	8/28/00 14:1	1 SW-846 601	O JJT
Cadmium (T), as Cd, mg/Kg	< 0.5	0.5	8/28/00 14:1	1 SW-846 601	O JJT
Chromium(T), as Cr, mg/Kg	< 0.5	0.5	8/28/00 14:1	1 SW-846 601	O JJT
Lead (T), as Pb, mg/Kg	< 7	7	8/28/00 14:1	1 SW-846 601	O JJT
Total Organic Halogens, mg/Kg	< 1	1	9/28/00	SW846 9020	B AWAL, Inc.
Temperature, Receiving, C	17.0		8/23/00 10:1	5	CSM

NOTE: Sample received on ice.

TOX analysis performed by American West Lab,

463 West 3600 South, SLC, UT 84115.

Approved By:

David Gayer, Laberatory Director

MRL = Report detection limit

Page 6

To: JBR Consultants

attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007950 Project: SILVER PEAK Sample Desc: SP-4

Sample Matrix: OIL/OILY WASTE Date/Time Sampled: 8/22/00,

Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

RESULT

MINIMUM

REPORTING

LIMIT DATE (MRL) ANALYZED

ANALYST

METHOD

INORGANIC PARAMETERS

PARAMETER

Total Organic Halogens, mg/Kg < 1 1 8/28/00 SW846 9020B AWAL, Inc.
Temperature, Receiving, C 18.0 8/23/00 10:15 CSM

NOTE: Sample received on ice.

TOX analysis performed by American West Lab,

463 West 3600 South, SLC, UT 84115.

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page '

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007951 Project: SILVER PEAK Sample Desc: SP-5

Sample Matrix: WASTE WATER Date/Time Sampled: 8/22/00,

Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

MINIMUM REPORTING

	V1.1			
I.	IMI	T	DATE	

PARAMETER	RESULT	(MRL)	ANALYZED	METHOD	ANALYST
INORGANIC PARAMETERS					
TCLP Ext. Solution pH, units	4.93	0.05	8/25/00 10:00		MJB
pH, solution selection, units	6.00	0.05	8/25/00 10:00	SW 846	9045 MJB
pH, after extraction TCLP, units	4.50	0.05	8/25/00 10:00	SW 846	9045 MJB
Arsenic (T), as As, mg/L	< 10	10	8/28/00 14:11	SW-846	6010 JJT
Arsenic (TCLP), as As, mg/L	< 0.2	0.2	8/29/00 10:51	SW-846	6010 JJT
Barium (TCLP), as Ba, mg/L	0.2	0.1	8/29/00 10:51	SW-846	
Cadmium (T), as Cd, mg/L	< 0.5	0.5	8/28/00 14:11	SW-846	
Cadmium (TCLP), as Cd, mg/L	< 0.01	0.01	8/29/00 10:51	SW-846	
Chromium(T), as Cr, mg/L	0.8	0.5	8/28/00 14:11	SW-846	
Chromium (TCLP), as Cr, mg/L	< 0.02	0.02	8/29/00 10:51	SW-846	
Lead (T), as Pb, mg/L	. 9	7	8/28/00 14:11	SW-846	
Lead (TCLP), as Pb, mg/L	< 0.1	0.1	8/29/00 10:51	SW-846	
Mercury (TCLP), as Hg, mg/L	< 0.0002	0.0002	8/28/00 12:40		7470A MJB
Selenium (TCLP), as Se, mg/L	< 0.1	0.1	8/29/00 10:51	SW-846	•
Silver (TCLP), as Ag, mg/L	< 0.01	0.01	8/29/00 10:51	SW-846	6010 JJT

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page 8

<u>ANALYTICAL LABORATORIES</u>

Date: 9/22/00

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007951 Project: SILVER PEAK Sample Desc: SP-5

Sample Matrix: WASTE WATER Date/Time Sampled: 8/22/00,

Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

MINIMUM

REPORTING

PARAMETER RESULT (MRL) ANALYZED METHOD ANALYST

INORGANIC PARAMETERS

Total Organic Halogens, mg/Kg < 1 1 8/28/00 SW846 9020B AWAL, Inc.
Temperature, Receiving, C 19.0 8/23/00 10:15 CSM

NOTE: Sample received on ice.

TOX analysis performed by American West Lab,

463 West 3600 South, SLC, UT 84115.

Flashpoint not completed due to limited sample

volume.

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page 5

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007951 Project: SILVER PEAK Sample Desc: SP-5

Sample Matrix: WASTE WATER Date/Time Sampled: 8/22/00,

Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

RECEIVING TEMPERATURE: 19.0 C

PARAMETER	RESULT	LIMIT (MRL)	METHOD
Volatiles			
Analyst: MSS Date Analyzed: 9/5/0	00 Time: 12:58		
Benzene, ug/L	< 2	2	SW846-8260A
Bromobenzene, ug/L	< 5	5	SW846-8260A
Bromochloromethane, ug/L	< 5	5	SW846-8260A
Bromodichloromethane, ug/L	< 5	5	SW846-8260A
Bromoform, ug/L	< 5	5	SW846-8260A
Bromomethane, ug/L	< 20	20	SW846-8260A
n-Butylbenzene, ug/L	< 10	10	SW846-8260A
sec-Butylbenzene, ug/L	< 10	10	SW846-8260A
tert-Butylbenzene, ug/L	< 10	10	SW846-8260A
Carbon Tetrachloride, ug/L	< 6	6	SW846-8260A
Chlorobenzene, ug/L	< 2	2	SW846-8260A
Chloroethane, ug/L	< 10	10	SW846-8260A

Approved By:

David Gayer, Laboratory Director

< 6

< 20

6

20

MINIMUM REPORTING

MRL = Report detection limit

Chloromethane, ug/L

Chloroform, ug/L

Page 10

{generic.rpt}

SW846-8260A

SW846-8260A

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007951 Project: SILVER PEAK Sample Desc: SP-5

Sample Matrix: WASTE WATER Date/Time Sampled: 8/22/00,

Date/Time Received: 8/23/00 , 10:15

CERTIFICATE OF ANALYSIS

RECEIVING TEMPERATURE: 19.0 C

		LIMIT	
전 <u>하는 것으로</u> 그리고 있다. 보고 있는 그리고 있는 것이다. 그 모든 것이다. 그리고 있다.	RESULT	(MRL)	METHOD
PARAMETER	< 10	10	SW846-8260A
2-Chlorotoluene, ug/L	< 10	10	SW846-8260A
4-Chlorotoluene, ug/L	< 100	100	SW846-8260A
1,2-Dibromo-3-chloropropane, ug/L	< 5	5	SW846-8260A
Dibromochloromethane, ug/L	< 5	5	SW846-8260A
1,2-Dibromoethane, ug/L	< 5	5	SW846-8260A
Dibromomethane, ug/L	< 10	10	SW846-8260A
o-Dichlorobenzene, ug/L	< 10	10	SW846-8260A
1,3-Dichlorobenzene, ug/L	< 10	10	SW846-8260A
p-Dichlorobenzene, ug/L	< 50	50	SW846-8260A
Dichlorodifluoromethane, ug/L	< 5	5	SW846-8260A
1,1-Dichloroethane, ug/L	< 6	6	SW846-8260A
1,2-Dichloroethane, ug/L	< 6	6	SW846-8260A
1,1-Dichloroethylene, ug/L	< 5	5	SW846-8260A
cis-1,2-Dichloroethene, ug/L	< 5	5	SW846-8260A
trans-1,2-Dichloroethene, ug/L 1,2-Dichloropropane, ug/L	< 5	5	SW846-8260A

Approved By:

David Gayer, Laboratory Director

MINIMUM REPORTING

MRL = Report detection limit

Page 11

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007951 Project: SILVER PEAK Sample Desc: SP-5

Sample Matrix: WASTE WATER Date/Time Sampled: 8/22/00,

Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

RECEIVING TEMPERATURE: 19.0 C

MINIMUM REPORTING LIMIT

PARAMETER	RESULT	(MRL)	METHOD	
1,3-Dichloropropane, ug/L	< 5	5	SW846-8260A	
2,2-Dichloropropane, ug/L	< 10	10	SW846-8260A	
- · · · · · · · · · · · · · · · · · · ·	< 5	5	SW846-8260A	
1,1-Dichloropropene, ug/L	< 5	5	SW846-8260A	
cis-1,3-Dichloropropene, ug/L	< 5	-5	SW846-8260A	
trans-1,3-Dichloropropene, ug/L	< 6	6	SW846-8260A	
Ethylbenzene, ug/L	· -	10	SW846-8260A	
Hexachlorobutadiene, ug/L	< 10			
Isopropylbenzene, ug/L	< 10	10	SW846-8260A	
4-Isopropyltoluene, ug/L	< 10	10	SW846-8260A	
Methyl Isobutyl Ketone, ug/L	< 60	60	SW846-8260A	
Methylene Chloride, ug/L	< 10	10	SW846-8260A	
Naphthalene, ug/L	18.4	10	SW846-8260A	
n-propylbenzene, ug/L	< 10	10	SW846-8260A	
	< 5	5	SW846-8260A	
Styrene, ug/L	< 5	5	SW846-8260A	
1,1,1,2-Tetrachloroethane, ug/L	< 5	5	SW846-8260A	
1,1,2,2-Tetrachloroethane, ug/L	\ 3	_		

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page 12

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007951 Project: SILVER PEAK Sample Desc: SP-5

Sample Matrix: WASTE WATER Date/Time Sampled: 8/22/00,

Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

RECEIVING TEMPERATURE:

19.0 C

		LIMIT	
PARAMETER	RESULT	(MRL)	METHOD
Tetrachloroethylene, ug/L	< 6	6	SW846-8260A
Toluene, ug/L	< 10	10	SW846-8260A
1,2,3-Trichlorobenzene, ug/L	< 10	10	SW846-8260A
1,2,4-Trichlorobenzene, ug/L	< 10	10	SW846-8260A
1,1,1-Trichloroethane, ug/L	< 6	6	SW846-8260A
1,1,2-Trichloroethane, ug/L	< 6	6	SW846-8260A
Trichloroethylene, ug/L	< 6	6	SW846-8260A
Trichlorofluoromethane, ug/L	< 10	10	SW846-8260A
1,2,3-Trichloropropane, ug/L	< 10	10	SW846-8260A
	< 10	10	SW846-8260A
1,2,4-Trimethylbenzene, ug/L	< 10	10	SW846-8260A
1,3,5-Trimethylbenzene, ug/L	< 6	6	SW846-8260A
Vinyl Chloride, ug/L Xylenes, ug/L	< 6	6	SW846-8260A

Approved By:

David Gayer, Laboratory Director

MINIMUM REPORTING

MRL = Report detection limit

Page 13

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007951 Project: SILVER PEAK Sample Desc: SP-5

Sample Matrix: WASTE WATER Date/Time Sampled: 8/22/00,

Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

RECEIVING TEMPERATURE: 19.0 C

MINIMUM REPORTING

LIMIT

PARAMETER RESULT (MRL) METHOD

NOTE: Sample received on ice.

TOX analysis performed by American West Lab,

463 West 3600 South, SLC, UT 84115.

Flashpoint not completed due to limited sample

volume.

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page 14

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007952 Project: SILVER PEAK Sample Desc: SP-6

Sample Matrix: OIL/OILY WASTE Date/Time Sampled: 8/22/00,

Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

MINIMUM

KEP	OKTING	

PARAMETER	RESULT	LIMIT	DATE ANALYZED		METHOD	AN	MALYST	
PARAMEIER	MBODI	(223,422)	ANRUIDED					
INORGANIC PARAMETERS								
Mercury, as Hg Total, mg/Kg	< 0.05	0.05	8/30/00	15:40	SW 846	7471A	MJB	
pH, Solids/Sludges Paste, units	6.50	0.05	8/28/00	17:00	SW 846	9045	TSM	
Arsenic (T), as As, mg/Kg	< 10	10	8/28/00	14:11	SW-846	6010	JJT	
Barium (T), as Ba, mg/Kg	3.6	0.5	8/28/00	14:11	SW-846	6010	JJT	
Cadmium (T), as Cd, mg/Kg	< 0.5	0.5	8/28/00	14:11	SW-846	6010	JJT	
Chromium(T), as Cr, mg/Kg	< 0.5	0.5	8/28/00	14:11	SW-846	6010	JJT	
Lead (T), as Pb, mg/Kg	160	7	8/28/00	14:11	SW-846	6010	JJT	
Selenium (T), as Se, mg/Kg	< 10	10	8/28/00	14:11	SW-846	6010	JJT	
Silver (T), as Ag, mg/Kg	< 0.5	0.5	8/28/00	14:11	SW-846	6010	JJT	
Total Organic Halogens, mg/Kg	< 1	1	8/28/00		SW846 9	9020B	AWAL, I	nc.
Temperature, Receiving, C	18.0		8/23/00	10:15			CSM	

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page 15

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007952 Project: SILVER PEAK Sample Desc: SP-6

Sample Matrix: OIL/OILY WASTE Date/Time Sampled: 8/22/00,

Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

MINIMUM

REPORTING

LIMIT DATE

PARAMETER RESULT (MRL) ANALYZED METHOD ANALYST

INORGANIC PARAMETERS

NOTE: Sample received on ice.

TOX analysis performed by American West Lab,

463 West 3600 South, SLC, UT 84115.

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page 16

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007953 Project: SILVER PEAK Sample Desc: SP-7

Muriatic Acid.

Sample Matrix: SOLVENT

Date/Time Sampled: 8/22/00, Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

MINIMUM REPORTING

PARAMETER	RESULT	LIMIT (MRL)	DATE ANALYZED		METHOD	A	NALYST
INORGANIC PARAMETERS							
Mercury, as Hg Total, mg/Kg	< 0.05	0.05	8/30/00	15:40	SW 846	7471A	MJB
pH,	0.0	0.1	8/23/00	10:30	SW 846	9045	LPS
Arsenic (T), as As, mg/Kg	< 10	10	8/28/00	14:11	SW-846	6010	JJT
Barium (T), as Ba, mg/Kg	33	0.5	8/28/00	14:11	SW-846	6010	JJT
Cadmium (T), as Cd, mg/Kg	< 0.5	0.5	8/28/00	14:11	SW-846	6010	JJT
Chromium(T), as Cr, mg/Kg	0.6	0.5	8/28/00	14:11	SW-846	6010	JJT
Lead (T), as Pb, mg/Kg	< 7	7	8/28/00	14:11	SW-846	6010	JJT
Selenium (T), as Se, mg/Kg	< 10	10	8/28/00	14:11	SW-846	6010	JJT
Silver (T), as Ag, mg/Kg	< 0.5	0.5	8/28/00	14:11	SW-846	6010	JJT
Temperature, Receiving, C	18.0		8/23/00	10:15			CSM

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

17 Page

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007953 Project: SILVER PEAK Sample Desc: SP-7

Muriatic Acid.

Sample Matrix: SOLVENT

Date/Time Sampled: 8/22/00, Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

MUMINIM REPORTING

LIMIT DATE

(MRL) ANALYZED RESULT PARAMETER

METHOD

ANALYST

INORGANIC PARAMETERS

NOTE: Sample received on ice.

Reported pH is an approxiamte value.

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

18 Page

To: JBR Consultants attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007954 Project: SILVER PEAK Sample Desc: SP-8

Sample Matrix: OIL/OILY WASTE Date/Time Sampled: 8/22/00,

Date/Time Received: 8/23/00, 10:15

CERTIFICATE OF ANALYSIS

RESULT

MINIMUM

REPORTING

LIMIT DATE
(MRL) ANALYZED

METHOD ANALYST

INORGANIC PARAMETERS

PARAMETER

Total Organic Halogens, mg/Kg < 1 1 8/28/00 SW846 9020B AWAL, Inc. Temperature, Receiving, C 19.0 8/23/00 10:15 CSM

NOTE: Sample received on ice.

Sample not run for pH due to matrix.

TOX analysis performed by American West Lab,

463 West 3600 South, SLC, UT 84115.

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page 19



AMERICAN WEST

LABORATORIES

West 3600 South Salt Lake City, Utah 84115

(801) 263-8686 folleree (888) 263-8686 Fax (801) 263-8687 JBR Consultants Group

Project: N. Lilly-01

Lab Set ID: L46046

23-May-01

All analysis performed in accordance to NELAC protocols. Any questions regarding the results please feel free to call one of the following at (801) 263-8686 or (888) 263-8686:

Paul Ellingson Laboratory Manager

Mark Broadhead Inorganic & Metals Supervisor

Greg Hess Organic Supervisor

Pat Noteboom Project Coordinator

Peggy McNicol QA Officer



AMERICAN WEST ANALYTICAL



ABORATORIES

West 3600 South Salt Lake City, Utah 84115

(801) 263-8686 ree (888) 263-8686 Fax (801) 263-8687

INORGANIC ANALYSIS REPORT

Client: JBR Consultants Group

Date Sampled: May 18, 2001

Project: N. Lilly-01

L46046-01B

Lab Sample ID:

Contact: Bill Fuller

Date Received: May 18, 2001

Field Sample ID:

NL-S-01

Analytical Results	Units	Date Analyzed	Method Used	-	oorting Limit	Amount Detected	
pH	pH units	5/22/01	9045C	0	1	3.20	

Released by:

Laboratory Supervisor

Report Date:

May 23, 2001

Page 1 of 1



AMERICAN WEST ANALYTICAL LABORATORIES

West 3600 South Salt Lake City, Utah 84115

(801) 263-8686 Folloree (888) 263-8686 Fax (801) 263-8687

INORGANIC ANALYSIS REPORT

Client: JBR Consultants Group

Date Sampled: May 18, 2001

Project: N. Lilly-01

Lab Sample ID:

L46046-01A

Contact: Bill Fuller

Date Received: May 18, 2001

Field Sample ID:

NL-S-01

TCLP METALS Me	thod 1311	Date	Method	Reporting		
Analytical Results	Units	Analyzed	Used	Limit	Detected	
Arsenic	mg/L	5/21/01	6010B	2.0	2.6	
Barium	mg/L	5/21/01	6010B	0.050	< 0.050	
Cadmium	mg/L	5/21/01	6010B	0.030	< 0.030	
Chromium	mg/L	5/21/01	6010B	0.050	< 0.050	
Lead	mg/L	5/21/01	6010B	0.10	< 0.10	
Mercury	mg/L	5/21/01	7470A	0.050	< 0.050	
Selenium	mg/L	5/21/01	6010B	0.50	1.0	
Silver	mg/L	5/21/01	6010B	0.10	< 0.10	

Released by:

Laboratory Supervisor

Report Date:

May 23, 2001

Page 1 of 1

Page

American West Analytical Labs

>
ımar
Im
Sa
ER
3
0 3
SE
×


JBR400 Client ID:

N. Lilly-01 Project:

OCLEVEL: 1-10 K

21-May-01 Work Order L46046

Comments:	Comments: Rush Level 2		-	<u>.</u>				1
Sample ID	Client Sample ID	Collection Date	Date Received	Date Due	Matrix	Test Code	Storage	. 1
L46046-01A	NL-S-01	5/18/01	5/18/01	5/23/01	Solids	1311LM	tclp/rush	i .
				5/23/01		3015	tclp/rush	•
				5/23/01		Hg-prep-W	tclp/rush	
				5/23/01		M-9H	tclp/rush	
				5/23/01		ICP-W	tclp/rush	
L46046-01B		-		5/23/01		PH-S	TCLPFridge	
				5/23/01		Soil_Prep	TCLPFridge	



Appendix D

Draft Amended Ground Water Discharge Permit, No UGW230001



Michael O. Leavitt Governor

Dianne R. Nielson, Ph.D. **Executive Director**

Don A. Ostler, P.E.

DEPARTMENT OF ENVIRONMENTAL QUALITY **DIVISION OF WATER QUALITY**

NUNIA LILI MIND

288 North 1460 West P.O. Box 144870 Salt Lake City, Utah 84114-4870 (801) 538-6146 (801) 538-6016 Fax (801) 536-4414 T.D.D. www.deg.state.ut.us Web

August 23, 2001

Water Quality Board K.C. Shaw, P.E. Chairman

William R. Williams Robert G. Adams Nan Bunker Ray M. Child, C.P.A.

John R. Cushing, Mayor Neil K. Kochenour, M.D. Dianne R. Nielson, Ph.D. Ronald C. Sims, Ph.D. Douglas E. Thompson, Mayor

> J. Ann Wechsler Don A. Ostler, P.E.

Mr. Stephen Flechner, President North Lily Mining Company Silver City Heap Leach 1800 Glenarm Place, Suite 210 Denver, Colorado 80202

Dear Mr. Flechner:

Subject:

Draft Amended Ground Water Discharge Permit, No. UGW230001

Enclosed is the proposed draft amended Ground Water Discharge Permit and Statement of Basis for Permit No. UGW230001.

The permit is modified mainly to incorporate post-closure monitoring requirements. This draft permit is for your review and comment. If possible please respond within 30 days. Upon an indication of your concurrence with this draft, a final draft version of the permit will be public noticed by the Executive Secretary prior to issuance.

If you have any questions, please contact Beth Wondimu at (801) 538-6084.

Sincerely,

Dennis Frederick, P.E., Manager

Ground Water Protection Section

DAF:BW:bjr

Enclosures

U:\WQ\PERMITS\BWONDIMU\wp\NOLILY\PERMIT\NLCOV.wpD

00/01/01 14:15 PAA 000 600 660

STATEMENT OF BASIS

DRAFT

North Lily: Silver City Heap Leach Closure Permit Modification, No. UGW230001

August 18, 2001

Introduction

North Lily was issued a groundwater discharge permit on December 8, 1997 to cover the operation of heap leach facility closure. Due to the completion of closure of the heap leach facility, the permit is modified to incorporate new technology performance standards and requirements for post-closure monitoring.

Description of Facility

The Silver City Heap Leach facility consists of 15 acres of spent ore stacked to an average depth of 100 feet. Recovery of precious metals from the ore was terminated in October, 1995. North Lily has rinsed the ore by exposure to precipitation and by recycling drain down solutions to the heap leach. Significant reductions in initial contaminant concentrations of cyanide and other metals have been achieved.

Subsequent to the termination of operation, the facility underwent closure according to the provision of DOGM reclamation plan. The heap leach was reclaimed in December, 2000. The pad cover consists of graded and compacted subore that was ripped to a nominal depth. The top soil was seeded in accordance with Division of Oil, Gas and Mining (DOGM) reclamation requirements to establish vegetation.

Post Closure Fluid Management System

Drain-down fluid from the reclaimed heap leach is disposed of utilizing an absorption drainfield system. The absorption drainfield is installed west of the heap leach pad. The system is designed to transfer fluid from heap leach pad into a distribution box, that is located at the pad margin, and then to the absorption field. Construction standards for drainfield is covered under the construction permit issued on by the Executive Secretary April 5, 2001.

The technology performance standard to be achieved in this post operational permit is the operation and maintenance of the absorption drainfield as set forth in the approved construction permit. In addition, post closure fluid management for purposes of the permit is defined as: 1) Flow rate for heap leach draindown fluid will not exceed the design limit of 6.41 gallons per minute;

2) Concentrations of constituents of the drainown fluid must be *de minimis* for potential impact to the ground water quality in the vicinity.

Post-Closure Monitoring

The heap leach draindown fluid will be monitored for constituents listed in the permit during postclosure operation. Samples will be taken from the draindown fluid sampling port on a quarterly basis.

Flow measurement will also be conducted as part of post closure monitoring. Manual measurement of flow rate will be conducted on a weekly basis for both instantaneous and cumulative flow.

 $f: \verb|\wq\permits| dfrederi \verb|\wp\nli| y \verb|\nli| y. sob$

UU/UI/UI 14.10 PAA UUU 480 440

Permit No.: UGW230001

DRAFT

STATE OF UTAH DIVISION OF WATER QUALITY DEPARTMENT OF ENVIRONMENTAL QUALITY P.O. BOX 144870 SALT LAKE CITY, UTAH 84114-4870

Ground Water Quality Discharge Permit

In compliance with the provisions of the Utah Water Pollution Control Act, Title 19, Chapter 5, Utah Code Annotated 1953, as amended,

North Lily Mining Company Silver City Heap Leach 1800 Glenarm Place, Suite 210 Denver, Colorado 80202

is granted an amended Ground Water Quality Discharge Permit for the Silver City Heap Leach located on a tract of land in Tintic Valley with the NE1/4; Section 35, Township 10 South Range 3 West, Salt Lake Base and Meridian, Juab Co., Utah in accordance with conditions set forth herein.

This Ground Water Quality Discharge Permit supersedes all other Ground Water Discharge permits for this facility issued previously.

This modified permit shall become effective on	
This permit and the authorization to operate shall expire at midnight,	

Executive Secretary
Utah Water Quality Board

TABLE OF CONTENTS

I.	SPEC	CIFIC CONDITIONS	Page 1 of	13
	A.	Ground Water Classification	Page 1 of	13
	В.	Post Operation Discharge Minimization Technology	Page 1 of	13
	C.	Post-Closure Compliance Monitoring Requirements	Page 1 of	13
	D.	Non-Compliance Status	Page 3 of	13
	E.	Reporting Requirements	Page 3 of	13
	F.	Compliance Schedule	Page 4 of	13
		Construction Plans and Specifications	Page 4 of	13
П.	MON	ITORING, RECORDING AND REPORTING REQUIREMENTS	Page 5 of	13
	A.	Representative Sampling	Page 5 of	13
	В.	Analytical Procedures	Page 5 of	13
	C.	Penalties for Tampering	Page 5 of	13
	D.	Reporting of Monitoring Results	Page 5 of	13
	E.	Compliance Schedules	Page 5 of	13
	F.	Additional Monitoring by the Permittee	Page 5 of	13
	G.	Records Contents	Page 5 of	13
	H.	Retention of Records	Page 5 of	13
	I.	Twenty-four Hour Notice of Noncompliance Reporting	Page 6 of	13
•	J.	Other Noncompliance Reporting	Page 6 of	13
`	K.	Inspection and Entry	Page 6 of	13
m.	COM	IPLIANCE RESPONSIBILITIES	Page 8 of	13
	Α.	Duty to Comply	Page 8 of	13
	В.	Penalties for Violations of Permit Conditions		
	C.	Need to Halt or Reduce Activity not a Defense	Page 8 of	13
	D.	Duty to Mitigate	Page 8 of	13
	E.	Proper Operation and Maintenance	Page 8 of	13
	F.	Bypass of Treatment Facilities	Page 8 of	13
	G.	Affirmative Defense	Page 9 of	13
IV.	GEN	ERAL REQUIREMENTS	Page 11 of	13
	Α.	Planned Changes	Page 11 of	13
	B.	Anticipated Noncompliance	Page 11 of	13
•	C.	Spill Reporting	Page 11 of	13
	D.	Permit Actions	Page 11 of	13
	E.	Duty to Reapply	Page 11 of	13
	F.	Duty to Provide Information	Page 11 of	13
	G.	Other Information	Page 11 of	13
	H.	Signatory Requirements	Page 11 of	13
	Ī.	Penalties for Falsification of Reports	Page 12 of	13
	J.	Availability of Reports	Page 12 of	13

K.	Property Rights	Page 13 of 13
L.	Severability	
M.	Transfers	Page 13 of 13
	State Laws	
	Reopener Provisions	_

I. SPECIFIC CONDITIONS

A. Ground Water Classification

Based on ground water data collected from a downgradient water supply well, ground water in the area of the facility is classified as Class IA Drinking Water Quality Ground Water.

B. Post Operation Discharge Minimization Technology

1. Heap Leach Pad Cover

The heap leach was reclaimed in December, 2000. The pad cover consist of graded and compacted subore that was ripped to a nominal depth. The top soil was seeded in accordance with Division of Oil, Gas and Mining (DOGM) reclamation requirements to establish vegetation. At a minimum, vegetative earthen cover must be established to a density consistent with DOGM requirements.

2. Post-Closure Fluid Management System

Drain-down fluid from the reclaimed heap leach is disposed of utilizing an absorption drainfield system. The absorption drainfield is installed at west of the heap leach pad. The system is designed to transfer fluid from heap leach pad to the absorption field. Construction standards for the absorption drainfield is covered under the construction permit issued by Executive Secretary on April 5, 2001.

3. Performance Standards

- a. The absorption drainfield shall be maintained in operable condition such that effective leachate flow through and treatment is provided at all times;
- b. Flow rate for heap leach draindown fluid shall not exceed the design limit, 6.41 gallons per minute.
- c. Concentrations of constituents of the draindown fluid must be *de minimis* for potential impact to the ground water quality in the vicinity.

C. <u>Post-Closure Compliance Monitoring Requirements</u>

1. Heap Leach Draindown Fluid Monitoring



a) Monitoring Frequency - Compliance monitoring of the heap leach draindown fluid shall be conducted by the permittee quarterly. Monitoring will be reported to the Executive Secretary as per the requirements stipulated in Part I.E.1.

- b) Analysis by Certified Laboratories draindown fluid samples shall be submitted to a laboratory certified by the State Health Laboratory for analysis.
- c) Analytical Methods methods used to analyze samples must be methods cited in UAC R317-6-6.3A(13)
- d) Analysis Parameters the following analyses will be conducted on all water samples collected:
 - 1) Field Parameters pH, temperature, and specific conductance
 - 2) Laboratory Parameters -
 - Major Anions and Cations: including chloride, sulfate, carbonate, bicarbonate, sodium, potassium, magnesium and calcium.
 - Dissolved Metals: including arsenic, barium, cadmium, chromium, copper, lead, mercury, selenium, silver and zinc.
 - Fluoride, nitrite and nitrate.
 - Weak Acid Dissociable Cyanide.
 - Cyanide Amenable to Chlorination.
- h) Sampling Port samples of draindown fluid shall be taken at the distribution box that is located at the heap leach pad margin.
- 2. Heap Leach Draindown Fluid Flow Measurement
 - a) Monitoring Frequency Manual measurement of flow rate for draindown fluid shall be conducted on a weekly basis, for both instantaneous and cumulative flow. The data will be reported on a quarterly basis in accordance with the schedule of Table 1, Part I.E.1.
 - b) Sampling Port The flow measurement shall be taken manually at the distribution box that is located at the heap leach pad margin.

D. <u>Non-Compliance Status</u>

In the event the permittee fails to maintain the Heap Leach Pad Cover and the absorption field in compliance with any of the requirements of Part I.B.3 of this permit, the permittee shall be in violation of this permit unless the affirmative defense provisions of Part III.G are satisfied. The permittee shall submit to the Executive Secretary a notification and description of the failure in accordance with Part II I.1 and 2.

E. Reporting Requirements

a) Post closure monitoring schedule - The sampling and analysis required in Part I.C, above, shall be reported according to Table 1, below.

Table 1 - Compliance Monitoring Reporting Schedule

Quart	<u>ter</u>	Report Due On
1st	(Jan., Feb., March)	April 15
2nd	(April, May, June)	July 15
3rd	(July, Aug., Sept.)	October 15
_4th	(Oct., Nov., Dec.)	January 15

- b) Sampling and Analysis Report will include:
 - 1) Field Data Sheets or copies thereof, including the field measurements, required in Part I C 1(c)(1), above, and other pertinent field data, such as: sample location, date and time, names of sampling crew, type of sampling pump or bail, measured casing volume, volume of water purged before sampling.
 - 2) Results of Sample Analysis including date sampled, date received, ion balance; and the results of analysis for each parameter, including: value or concentration, units of measurement, reporting limit (minimum detection limit for the examination), analytical method, and the date of the analysis.
 - Electronic Filing Requirements In addition to submittal of the hard copy data, above, the permittee will be required to electronically submit the required ground water monitoring data in an electronic format approved by the Executive Secretary. The data may be sent by e-mail, floppy disc, modem or other approved transmittal mechanism.

F. <u>Compliance Schedule</u>



Construction Plans and Specifications - Within 30 days of issuance of this permit, the permittee shall submit As-Built plans and specifications for the recently constructed absorption draindown field.

II. MONITORING, RECORDING AND REPORTING REQUIREMENTS

- A. <u>Representative Sampling.</u> Samples taken in compliance with the monitoring requirements established under Part I shall be representative of the monitored activity.
- B. <u>Analytical Procedures.</u> Water sample analysis must be conducted according to test procedures specified under UACR317-6.3.A.13, unless other test procedures have been specified in this permit.
- C. <u>Penalties for Tampering.</u> The Act provides that any person who falsifies, tampers with, or knowingly renders inaccurate, any monitoring device or method required to be maintained under this permit shall, upon conviction, be punished by a fine of not more than \$10,000 per violation, or by imprisonment for not more than six months per violation, or by both.
- D. Reporting of Monitoring Results. Monitoring results obtained during each reporting period specified in the permit, shall be submitted to the Executive Secretary, Utah Division of Water Quality at the following address no later than the 15th day of the month following the completed reporting period:

State of Utah
Division of Water Quality
Department of Environmental Quality
P. O. Box 144870
Salt Lake City, Utah 84114-4870
Attention: Ground Water Protection Section

- E. <u>Compliance Schedules</u>. Reports of compliance or noncompliance with, or any progress reports on interim and final requirements contained in any Compliance Schedule of this permit shall be submitted no later than 14 days following each schedule date.
- F. Additional Monitoring by the Permittee. If the permittee monitors any pollutant more frequently than required by this permit, using approved test procedures as specified in this permit, the results of this monitoring shall be included in the calculation and reporting of the data submitted. Such increased frequency shall also be indicated.
- G. Records Contents. Records of monitoring information shall include:
 - 1. The date, exact place, and time of sampling or measurements:
 - 2. The individual(s) who performed the sampling or measurements;
 - 3. The date(s) and time(s) analyses were performed;
 - 4. The individual(s) who performed the analyses;
 - 5. The analytical techniques or methods used; and,
 - 6. The results of such analyses.
- H. Retention of Records. The permittee shall retain records of all monitoring information, including all calibration and maintenance records and copies of all reports required by this permit, and records of all data used to complete the application for this permit, for a period of at least three years from

the date of the sample, measurement, report or application. This period may be extended by request of the Executive Secretary at any time.

- I. Twenty-four Hour Notice of Noncompliance Reporting.
 - 1. The permittee shall verbally report any noncompliance with permit conditions or limits as soon as possible, but no later than twenty-four (24) hours from the time the permittee first became aware of the circumstances. The report shall be made to the Utah Department of Environmental Quality 24 hour number, (801) 538-6333, or to the Division of Water Quality, Ground Water Protection Section at (801) 538-6146, during normal business hours (8:00 am 5:00 pm Mountain Time).
 - 2. A written submission of any noncompliance with permit conditions or limits shall be provided to the Executive Secretary within five days of the time that the permittee becomes aware of the circumstances. The written submission shall contain:
 - a. A description of the noncompliance and its cause;
 - b. The period of noncompliance, including exact dates and times;
 - c. The estimated time noncompliance is expected to continue if it has not been corrected; and,
 - d. Steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance.
 - e. If necessary a proposed schedule for implementation of the Contingency Plan in accordance with Part I.D.2.
 - 3. Written reports shall be submitted to the addresses in Part II D, Reporting of Monitoring Results.
- J. Other Noncompliance Reporting. Instances of noncompliance not required to be reported within 24 hours, shall be reported at the time that monitoring reports for Part II D are submitted.
- K. <u>Inspection and Entry</u>. The permittee shall allow the Executive Secretary, or an authorized representative, upon the presentation of credentials and other documents as may be required by law, to:
 - 1. Enter upon the permittee's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of the permit;
 - 2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;

- 3. Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit; and,
- 4. Sample or monitor at reasonable times, for the purpose of assuring permit compliance or as otherwise authorized by the Act, any substances or parameters at any location.

III. COMPLIANCE RESPONSIBILITIES

- A. <u>Duty to Comply</u>. The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application. The permittee shall give advance notice to the Executive Secretary of the Utah Water Quality Board of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.
- B. Penalties for Violations of Permit Conditions. The Act provides that any person who violates a permit condition implementing provisions of the Act is subject to a civil penalty not to exceed \$10,000 per day of such violation. Any person who willfully or negligently violates permit conditions is subject to a fine not exceeding \$25,000 per day of violation. Any person convicted under Section 19-5-115(2) of the Act a second time shall be punished by a fine not exceeding \$50,000 per day. Nothing in this permit shall be construed to relieve the permittee of the civil or criminal penalties for noncompliance.
- C. Need to Halt or Reduce Activity not a Defense. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.
- D. <u>Duty to Mitigate</u>. The permittee shall take all reasonable steps to minimize or prevent any discharge in violation of this permit which has a reasonable likelihood of adversely affecting human health or the environment.
- E. <u>Proper Operation and Maintenance</u>. The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance also includes adequate laboratory controls and quality assurance procedures. This provision requires the operation of back-up or auxiliary facilities or similar systems which are installed by a permittee only when the operation is necessary to achieve compliance with the conditions of the permit.

F. Bypass of Treatment Facilities

1. Definitions:

- a. "Bypass" means the intentional diversion of heap leach solutions from any portion of the treatment system or untreated flow through the system during a partial system failure.
- b. "Severe property damage" means substantial physical damage to property, damage to treatment facilities which may cause them to become inoperable, or substantial and permanent loss of natural resources which can reasonably be expected to occur in the absence of a bypass. Severe property damage does not mean economic loss caused

by delays in production.

2. Anticipated Bypass - If the permittee knows in advance of the need for a bypass, it shall submit prior notice, at least five (5) days before the date of the bypass. The notice shall include the reason(s) for the anticipated bypass, the expected length of time treatment systems will be bypassed, and a description of the measures taken to mitigate the quantities released during the bypass. Operational records shall be submitted following the anticipated bypass detailing the quantities of materials released and the levels of relevant chemical constituents in the materials released. The permittee shall limit the time period of the bypass to the minimum amount of time necessary to affect system maintenance or repairs.

The Executive Secretary may approve an anticipated bypass, after considering any potential effects, if the Executive Secretary determines that it will meet the three conditions listed in paragraph 5 below of this section.

- 3. Unanticipated Bypass The permittee shall submit notice of an unanticipated bypass as required in Part I.D.1. The permittee shall limit the time period of the bypass to the minimum amount of time necessary to affect system maintenance or repairs.
- 4. Prohibition of Bypass Bypass is prohibited and the Executive Secretary may take enforcement action against a permittee for a bypass, unless:
 - a) The bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;
 - b) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgement to prevent a bypass which occurred during normal periods of equipment downtime or preventive maintenance; and,
 - c) The permittee submitted notices as required under Part III F.3, above.

G. Affirmative Defense

In the event that a compliance action is initiated against the permittee for violation of permit conditions relating to discharge minimization technology, the permittee may affirmatively defend against that action by demonstrating the following:

- 1. The permittee submitted notification according to Part I.D.1 and Part II.I.1 and 2;
- 2. The failure was not intentional or caused by the permittee's negligence, either in action or in failure to act;

- 3. The permittee has taken adequate measures to meet permit conditions in a timely manner or has submitted to the Executive Secretary, for the Executive Secretary's approval, an adequate plan and schedule for meeting permit conditions; and
- 4. The provisions of 19-5-107 have not been violated.

Page 10 of 13

IV. GENERAL REQUIREMENTS

- A. <u>Planned Changes</u>. The permittee shall give notice to the Executive Secretary as soon as possible of any planned physical alterations or additions to the permitted facility. Notice is required when the alteration or addition could significantly change the nature of the facility or increase the quantity of pollutants discharged.
- B. <u>Anticipated Noncompliance</u>. The permittee shall give advance notice of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.
- C. Spill Reporting The Permittee shall immediately report as per UCA 19-5-114 of the Utah Water Quality Act any spill or leakage from the tailings impoundment or associated facilities which is not totally contained by a collection system. This report shall be made to the phone numbers given in Part II I. A written report will be required within 5 days of the occurrence and should address the requirements of UCA 19-5-114 and Part II I 2 and 3 of this permit.
- D. <u>Permit Actions</u>. This permit may be modified, revoked and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance, does not stay any permit condition.
- E. <u>Duty to Reapply</u>. If the permittee wishes to continue an activity regulated by this permit after the expiration date of this permit, the permittee must apply for and obtain a permit renewal or extension. The application should be submitted at least 180 days before the expiration date of this permit.
- F. <u>Duty to Provide Information</u>. The permittee shall furnish to the Executive Secretary, within a reasonable time, any information which the Executive Secretary may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The permittee shall also furnish to the Executive Secretary, upon request, copies of records required to be kept by this permit.
- G. Other Information. When the permittee becomes aware that it failed to submit any relevant facts in a permit application, or submitted incorrect information in a permit application or any report to the Executive Secretary, it shall promptly submit such facts or information.
- H. <u>Signatory Requirements</u>. All applications, reports or information submitted to the Executive Secretary shall be signed and certified.
 - 1. All permit applications shall be signed as follows:
 - a. For a corporation: by a responsible corporate officer;
 - b. For a partnership or sole proprietorship: by a general partner or the proprietor, respectively.

- c. For a municipality, State, Federal, or other public agency: by either a principal executive officer or ranking elected official.
- 2. All reports required by the permit and other information requested by the Executive Secretary shall be signed by a person described above or by a duly authorized representative of that person. A person is a duly authorized representative only if:
 - a. The authorization is made in writing by a person described above and submitted to the Executive Secretary, and,
 - b. The authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility or activity, such as the position of plant manager, operator of a well or a well field, superintendent, position of equivalent responsibility, or an individual or position having overall responsibility for environmental matters for the company. (A duly authorized representative may thus be either a named individual or any individual occupying a named position.)
- 3. Changes to Authorization. If an authorization under Part IV H 2. is no longer accurate because a different individual or position has responsibility for the overall operation of the facility, a new authorization satisfying the requirements of Part IV H 2. must be submitted to the Executive Secretary prior to or together with any reports, information, or applications to be signed by an authorized representative.
- 4. Certification. Any person signing a document under this section shall make the following certification:

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

- I. Penalties for Falsification of Reports. The Act provides that any person who knowingly makes any false statement, representation, or certification in any record or other document submitted or required to be maintained under this permit, including monitoring reports or reports of compliance or noncompliance shall, upon conviction be punished by a fine of not more than \$10,000 per violation, or by imprisonment for not more than six months per violation, or by both.
- J. Availability of Reports. Except for data determined to be confidential by the permittee, all reports prepared in accordance with the terms of this permit shall be available for public inspection at the offices of the Executive Secretary. As required by the Act, permit applications, permits, effluent data, and ground water quality data shall not be considered confidential.

- K. <u>Property Rights</u>. The issuance of this permit does not convey any property rights of any sort, or any exclusive privileges, nor does it authorize any injury to private property or any invasion of personal rights, nor any infringement of federal, state or local laws or regulations.
- L. <u>Severability</u>. The provisions of this permit are severable, and if any provision of this permit, or the application of any provision of this permit to any circumstance, is held invalid, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected thereby.
- M. Transfers. This permit may be automatically transferred to a new permittee if:
 - 1. The current permittee notifies the Executive Secretary at least 30 days in advance of the proposed transfer date;
 - 2. The notice includes a written agreement between the existing and new permittee containing a specific date for transfer of permit responsibility, coverage, and liability between them; and,
 - 3. The Executive Secretary does not notify the existing permittee and the proposed new permittee of his or her intent to modify, or revoke and reissue the permit. If this notice is not received, the transfer is effective on the date specified in the agreement as described in Part IV.M.2, above.
- N. <u>State Laws</u>. Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, penalties established pursuant to any applicable state law or regulation under authority preserved by Section 19-5-117 of the Act.
- O. Reopener Provisions. This permit may be reopened and modified pursuant to R317-6-6.6.B or R317-6-6.10.C to include the appropriate limitations and compliance schedule, if necessary.

F:\wp\NOLILY\Permit\modified.per.wpd

Appendix E

Utah Underground Injection Control Program Inventory Information

MẠIL TO):	Well Class: Department of Environmental Quality
		Inventory
.	CWI	ID No.:
Division of P.O. Box		Quality Date Entered: / By Salt Lake Cit (leave this block blank)
Utah 841	14 - 4870	
		UTAH UNDERGROUND INJECTION CONTROL PROGRAM
		INVENTORY INFORMATION
		General Facility and Injection Well Information
Please pr wells. Pl	ovide the	e information requested below This form is to be submitted by the owner or operator of a facility having one or more inject e or print (ink). If you have any questions, call 801-538-6146.
1.	Facilit	ty Information.
	A.	Facility Name: Silver City, Utah Heap Leach Phone No.: N/A
	B.	Local Address: N/A (Closed Facility) See Item D Below
		(Number & Street, Route, City, Zip Code)
	C.	Mail Address: 1800 Glen Arm Place, Suite 210
		Denver Colorado 80202
		(If Different than Above; Number & Street, Box and/or Route, City, State, Zip Code)
	D.	Facility Location* County: Juab
	D.	
		T. 10 S , R. 3 W , Sec. 35 , NE 1/4 of NE 1/4, Lat. 39 ° 54 ′ 55 "N, Long. 112 ° 08 ′ 27 "W
		*Note: A topographic mapor detailed aerial photograph should be used to locate the facility or well.
2.	Well	Owner/Operator/Legal Contact Information.
	A.	Owner
	1.	Name: North Lily Mining Company Phone No.: (303) 294-0427
	2.	Mail Address 1800 Glen Arm Place, Suite 210
		Denver Colorado 80202
		(Number & Street, Box &/or Route, City, State, Zip Code)
	В.	Operator (if different than Owner above)
	1.	Name:Phone No.:()
	2.	Mail Address
		(Number & Street, Box &/or Route, City, State, Zip Code)
	C.	Legal Contact
		Name: Mr. Gene Webb Phone No:(303)294-0427
		Title: Executive Vice President
		Mail Address: 1800 Glen Arm Place, Suite 210

Denver Colorado 80202

[X] Private [] Public (State or Local) [] Indian [] Federal

Organization:

[] Other, please describe:

Type of Facility (check one)

3.

UICFORM.009

(Continued on back)

(Number & Street, Box and/or Route, City, State, Zip Code)

4.	[X]	tion Well Status (indicate numbe Active Femporarily Abandoned Permanently Abandoned	[] Proposed [] Under Construction/Modification
5.	SIC	Codes: 104	Code Numbers Used in Census & Other Government Reports
5.	same c	truction Details. Enter requested onstruction methods please note. If do the not yet constructed. Well diagram	information for each well noted in 4 above (use additional forms as needed). If all wells use that a is not available enter NAV. If category is not applicable enter NAP. Enter proposed details a may be substituted.
	A.	Well Identification No./Name	North Lily Drain Field
	B.	Well Depth	Trench depth @ approx.5980 feet
	C.	Casing Type For drywells Duracrete etc.	White PVC
	D.	Casing Diameter	<u>4"</u>
	E.	Grout Type	<u>N/A</u>
	F.	Screened Interval	2750' of horizontal screened PVC
	G.	Water Elevation	From two wells in the area the static water depth is 5,575'. The depth to water is 400' to 410'.
		Indicate if Artesian	The deput to water is 400 to 410.
	H.	Well Elevation	The topographic elevations range from approximately 5985' to 6010'
	I.	Injection Pressure	The drain field will be gravity fed.
7.	Initia	al Date of Injection:	May 8, 2001
8.	Injec	ction Fluid Description:	Heap Leach drain and water run-off water.
9. 10.		etion Fluid Source: ual Volume Injected	Heap Leach 1,576,800 to 3,153,600 (depending on annual precipitation)
11.	Com	(gallons) nments:	
	_		
The	informa	ation below should be provide	ed by the person filling out the form:
Jame	s R. Sa	FFICIAL TITLE (type or pri ge III tal Analyst / Geologist	(801) 943-4144 PHONE NO. (area code & no.)
	NATUR	258-	DATE SIGNED UICFORM.0



Michael O. Leavitt
Governor
Dianne R. Nielson, Ph.D.

Don A. Ostler, P.E. Director

Executive Director

RECEIVED APR 1 9 2001

DEPARTMENT OF ENVIRONMENTAL QUALITY DIVISION OF WATER QUALITY

288 North 1460 West P.O. Box 144870 Salt Lake City, Utah 84114-4870 (801) 538-6146 (801) 538-6016 Fax (801) 536-4414 T.D.D. www.deq.state.ut.us Web Done 4/19/01 BXB ater Quality Board K.C. Shaw, P.E.

William R. Williams
Vice Chairman
Robert G. Adams
Nan Bunker
Ray M. Child, C.P.A.
John R. Cushing, Mayor
Dianne R. Nielson, Ph.D.
Ronald C. Sims, Ph.D.
Douglas E. Thompson, Mayor
J. Ann Wechsler
Don A. Ostler, P.E.
Executive Secretary

April 13, 2001

Mr. Robert J. Bayer, RPG Vice President JBR Environmental Consultants, inc. 8160 South Highland Drive, Suite A-4 Sandy, Utah 84093

Dear Mr. Bayer:

SUBJECT: CUSTOMER SURVEY

On April 5, 2001, the Utah Water Quality Board issued a construction permit for the construction of a subsurface disposal system for the post closure fluid management.

Please take a moment to complete the enclosed, pre-addressed and postage-paid questionnaire. Your feedback is very important to us, to streamline and improve the approval process and to meet your needs effectively.

I sincerely appreciate and thank you for the time taken to respond and return this questionnaire.

Best regards,

Kiran L. Bhayani, P.E. D.EE.

Manager, Design Evaluation Section

Enclosure

KLB:

NORTH LILY SUBSURFACE SYSTEM JBR 04122001 23:28-12APR2001/KLB

FILE: NORTH LILY MINING COMPANY

Appendix F

Class IIIb Industrial Landfill Permit by Rule and Recorders Office Document



Michael O. Leavitt Governor Dianne R. Nielson, Ph.D. **Executive Director** Dennis R. Downs

DEPARTMENT OF ENVIRONMENTAL QUALITY COLVED MAY - 8 2001 DIVISION OF SOLID AND HAZARDOUS WASTE

288 North 1460 West P.O. Box 144880 Salt Lake City, Utah 84114-4880 (801) 538-6170 (801) 538-6715 Fax (801) 536-4414 T.D.D. www.deq.state.ut.us Web

May 7, 2001

Director

Robert J. Bayer, Managing Principal JBR Environmental Consultants, Inc. 8160 South Highland Drive Sandy, Utah 84093

Subject:

North Lily's Silver City Heap Leach Facility Reclamation - Industrial Solid Waste Landfill, Juab

County

Dear Mr. Bayer:

The application for a Permit by Rule for a Class IIIb Landfill at the North Lily Mining Company's Silver City Heap Leach Facility located in the SW1/4, NE1/4, NE1/4, of Section 35 Township 10 South, Range 3 West, Salt Lake Base and Meridian, Juab County has been reviewed.

It is determined that the waste disposed at the solid waste disposal site will be nonhazardous industrial waste and that the closure and reclamation activities at the site will be as stringent as the requirements for an Industrial Solid Waste Landfill specified in Utah Administrative Code (UAC) R315-304-5(2)(b). Also, the reclamation bond required by the Division of Oil, Gas, and Mining includes the closure and reclamation of the solid waste disposal site.

Therefore, the solid waste disposal site at the North Lily Mining Company's Silver City Heap Leach Facility meets the requirements of UAC R315-318 and is hereby permitted by rule under the condition that the requirements of UAC R315-302-2(6) are met. This requirement specifies that the owner or operator of a solid waste disposal facility shall, within 60 days of closure, make a change in the record of title that the property has been used as a solid waste disposal site and submit proof of the record of title filing to the Executive Secretary.

If you have questions or need further information on this matter, please contact Ralph Bohn or Carl Wadsworth at 801-538-6170.

Sincerely.

Dennis R. Downs, Executive Secretary

Utah Solid and Hazardous Waste Control Board

DRD/CEW/kk

Wayne Hedburg, Division of Oil, Gas, and Mining c:

Larry Mize, Division of Water Quality

Robert Resendes, M.B.A., M.T., Director, Central Utah Public Health Department

Roger Foisy, DEQ District Engineer

f:\shw\spb\cwadswor\wp\nrth-lily.pmt File: North Lily Mining Company

CRAIG J. SPERRY, JUAB COUNTY RECORDER 2001 JUL 06 13:42 PM FEE \$11.00 BY DPZ FOR: JBR ENVIRONMENTAL CONSULTANTS, INC.

8160 South Highland Drive • Sandy, Utah 84093 • (801) 943-4144 • Fax (801) 942-1852

06/26/01

Juab County Recorders Office 160 North Main Street Nephi, Utah 84648

RE: Class IIIb Industrial Landfill in Juab County, Utah

To whom it may concern:

This is a notification of a recently installed and closed Class IIIb Industrial Landfill in Juab County, Utah under the supervision of JBR Environmental Consultants, Inc. for the North Lily Mining Company Denver, Colorado. The State of Utah Division of Environmental Quality, Division of Solid and Hazardous Waste approved the landfill by a Permit by Rule in a letter sent on May 7, 2001 by Dennis R. Downs, Executive Secretary, Utah Solid and Hazardous Waste Control Board (see attached letter).

Location:

SW ¼ of NE ¼ of NE ¼ T. 10 S. R. 3 W. Section 35

T. 10 S. R. 3 W. NW ¼ of SE ¼ of NE ¼ Section 35

James R Sage

Geologist/Environmental Technician

Norma Stokes

Notary

NORMA STOKES

IOTARY PUBLIC - STATE of UTAH 60 SOUTH HIGHLAND DR. SANDY, UT 84093 COMM EXPIRES 7-26-2001

Robert J Bayer

Attachmen

Corporate Office • Sandy, Utah (801) 943-4144 Fax (801) 942-1852

Cedar City, Utah (435) 662-8793 Fax (435) 662-7106

Springville, Utah (801) 489-7120 Fax (801) 489-7129

Reno, Nevada (775) 747-5777 Fax (775) 747-2177

Elko, Nevada (775) 738-8766 Fax (775) 738-2264

Boise, Idaho (208) 853-0883 Fax (208) 853-0884

Appendix G

Heap Drainage Water Quality Data



Date: 1/17/02

JBR Consultants attn. Jim Sage 8160 South Highland Drive, Ste. A-4 Sandy, UT 84093

AMENDED REPORT

Project: N LILY-01

Project Group No. 50781

Date Sample(s) Submitted: 11/27/01

This is the final report for project 50781 and contains 3 pages of information in addition to attachments. Individual pages or sections of this report may not be separated when using the information for regulatory compliance.

The analyses presented on this report were performed in accordance with National Environmental Laboratory Accreditation Program (NELAP), Section 5.13.

Please feel free to contact us at (801) 262-7299 or (801) 262-7378 (fax) if you have questions or comments regarding this report.

Dave Gayer
Laboratory Director
dave@chemtechford.com

Linda Daniels
Customer Representative

Approved By:

Dave Gaver, Laboratory Directo



Lab No: 01-U011383 Report Date: 1/17/02

JBR Consultants atm. Jim Sage 8160 South Highland Drive, Ste. A-4 Sandy, UT 84093

CERTIFICATE OF ANALYSIS

DATE

Sample Description:

MW- 11/27/01

Project:

N LILY-01 WASTE WATER

Sample Matrix: Lab Group No:

50781

Date/Time Sampled: Date/Time Received: 11/27/01 , 12:00 11/27/01 , 16:45

Sample Note(s):

Sample received on ice.

PARAMETER / UNITS	RESULT	MRL	ANALYZED		METHOD	analyst
INORGANIC PARAMETERS	350	ı	11/29/01		SM 2320B	CSM
Alkalinity, as Bicarbonate, mg/L	< 1	1	11/29/01	14:45	SM 2320B	CSM
Alkalinity, as Carbonate, mg/L	350	10		16:00	HACH 8000	CSM
Chemical Oxygen Demand, mg/L	1,900	10	12/10/01		EPA 300.0	CSM
Chloride, mg/L	21,000	1	12/13/01		EPA 120.1	TAH
Conductance, Specific, umhos/cm	2.8	0.008			ASTM D2036	
Cyanide, Amenable to Cl2, mg/L	3.1	0.1	12/ 3/01	15:00	ASTM D2036	
Cyanide. Total. mg/L	0.42	0.01	12/ 3/01	15:00	ASTM D2036	
Cyanide, WAD, mg/L	3.2	0.1	4 - 1	12:43	EPA 300.0	CSM
Fluoride, mg/L	310	40		14:00	EPA 353.1	TSM
Nitrate, Nitrogen (Calc.), mg/L	130	6.2			EPA 354.1	TSM
Nitrite, Nitrogen, mg/L	7.6	0.1		14:20	EPA 150.1	eje
pH, units	8,000	50			EPA 300.0	CSM
Sulfate, mg/L	0.012	0.005			EPA 200.7	MJB
Barium (T), as Ba, mg/L	410	0.2			EPA 200.7	MJB
Calcium (T), as Ca, mg/L	< 0.005	0.005	_			MJB
Chromium (T), as Cr, mg/L	2.6	0.01			EPA 200.7	MJB
Copper (I), as Cu, mg/L		0.2	4 - 1			MJB
Magnesium (T), as Mg, mg/L	53 220	0.2				MJB
Potassium (T), as K, mg/L		4	4. 4	10:23		MJB
Sodium (T), as Na, mg/L	4,900	0.01				MJB
Zinc (T), as Zn, mg/L	2.2	0.0005				JJT
Arsenic (T), as As. mg/L	0.17	0.0005	*			JJT
Cadmium (T), as Cd, mg/L	0.021	0.005				JJT
Lead (T), as Pb, mg/L	0.18			13:32		JJT
Mercury (T), as Hg, mg/L Selenium (T), as Se, mg/L	0.0060 0.20	0.0002				JJT
Serement (a) , an ear a.						



Lab No: 01-U011383 Report Date: 1/17/02

JBR Consultants atm. Jim Sage 8160 South Highland Drive, Ste. A-4 Sandy, UT 84093

CERTIFICATE OF ANALYSIS

Sample Description:

MW- 11/27/01

Project:

N LILY-01

Sample Matrix:

WASTE WATER

Lab Group No:

50781

Date/Time Sampled: Date/Time Received: 11/27/01 , 12:00 11/27/01 , 16:45

Sample Note(s):

Sample received on ice.

Shimple received	Oll loc.		DATE		
PARAMETER / UNITS	RESULT	MRL	ANALYZED	METHOD	ANALYST
INORGANIC PARAMETERS Silver (T), as Ag, mg/L Temperature, Receiving, C	0.069	0.0005	12/11/01 13:32 11/27/01 16:45		jjt SPS



01-U008033 Lab No: Report Date: 9/25/01

JBR Consultants attn. Jim Sage 8160 South Highland Drive, Ste. A-4 Sandy, UT 84093

CERTIFICATE OF ANALYSIS

Sample Description:

N Lily Dist. Box

Project:

NLILY-01

Sample Matrix:

WASTE WATER

48432

Lab Group No: Date/Time Sampled: Date/Time Received:

8/28/01 , 11:30 8/28/01 , 13:05

Sample Note(s):

Sample received on ice.

PARAMETER / UNITS	RESULT	MRL	ANALYZED		METHOD	ANALYS
NORGANIC PARAMETERS	- Fac 25		ALC: N		av 0300F	CSM
Alkalinity, as Bicarbonate, mg/L	360	1	9/6/01		SM 2320B	CSM
Alkalinity, as Carbonate, mg/L	< 1	1	9/6/01		SM 2320B	CSM
Chemical Oxygen Demand, mg/L	490	10	9/6/01		HACH 8000 EPA 300.0	CSM
Chloride, mg/L	1,900	0.5	8/30/01		EPA 300.0	МЈВ
Conductance, Specific, umhos/cm	19,000	1	9/6/01			TC
Cyanide, Amenable to Cl2, mg/L	4.3	0.032	9/19/01		ASTM D2036	TC
Cyanide, Total, mg/L	4.4	0.4	8/30/01		ASTM D2036	
Cyanide, WAD, mg/L	0.52	0.032	9/ 5/01		ASTM D2036	
Fluoride, mg/L	3.2	0.5	8/30/01		EPA 300.0	CSM
Mercury, as Hg Total, mg/L	0.015	0.0002	9/ 5/01		EPA 245.2	MJB
Nitrate, Nitrogen, mg/L	280	0.1	8/30/01		EPA 300.0	CSM
Nitrite, Nitrogen, mg/L	81	0.05	8/30/01		EPA 300.0	CSM
pH, units	7.8	0.1	8/28/01		EPA 150.1	EJB
Sulfate, mg/L	7,800	1	8/30/01		EPA 300.0	CSM
Barium (T), as Ba, mg/L	0.015	0.005	8/30/01		EPA 200.7	МЈВ
Calcium (T), as Ca, mg/L	400	0.2	8/30/01		EPA 200.7	МЈВ
Chromium (T), as Cr, mg/L	< 0.005	0.005	8/30/01		EPA 200.7	МЈВ
Copper (T), as Cu, mg/L	3.1	0.01	8/30/01		EPA 200.7	MJB
Magnesium (T), as Mg, mg/L	48	0.2	8/30/01		EPA 200.7	MJB
Potassium (T), as K, mg/L	240	0.2	8/30/01		EPA 200.7	MJB
Sodium (T), as Na, mg/L	510	20	8/31/01		EPA 200.7	MJB
Zinc (T), as Zn, mg/L	1.4	0.01	8/30/01		EPA 200.7	MJB
Arsenic (T), as As, mg/L	0.14	0.0005			EPA 200.8	JJT
Cadmium (T), as Cd, mg/L	0.0097	0.0005	9/ 5/01		EPA 200.8	JJT
Lead (T), as Pb, mg/L	0.085	0.005	9/ 5/01	14:18	EPA 200.8	JJT
Selenium (T), as Se, mg/L	0.12	0.0005	9/ 5/01	14:18	EPA 200.8	JJT





Lab No: 01-U008033 Report Date: 9/25/01

JBR Consultants attn. Jim Sage .8160 South Highland Drive, Ste. A-4 Sandy, UT 84093

CERTIFICATE OF ANALYSIS

Sample Description:

N Lily Dist. Box

Project:

NLILY-01

Sample Matrix:

WASTE WATER

48432

Lab Group No: Date/Time Sampled: Date/Time Received:

8/28/01, 11:30 8/28/01, 13:05

Sample Note(s):

Sample received on ice.

PARAMETER / UNITS	RESULT	MRL	ANALYZED	METHOD	ANALYST
INORGANIC PARAMETERS Silver (T), as Ag, mg/L Temperature, Receiving, C	0.080	0.0005	9/ 5/01 14:18 8/28/01 13:05		JJT SPS

Date: 5/10/01

To: JBR Consultants attn. Rich Pratt

8160 South Highland Drive, Ste. A-4

Sandy, UT 84093

Group #: 45202 Lab #: 01-U003516 Project: N LILY -01

Sample Desc: Preg Pond Sample Matrix: WASTE WATER Date/Time Sampled: 4/19/01, 9:30 Date/Time Received: 4/19/01, 11:40

CERTIFICATE OF ANALYSIS

MINIMUM DARMING

KEPORITING	
LIMIT	DATE

PARAMETER	RESULT	LIMIT (MRL)	ANALYZED		METHOD	ANALYST
INORGANIC PARAMETERS						
Alkalinity, as Bicarbonate, mg/L	280	1	4/25/01	11:45	SM 2320B	CSM
Alkalinity, as Carbonate, mg/L	< 1	1	4/25/01	11:45		CSM
Chloride, mg/L	2,100	50	4/23/01		EPA 325.3	CSM
Conductance, Specific, umhos/cm	22,000	1	4/26/01	10:35		TAH
Cyanide, Amenable to Cl2, mg/L	16	0.002			ASTM D2036	
Cyanide, Total, mg/L	16	1	4/24/01		ASTM D2036	
Cyanide, WAD, mg/L	12	3.2			ASTM D2036	
Fluoride, mg/L	5.6	0.5	4/22/01			TSM
Mercury, as Hg Total, mg/L	0.019	0.0002	4/27/01			MJB
Nitrite, Nitrogen, mg/L	57	2.5	4/19/01			TSM
Nitrate+Nitrite-Total, mg/L	160	50	4/30/01			PNM
pH, units	8.2	0.1				CSM
Sulfate, mg/L	11,000	2000				TSM
Barium (T), as Ba, mg/L	0.045	0.005				MJB
Calcium (T), as Ca, mg/L	280	0.2	4/26/01	15:57	EPA 200.7	MJB

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

1 Page

{generic.rpt}

Date: 5/10/01

To: JBR Consultants attn. Rich Pratt

8160 South Highland Drive, Ste. A-4

Sandy, UT 84093

Group #: 45202 Lab #: 01-U003516 Project: N LILY -01

Sample Desc: Preg Pond

Sample Matrix: WASTE WATER Date/Time Sampled: 4/19/01, 9:30 Date/Time Received: 4/19/01, 11:40

CERTIFICATE OF ANALYSIS

MINIMUM

		KEPUKIT	NG			
PARAMETER	RESULT	LIMIT (MRL)			METHOD	ANALYST
INORGANIC PARAMETERS Chromium(T), as Cr, mg/L Copper (T), as Cu, mg/L	< 0.005 15	0.005	4/26/01 4/26/01	15:57	EPA 200.7 EPA 200.7 EPA 200.7	MJB MJB MJB
Magnesium (T), as Mg, mg/L Potassium (T), as K, mg/L Sodium (T), as Na, mg/L Zinc (T), as Zn, mg/L Arsenic (T), as As, mg/L Cadmium (T), as Cd, mg/L Lead (T), as Pb, mg/L Selenium (T), as Se, mg/L Silver (T), as Ag, mg/L Temperature, Receiving, C	110 260 5,100 0.48 0.17 0.006 0.20 0.15 0.64	0.2 0.2 20 0.01 0.005 0.005 0.005 0.005	4/26/01 4/26/01 5/ 8/01 4/26/01 5/ 7/01 5/ 7/01 5/ 7/01 5/ 7/01 5/ 7/01 4/19/01	15:57 12:08 15:57 17:43 17:43 17:43 17:43	EPA 200.7 EPA 200.7 EPA 200.8 EPA 200.8 EPA 200.8 EPA 200.8 EPA 200.8	MJB MJB MJB JJT JJT JJT JJT JJT SPS

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page

{generic.rpt}

Date: 5/10/01

To: JBR Consultants attn. Rich Pratt

8160 South Highland Drive, Ste. A-4

Sandy, UT 84093

Group #: 45202 Lab #: 01-U003516 Project: N LILY -01

Sample Desc: Preg Pond

Sample Matrix: WASTE WATER Date/Time Sampled: 4/19/01, 9:30 Date/Time Received: 4/19/01, 11:40

CERTIFICATE OF ANALYSIS

MUMINIM

REPORTING

LIMIT DATE

RESULT (MRL) ANALYZED METHOD ANALYST

INORGANIC PARAMETERS

PARAMETER

NOTE: Sample not received on ice.

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page

{generic.rpt}

6100 SOUTH STRATLER SALT LAKE CITY UTAH 84107 6905 801 262 7299 PHONE 801 262 7378 FAX

Date: 9/22/00

ANALYTICAL LABORATORIES

To: JBR Consultants

attn. Scott Page 8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007946 Project: SILVER PEAK

Sample Desc: Heap Leach Outfall Sample Matrix: WASTE WATER Date/Time Sampled: 8/22/00 , 14:00 Date/Time Received: 8/23/00 , 10:15

CERTIFICATE OF ANALYSIS

MINIMUM

REPORTING

		LIMIT	DATE			
PARAMETER	RESULT	(MRL)	ANALYZED		METHOD	ANALYST
INORGANIC PARAMETERS						
Alkalinity, as Bicarbonate, mg/L	388	ı	8/25/00	12:00	SM 2320B	TSM
Alkalinity, as Carbonate, mg/L	< 1	1	8/25/00	12:00	SM 2320B	TSM
Chloride, mg/L	2,220	10	8/30/00	14:00	EPA 325.3	TSM
Conductance, Specific, umhos/cm	23,300	1	B/31/00	10:15	EPA 130.1	MJB
Cyanide, Amenable to Cl2, mg/L	18.8	0.002	9/ 1/00	13:00	ASTM D2036	PNM
Cyanide, Total, mg/L	19	1	9/ 1/00	13:00	ASTM D2036	PNM
Cyanide, WAD, mg/L	14.4	0.457	9/8/00	8:00	ASTM D2036	PNM
Fluoride, mg/L	6.7	0.2	9/ 7/00	10:00	EPA 340.2	TSM
Mercury, as Hg (D), mg/L	< 0.0002	0.0002	8/28/00	12:40	EPA 245.2	. MJB
Nitrite, Nitrogen, mg/L	51	1.25	8/23/00	12:45	EPA 354.1	TSM
Nitrate+Nitrite-Total, mg/L	145	10	8/31/00	15:00	EPA 353.1	ejb
	8.1	0.1	8/23/00	12:30	EPA 150.1	LPS
pH, units Sulfate, mg/L	10,200		8/29/00	16:00	EPA 375.4	TSM
Total Dissolved Solids, mg/L	20,000	25	8/24/00	12:30	EPA 160.1	LPS
Barium (D), as Ba, mg/L	0.010	0.005	8/29/00	15:19	EPA 200.7	jjt

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page

{generic.rpt}

6100 SOUTH STRATLER SALT LAKE CITY UTAH 84107 8905 801 262 7288 PHONE 801 262 7378 FAX

Date: 9/22/00

To: JBR Consultants

attn. Scott Page

8160 South Highland Drive, Ste. A-4

Sandy, UT 84088

Group #: 39788 Lab #: 00-U007946 Project: SILVER PEAK

Sample Desc: Heap Leach Outfall Sample Matrix: WASTE WATER

Date/Time Sampled: 8/22/00 , 14:00 Date/Time Received: 8/23/00 , 10:15

CERTIFICATE OF ANALYSIS

MINIMUM

RP	OR	T	TN	G		
					_	١

PARAMETER	RESULT	LIMIT (MRL)	DATE ANALYZED		METHOD	ANALYST
INORGANIC PARAMETERS						
Calcium (T), as Ca, mg/L	350	0.2	8/29/00		EPA 200.7	JJT
Chromium (D), as Cr, mg/L	< 0.005	0.005	8/29/00		EPA 200.7	JJT
Copper (D), as Cu, mg/L	19	0.01	8/29/00		EPA 200.7	JJT
Magnesium (T), as Mg, mg/L	29	. 0.2	8/29/00	15:19	EPA 200.7	JJT
Potassium (T), as K, mg/L	310	0.2	8/29/00	15:19	EPA 200.7	JJT
Sodium (T), as Na, mg/L	5,600	20	9/ 5/00	16:25	EPA 200.7	JJT
Zinc (D), as Zn, mg/L	0.42	0.01	8/29/00	15:19	EPA 200.7	JJT
Arsenic (D), as As, mg/L	0.2464	0.0005	9/6/00	14:16	EPA 200.8	JJT
Cadmium (D), as Cd, mg/L	0.0076	0.0005	9/6/00	14:16	EPA 200.8	JJT
Lead (D), as Pb, mg/L	0.1581	0.0005	9/6/00	14:16	EPA 200.8	JJT
	0.2707	0.0005	9/ 6/00	14:16	EPA 200.8	JJT
Selenium (D), as Se, mg/L	0.3147	0.0005	9/6/00		200.2/200.8	B <i>JJ</i> T
Silver (D), as Ag, mg/L		0.0003	8/23/00			CSM
Temperature, Receiving, C	19.0		6/23/00	10.15		0511

Approved By:

David Gayer, Laboratory Director

MRL = Report detection limit

Page

(generic.rpt)

6100 SOUTH STRATLER SALT LAKE CITY UTAH 84107 6905 801 262 7299 PHONE 801 262 7378 FAX Utah DEQ/Water Quality rax:801-336-0010

UTAH STATE DEPARTMENT OF HEALTH DIVISION OF LABORATORY SERVICES Environmental Chemistry Analysis Report

JEP 24

UDEQ - DWQ ARNE HULTQUIST 288 N 1460 W PO BOX 144870 SALT LAKE CITY

2000

UT 84114-4870

801-538-6146

Lab Number: . 200002437 Sample Type: 04 Cost Code: 352 Description: NORTH LILY FLOW FROM HEAP LEACH INTO POND Organic Review: Source No: 02 Site ID: 599712 Inorganic Review: Time: 10:00 Sample Date: 04/04/00 Radiochemistry Review: Microbiology Review: 272.7 me/l6297 mg/l 6797 mg/l Tot. Cations: 157.9 me/lTot. Anions: %D = 26.713094 mg/l Grand Total: TEST RESULTS: 9.0 mg/lT.Sus.Sol 8.68 35.0 mg/lL-pH Cyanide 2110.0 mg/l <5.0 ug/1NO2+NO3, N D-Barium 76.0 ug/l481 mg/l D-Arsenic D-Calcium <1.0 ug/1332.0 ug/l D-Cadmium D-Copper <5.0 ug/1 $9.0 \, \text{ug/l}$ D-Chromium D-Lead <20.0 ug/111.0 ug/l D-Iron D-Mangan 23.4 mg/l14.0 ug/l D-Magnesum D-Selenium 293 mg/l 5500.0 mg/l D-Potassum D-Sodium 29.0 ug/l 248 mg/l D-Silver Bicarbnate <30.0 ug/10 mg/l D-Zinc Carbonate 1 mg/l0 mg/lCarb. Diox Hydroxide 2025 mg/l 203 mg/l Chloride Tot. Alk. 4650.0 mg/l 0.235 NTU Sulfate Turbidity 1296.4 mg/l18358 mg/l T. Hardns. TDS @ 180C 22000 umhos 34.87 mg/l L-Sp. Cond Cyan. (Cl) <30.0 ug/lD-Aluminum 122 mg/l CO3 Solids 89.1 ug/l D-Mercury

QUALIFYING COMMENTS (*) on test results: NO COMMENTS

END OF REPORT

Appendix H

Heap Drainage Water Quantity Data

66 I £61 **L81** 181 SLI 69I 163 LSI ISI \$†I 136 133 LZI 171 SII 601 -+- Series1 Date 103 46 16 ς8 *6L* ٤L *L*9 19 ςς **6**† ٤4 Lε 18 52 **6**I $\mathfrak{l}\mathfrak{I}$ (GPM) Sign (GPM) 5.0 10.0 20.0 30.0 25.0

Heap Leach Pad Discharge

Date	Daily Average (GPM)	Application Stie	Return Rate (Feet)	RetumRate (GPM)	Amount Pumped From Preg Pond
July 3, 2000	100	N/A	N/A		
July 4, 2000	100	N/A	N/A		
July 5, 2000	100	N/A	N/A		270
July 6, 2000	100	N/A	N/A		
July 7, 2000	100	N/A	N/A		
July 10, 2000	95	N/A	N/A		
July 11, 2000	95	N/A	N/A		
July 12, 2000	90	N/A	N/A		260
July 13, 2000	90	N/A	N/A		
July 14, 2000	95	N/A	N/A		
July 15, 2000	225	N/A	N/A		28.7
July 17, 2000	N/A	Recycle into Preg	N/A		
July 18, 2000	220	N/A	N/A	1.5 4 5 9	
July 19, 2000	220	N/A	N/A	* - F- 1-72	250
July 20, 2000	220	N/A	N/A		
July 21, 2000	220	N/A	N/A	100	
July 24, 2000	N/A	Recycle into Preg	N/A		
July 25, 2000	N/A	Recycle into Preg	N/A		280
July 26, 2000	300	Pad and Preg	N/A		
July 27, 2000	300	Pad and Preg	N/A		
July 28, 2000	300	Pad and Preg	N/A		
July 30, 2000	N/A	Recycle into Preg	0.24		
July 31, 2000	N/A	Overflow	0.24		670
August 1, 2000	N/A	Overflow	0.24		270
August 2, 2000	N/A	Overflow	0.22		2 25
August 3, 2000	N/A	Overflow	0.22		
August 6, 2000	N/A	Rec	N/A		000
August 7, 2000	N/A	Rec	N/A		300
August 8, 2000	360	Pad and Preg	N/A		
August 9, 2000	360	Pad and Preg	N/A		200
August 10, 2000	360	Pad and Preg	N/A	1	200
August 11, 2000	360	Pad and Preg	N/A		
August 12, 2000	360	Pad and Preg	N/A	00.4	
August 13, 2000	360	Rec	0.19	23.1	
August 14, 2000	360	Rec	0.19	23.1	T S S S S S S S S S S S S S S S S S S S
August 15, 2000	360	Rec	0.19	23.1	490
August 16, 2000	360	Rec	0.19	23.1	490
August 17, 2000	360	Rec	0.2	25.0	
August 18, 2000	360	Rec	0.2	25.0	
August 19, 2000	360	Rec	0.21	27.0	
August 20, 2000	340	Rec	0.21	27.0	
August 21, 2000	340	Rec	0.21	27.0	
August 22, 2000	340	Rec	0.21	27.0	
August 23, 2000	340	Rec	0.21	27.0	

KEY N/R = Not Recorded N/A = Not Avaliable

August 24, 2000	340	Rec	0.21	27.0	500
August 27, 2000	350	Preg and Overflow	0.19	23.1	
August 28, 2000	220	Preg and Overflow	0.18	21.3	
August 29, 2000	220	Preg and Overflow	0.18	21.3	
August 30, 2000	340	Preg and Overflow	0.17	19.5	
August 31, 2000	200	Preg and Overflow	0.17	19.5	475
September 1, 2000	210	Preg and Overflow	0.16	17.7	
September 5, 2000	N/A	Recycle to preg pond	0.14	14.4	4.94
September 6, 2000	N/A	Recycle to preg pond	0.14	14.4	
September 7, 2000	N/A	Recycle to preg pond	0.14	14.4	500
September 8, 2000	N/A	Recycle to preg pond	0.14	14.4	
September 9, 2000	N/A	Recycle to preg pond	0.13	12.8	
September 10, 2000	N/A	Recycle to preg pond	0.13	12.8	
September 11, 2000	N/A	Overflow Ponds	0.13	12.8	
September 12, 2000	N/A	Overflow Ponds	0.12	11.3	
September 13, 2000	N/A	Overflow Ponds	0.12	11.3	480
September 14, 2000	N/A	Overflow Ponds	0.12	11.3	
September 15, 2000	N/A	Overflow Ponds	0.12	11.3	
September 16, 2000	N/A	Overflow Ponds	0.12	11.3	
September 18, 2000	N/A	Recycle to preg pond	0.12	11.3	1 1
September 19, 2000	N/A	Recycle to preg pond	0.12	11.3	
September 20, 2000	N/A	Recycle to preg pond	0.11	9.1	490
September 21, 2000	N/A	Recycle to preg pond	0.11	9.1	
September 21, 2000 September 22, 2000	N/A	Recycle to preg pond	0.11	9.1	
September 23, 2000	N/A	Recycle to preg pond	0.11	9.1	
September 25, 2000	N/A	Recycle to preg pond	0.11	9.1	
September 26, 2000	N/A	Recycle to preg pond	0.11	9.1	
September 27, 2000	N/A	Recycle to preg pond	0.11	9.1	475
September 28, 2000	N/A	Recycle to preg pond	0.10	8.6	
September 29, 2000	N/A	Recycle to preg pond	0.10	8.6	
October 2, 2000	N/A	Recycle to preg pond	0.10	8.6	At a comme
October 3, 2000	N/A	Recycle to preg pond	0.10	8.6	
October 4, 2000	N/A	Recycle to preg pond	0.10	8.6	469
October 5, 2000	N/A	Recycle to preg pond	0.10	8.6	37.7
October 6, 2000	N/A	Recycle to preg pond	0.10	8.6	
October 9, 2000	N/A	Recycle to preg pond	0.10	8.6	
October 10, 2000	N/A	Recycle to preg pond	0.10	8.6	
October 11, 2000	N/A	Recycle to preg pond	0.10	8.6	100
October 12, 2000	N/A	Recycle to preg pond	0.10	8.6	490
October 13, 2000	N/A	Recycle to preg pond	0.10	8.6	
October 16, 2000	N/A	Recycle to preg pond	0.10	8.6	
October 17, 2000	N/A	Recycle to preg pond	0.10	8.6	
October 18, 2000	N/A	Recycle to preg pond	0.10	8.6	480
October 19, 2000	N/A	Recycle to preg pond	0.10	8.6	
October 20, 2000	N/A	Recycle to preg pond	0.10	8.6	
October 23, 2000	N/A	Recycle to preg pond	0.10	8.6	
October 24, 2000	N/A	Recycle to preg pond	0.10	8.6	
October 25, 2000	N/A	Recycle to preg pond	0.09	7.3	440

KEY N/R = Not Recorded N/A = Not Avaliable

0 1 1 00 0000 1	NI/A	Decuele to progrand	0.09	7.3	
October 26, 2000	N/A	Recycle to preg pond	0.09	7.3	
October 27, 2000	N/A	Recycle to preg pond	0.10	8.6	
November 6, 2000	N/A	Recycle to preg pond	0.09	7.3	·
November 7, 2000	N/A	Recycle to preg pond	0.09	7.3	390
November 8, 2000	N/A	Recycle to preg pond		8.6	390
November 9, 2000	N/A	Recycle to preg pond	0.10		THE PERSON NAMED IN
November 10, 2000	N/A	Recycle to preg pond	0.10	8.6	
November 13, 2000	N/A	Recycle to preg pond	0.10	8.6	
November 14, 2000	N/A	Recycle to preg pond	0.10	8.6	390
November 15, 2000	N/A	Recycle to preg pond	0.10	8.6	390
November 16, 2000	N/A	Recycle to preg pond	0.10	8.6	
November 17, 2000	N/A	Recycle to preg pond	0.10	8.6	
November 20, 2000	N/A	Recycle to preg pond	0.10	8.6	
November 21, 2000	N/A	Recycle to preg pond	0.10	8.6	
November 22, 2000	N/A	Recycle to preg pond	0.10	8.6	350
November 23, 2000	N/A	Recycle to preg pond	0.09	7.3	
November 24, 2000	N/A	Recycle to preg pond	0.09	7.3	
November 27, 2000	N/A	Recycle to preg pond	0.09	7.3	
November 28, 2000	N/A	Recycle to preg pond	0.09	7.3	
November 29, 2000	N/A	Recycle to preg pond	0.09	7.3	
November 30, 2000	N/A	Recycle to preg pond	0.09	7.3	300
December 1, 2000	N/A	Recycle to preg pond	0.09	7.3	
December 4, 2000	N/A	Recycle to preg pond	0.09	7.3	
December 5, 2000	N/A	Recycle to preg pond	0.09	7.3	
December 6, 2000	N/A	Recycle to preg pond	0.09	7.3	300
December 7, 2000	N/A	Recycle to preg pond	0.09	7.3	
December 8, 2000	N/A	Recycle to preg pond	0.09	7.3	
December 11, 2000	N/A	Recycle to preg pond	0.09	7.3	
December 12, 2000	N/A	Recycle to preg pond	0.09	7.3	300
December 13, 2000	N/A	Recycle to preg pond	0.09	7.3	
December 14, 2000	N/A	Recycle to preg pond	0.09	7.3	
December 15, 2000	N/A	Recycle to preg pond	0.09	7.3	
December 18, 2000	N/A	Recycle to preg pond	0.08	6.1	
December 19, 2000	N/A	Recycle to preg pond	0.08	6.1	
December 20, 2000	N/A	Recycle to preg pond	0.08	6.1	290
December 21, 2000	N/A	Recycle to preg pond	0.08	6.1	
December 22, 2000	N/A	Recycle to preg pond	0.08	6.1	
December 26, 2000	N/A	Recycle to preg pond	0.07	4.9	
December 27, 2000	N/A	Recycle to preg pond	0.07	4.9	
December 28, 2000	N/A	Recycle to preg pond	0.07	4.9	290
December 29, 2000	N/A	Recycle to preg pond	0.07	4.9	
	N/A	Recycle to preg pond	0.07	4.9	200 Hart 2
January 2, 2001	N/A N/A	Recycle to preg pond	0.07	4.9	2.99 14 25 13
January 3, 2001		Recycle to preg pond	0.07	4.9	280
January 4, 2001	N/A	Recycle to preg pond	0.06	3.6	
January 5, 2001	N/A	Pump was off	0.06	3.6	
January 8, 2001	N/A		0.06	3.6	
January 9, 2001	N/A	Recycle to preg pond		3.6	285
January 10, 2001	N/A	Recycle to preg pond	0.06	3.0	200

KEY N/R = Not Recorded N/A = Not Avaliable

January 11, 2001	N/A	Recycle to preg pond	0.06	3.6	
January 12, 2001	N/A	Recycle to preg pond	0.06	3.6	
January 15, 2001	N/A	Pump was off	0.06	3.6	
January 16, 2001	N/A	Recycle to preg pond	0.06	3.6	
January 17, 2001	N/A	Recycle to preg pond	0.06	3.6	270
January 18, 2001	N/A	Recycle to preg pond	0.06	3.6	270
January 19, 2001	N/A	Recycle to preg pond	0.06		
January 22, 2001	N/A	Recycle to preg pond	0.06	3.6	
January 23, 2001	N/A	Recycle to preg pond	0.06	3.6	
January 24, 2001	N/A	Recycle to preg pond	0.06	3.6	200
January 25, 2001	N/A	Recycle to preg pond	0.06	3.6	290
January 26, 2001	N/A	Recycle to preg pond		3.6	
January 29, 2001	N/A	Recycle to preg pond	0.06	3.6	
January 30, 2001	N/A		0.06	3.6	
January 31, 2001	N/A	Recycle to preg pond Recycle to preg pond	0.06	3.6	205
February 1, 2001	N/A		0.06	3.6	285
February 2, 2001	N/A	Recycle to preg pond	0.06	3.6	
February 5, 2001	N/A	Recycle to preg pond	0.06	3.6	
February 6, 2001	N/A	Recycle to preg pond	0.06	3.6	
February 7, 2001	N/A	Recycle to preg pond Recycle to preg pond	0.06	3.6	005
February 8, 2001	N/A	Recycle to preg pond	0.06	3.6	285
February 9, 2001	N/A		0.06	3.6	
February 12, 2001	N/A	Recycle to preg pond	0.06	3.6	
February 13, 2001	N/A	Recycle to preg pond	0.06	3.6	
February 14, 2001	N/A	Recycle to preg pond	0.06	3.6	000
February 15, 2001	N/A	Recycle to preg pond	0.06	3.6	320
February 16, 2001	N/A	Recycle to preg pond	0.06	3.6	
February 17, 2001	N/A	Recycle to preg pond	0.06	3.6	
February 19, 2001	N/A	Recycle to preg pond	0.06	3.6	10 - 10 A A A A A A A A A A A A A A A A A A
February 20, 2001	N/A	Recycle to preg pond	0.06	3.6	8-10 NS
February 21, 2001	N/A	Recycle to preg pond	0.06	3.6	
February 22, 2001	N/A N/A	Recycle to preg pond	0.06	3.6	0.10
February 23, 2001	N/A N/A	Recycle to preg pond	0.06	3.6	310
February 26, 2001	N/A N/A	Recycle to preg pond Recycle to preg pond	0.06	3.6	
February 27, 2001	N/A N/A		0.06	3.6	
February 28, 2001	N/A N/A	Recycle to preg pond	0.06	3.6	200
March 1, 2001	N/A N/A	Recycle to preg pond	0.06	3.6	290
March 2, 2001	N/A N/A	Recycle to preg pond	0.06	3.6	
March 5, 2001	N/A N/A	Recycle to preg pond	0.06	3.6	
March 6, 2001	N/A N/A	Recycle to preg pond	0.06	3.6	
March 7, 2001	N/A N/A	Recycle to preg pond	0.06	3.6	
March 8, 2001	N/A N/A	Recycle to preg pond	0.06	3.6	000
March 9, 2001	N/A N/A	Recycle to preg pond	0.06	3.6	280
March 12, 2001	N/A	Recycle to preg pond	0.06	3.6	
March 13, 2001	N/A N/A	Recycle to preg pond	0.06	3.6	
March 14, 2001		Recycle to preg pond	0.06	3.6	VI-181
March 15, 2001	N/A	Recycle to preg pond	0.06	3.6	e 1 14 P
March 16, 2001	N/A	Recycle to preg pond	0.06	3.6	
March 10, 2001	N/A	Recycle to preg pond	0.06	3.6	280

			OITT ILLD OA		
March 19, 2001	N/A	Recycle to preg pond	0.06	3.6	
March 20, 2001	N/A	Recycle to preg pond	0.06	3.6	
March 21, 2001	N/A	Recycle to preg pond	0.06	3.6	
March 22, 2001	N/A	Recycle to preg pond	0.06	3.6	280
March 23, 2001	N/A	Recycle to preg pond	0.06	3.6	
March 26, 2001	N/A	Recycle to preg pond	0.06	3.6	
March 27, 2001	N/A	Recycle to preg pond	0.06	3.6	†
March 28, 2001	N/A	Recycle to preg pond	0.06	3.6	
March 29, 2001	N/A	Recycle to preg pond	0.06	3.6	290
March 30, 2001	N/A	Recycle to preg pond	0.06	3.6	
April 2, 2001	N/A	Recycle to preg pond	0.06	3.6	<u> </u>
April 3, 2001	N/A	Recycle to preg pond	0.06	3.6	
April 4, 2001	N/A	Recycle to preg pond	0.06	3.6	
April 5, 2001	N/A	Recycle to preg pond	0.06	3.6	270
April 6, 2001	N/A	Recycle to preg pond	0.06	3.6	
May, 2001 Week 1	N/A	Drain Field	N/A	3.6	N/A
May, 2001 Week 2	N/A	Drain Field	N/A	3.6	N/A
May, 2001 Week 3	N/A	Drain Field	N/A	3.6	N/A
May, 2001 Week 4	N/A	Drain Field	N/A	3.6	N/A
June 6, 2001	N/A	Drain Field	N/A	3.6	N/A
June 13, 2001	N/A	Drain Field	N/A	3.6	N/A
June 20, 2001	N/A	Drain Field	N/A	3.6	N/A
June 27, 2001	N/A	Drain Field	N/A	3.6	N/A
July 3, 2001	N/A	Drain Field	N/A	3.6	N/A
July 11, 2001	N/A	Drain Field	N/A	3.6	N/A
July 18, 2001	N/A	Drain Field	N/A	3.6	N/A
July 23, 2001	N/A	Drain Field	N/A	3.6	N/A
August 1, 2001	N/A	Drain Field	N/A	3.0	N/A
August 8, 2001	N/A	Drain Field	N/A	3.0	N/A
August 15, 2001	N/A	Drain Field	N/A	3.0	N/A
August 21, 2001	N/A	Drain Field	N/A	3.0	N/A
August 29, 2001	N/A	Drain Field	N/A	3.0	N/A
October 17, 2001	N/A	Drain Field	N/A	3.0	N/A
October 24, 2001	N/A	Drain Field	N/A	2.8	N/A
November 1, 2001	N/A	Drain Field	N/A	2.8	N/A
November 7, 2001	N/A	Drain Field	N/A	2.8	N/A
November 12, 2001	N/A	Drain Field	N/A	2.5	N/A
November 20, 2001	N/A	Drain Field	N/A	2.5	N/A
December 1, 2001	N/A	Drain Field	N/A	2.2	N/A
December 6, 2001	N/A	Drain Field	N/A	2.2	N/A
December 15, 2001	N/A	Drain Field	N/A	2.2	N/A
December 22, 2001	N/A	Drain Field	N/A	2.4	N/A
December 29, 2001	N/A	Drain Field	N/A	2.6	N/A
January 2, 2002	N/A	Drain Field	N/A	2.8	N/A
January 9, 2002	N/A	Drain Field	N/A	2.8	N/A
			 		

This page is a reference page used to track documents internally for the Division of Oil, Gas and Mining
Mine Permit Number Morson Mine Name Tintic Project Operator Orth Lily Date March 6, 2002 TO FROM
CONFIDENTIALBOND CLOSURELARGE MAPS _XEXPANDABLEMULTIPUL DOCUMENT TRACKING SHEETNEW APPROVED NOIAMENDMENT _OTHER
Description YEAR-Record Number
NOI \(\sum \) IncomingOutgoingInternalSuperceded
Closure Report
NOIIncomingOutgoingInternalSuperceded
NOIIncomingOutgoingInternalSuperceded
NOIIncomingOutgoingInternalSuperceded
TEXT/ 81/2 X 11 MAP PAGES11 X 17 MAPSLARGE MAP COMMENTS:
CC: